

Distributed by: BEST MATERIALS LLC  
Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014  
www.BestMaterials.com Email: Sales@BestMaterials.com

### Basic Use

Eternabond A-Seal Tape is designed for use on metal buildings, trailer/RV roofs and sides, drain pans, drain pipes, ductwork, boats, canoes, and as a protective coating for surfaces where abrasion and corrosion resistance is required. A-Seal seals to itself so it can be cut and folded around an object, as if wrapping a present.

### Composition

Eternabond A-Seal utilizes EternaBond's advanced MicroSealant™ Technology, a 100% solids formulation of synthetic resins, thermoplastics and non-curing rubber (non butyl) with a built in primer. It is then bonded to a thick, 4-mil aluminum metal backing. The adhesive coating is protected by a thin, siliconized release liner, which is removed prior to application.

### Technical Data

Application temp	Above -10°F (-23°C)
Total thickness	20 mils (0.51 mm)
Adhesion	>17lbs/in width (to unprimed aluminum)
Flexibility	Excellent
Tensile strength	>1000 psi
Weathering	Excellent resistance to wind, rain erosion, and ultra violet rays.
Sizes available	2", 4", 6", 12" X 50' rolls
Shelf life	Up to 5 years

### Surface Preparation

Surface must be clean and dry. Moisture, dust, dirt, or other foreign matter should be removed. Remove oil and grease, etc. with a suitable cleaner. Remove salt and other contaminants.

### Application

Cut tape to desired lengths and shapes. Remove the release liner to expose the adhesive coating. Press tape firmly to surface to obtain conformability and adhesion. Apply pressure aggressively by hand, or preferably using a steel roller. When applied to surfaces, which permit spiral wrapping, allow for a half inch overlap to insure seal. Installation to temperatures as low as -10°F is possible by treating the surface with Eternabond EternaPrime prior to installation and allowing A-Seal to remain at room temperature (+ 60°F) before applying.

Distributed by:  
BEST MATERIALS LLC  
Phoenix AZ  
Ph: 800-474-7570, 602-272-8128  
Fax: 602-272-8014  
Email: sales@bestmaterials.com  
www.bestmaterials.com

**ETERNABOND**

**ETERNABOND, Inc.**  
Hawthorn Woods, IL, USA

**ETERNABOND™**  
**A•Seal™**

**For use on virtually all roofs, walls, floors, gravity tanks, troughs, etc...UV stable and moisture tight, it provides an air and vapor barrier. And the thick, 4 mil aluminum backing combined with a thinner layer of EternaBond's advanced MicroSealant™ creates an extremely hard surface.**

**A•Seal bonds to a wide range of materials including carbon steel, aluminum, galvanized steel, aluminum foil, gypsum board, wood, rubber, tar, polyethylene, polypropylene, polystyrene, fiberglass, brick, concrete, masonry, rubber, thermoplastics, single-ply roofing, etc.**

**ETERNABOND A•Seal™**