


Technical Data Sheet

www.pamfast.com



**Truss Head w/ Under Cut, PAMDrive Recess
Fine & 2/3 Coarse Thread, Sharp Point, Hardened
CDS10212 #10 x 2-1/2" Magni #57 Coating, with Wax
Brown, Gray, Tan, Red
(1000 hour salt spray test and Kesternich Test)
PAM Fastening Technology, Inc.**

Head Diameter	7.3 ~ 7.8mm
Major Diameter	4.5 ~ 4.7mm
Minor Diameter	3.0 ~ 3.2mm
Length	63.5 ± 1.50mm
Access Depth	2.35 ~ 2.70mm
Wire Diameter	3.8mm
Surface Hardness	450 ~ 700 HV
Core Hardness	380 ~ 450 HV
Breaking Torque	MIN 65 KG-CM
Penetration	-
Withdrawal	-
Material	C1022
Salt Spray Test (ASTM B-117)	1000 hours
Bent Testing	15°↑

All fasteners manufactured for PAM Fastening Technology, Inc. are of a non-chemical hazardous nature.

Important Notice: The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply.

PAM[®]

PAM Fastening Technology, Inc.

2120 Gateway Blvd. • Charlotte, NC 28208

704/394-3141 • Fax 704/394-9339 • email: sales@pamfast.com