

# Technical Data Sheet



Willamette Valley Company

Partnering through service,  
innovation, and integrity

# POLYQuik® EJC-25

Distributed by: BEST MATERIALS®  
Ph: 800-474-7570, 602-272-8128  
www.BestMaterials.com  
Email: Sales@BestMaterials.com

Expansion Joint Compound with 25% movement capability

## DESCRIPTION

POLYQuik® EJC-25 is a rapid setting, 2-component, self-leveling joint sealant with excellent adhesion and durability. EJC-25 has demonstrated superior long-term performance for joint sealant applications with small to moderate movement requirements.

## WHERE TO USE

- Airports
- Bridge Joints
- Highways
- Parking Decks
- Sidewalks
- Any Joint with  $\pm 25\%$  Movement

## FEATURES AND BENEFITS

- **Rapid Cure**— as little as 1 hour return to service
- **Self-Leveling**—flows easily, completely fills joint
- **Flexible at Freezing Temperatures**
- **ASTM C920** –Type M, Grade P, Class 25
- **100% Solids, 0 VOC**—environmentally friendly
- **1:1 Ratio by Volume**—easy application

## PACKAGING

20-oz. (600 mL) Cartridge  
50-oz. (1500 mL) Cartridge  
5-Gallon (19 Liter) Pail  
50-Gallon (190 Liter) Drum

## COLORS

Black, Gray

## SHELF LIFE

1 year when properly stored.

## STORAGE

Store and ship this product in clean, dry, low-humidity, and shaded or covered environments between 50 and 90°F (10-32°C)

## TYPICAL PROPERTIES

	Result	ASTM
Solids Content	100%, SCAQMD compliant	D2369
Cyclic Movement Capabilities, Class 25	Passes 10 cycles, no loss of adhesion or cohesion	C719, C920 (4.1.5)
Tack-Free Time	45 minutes	C679
Concrete Adhesion, primed with POLYQuik® PolyPrime	$\geq 50$ pli (8.8 N/mm)	C794
Concrete Adhesion, unprimed	10 pli (1.8 N/mm)	C794
FastPatch Adhesion, unprimed	$\geq 40$ pli (7.0 N/mm)	C794
Hardness	45-55 Shore A	C661
Mix Ratio (by Volume)	1:1	-

---

### APPLICATION INSTRUCTIONS

---

For instructions on how to handle and apply POLYQuik® EJC-25 from cartridges, please refer to [POLYQuik® Cartridge Instructions](#).

For instructions on how to apply POLYQuik® EJC-25 from bulk containers with WVCO/Pre-Tec meters, training will be provided. If you have specific questions related to your dispensing equipment, please contact your WVCO representative or customer support.

For joint design and installation instructions, please refer to:

[POLYQuik® Joint Design and Installation Guidelines](#)

---

### ESTIMATED COVERAGE

---

Coverage chart assumes appropriate backer rod placement to provide 1/8 inch (3 mm) recessed sealant fill and 1/2 inch (13mm) sealant depth for the entire joint length.

Joint Width	Linear feet (meter) coverage per 20 oz (600mL) cartridge	Linear feet (meter) coverage per gallon (3.8 Liter)
0.5 in (13 mm)	10 (3.0)	64 (19.5)
1.0 in (25 mm)	5.5 (1.7)	35 (10.7)
1.5 in (38 mm)	3.75 (1.1)	24 (7.3)
2.0 in (51 mm)	2.9 (0.9)	18.3 (5.6)

---

### HEALTH AND SAFETY

---

Before handling, you should become familiar with the Safety Data Sheet (SDS) regarding the risks and safe use of this product. To obtain an SDS, please call 800-333-9826 or send an email to: [msds@wilvaco.com](mailto:msds@wilvaco.com)

---

#### DISCLAIMER OF WARRANTY

TEST RESULTS ARE TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION AND SHOULD NOT BE TREATED AS SPECIFICATIONS. WHILE ALL THE INFORMATION PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE RELIABLE AND TO REPRESENT THE BEST AVAILABLE DATA ON THESE PRODUCTS, NO GUARANTEE, WARRANTY, OR REPRESENTATION IS MADE, INTENDED, OR IMPLIED AS TO THE CORRECTNESS OR SUFFICIENCY OF ANY INFORMATION, OR AS TO THE SUITABILITY OF ANY CHEMICAL COMPOUNDS FOR ANY PARTICULAR USE, OR THAT ANY CHEMICAL COMPOUNDS OR USE THEREOF ARE NOT SUBJECT TO A CLAIM BY A THIRD PARTY FOR INFRINGEMENT OF ANY PATENT OR OTHER INTELLECTUAL PROPERTY RIGHT. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE SUITABILITY OF ANY PRODUCT FOR ITS INTENDED USE. PROPER APPLICATION IS THE RESPONSIBILITY OF THE USER. AS WITH ANY PRODUCT THE USE OF THIS PRODUCT IN A GIVEN APPLICATION MUST BE TESTED (INCLUDING BUT NOT LIMITED TO FIELD TESTING) IN ADVANCE BY THE USER TO DETERMINE SUITABILITY. TESTING IS THE REQUIREMENT OF BOTH ENGINEERS AND CONTRACTORS ALIKE. WVCO DOES NOT WARRANT THE APPLICATION UNDER ANY OR ALL CIRCUMSTANCES.

