

Distributed by: BEST MATERIALS LLC
Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014
www.BestMaterials.com Email: Sales@BestMaterials.com



SPECIFICATION DATA

1. Product Name

Versi-Tite® 12 oz. and 24 oz. Foam Sealant

2. Manufacturer

RHH FOAM SYSTEMS, INC.
17100 W. Victor Road | New Berlin, WI 53151

3. Product Description

Versi-Tite® is a one component foam sealant for small gaps and crevices. It is dispensed as a caulking bead, with an approximate 200% expansion rate. It is a moisture cured product using humidity to dry. It is a UL Classified – File #R13919 Caulking and Sealant.

4. Technical Data

Versi-Tite® 12 oz. and 24 oz. Foam Sealant has the following physical properties:

DENSITY (ASTM D1622): 1.25 – 1.4 lb/ft³

R FACTOR (ASTM C177): 4.0 to 5.0/inch

AIR BARRIER PROPERTIES (ASTM E283):

At 6.24 psf <0.01 cfm/ft²

At 1.57 psf <0.0025 cfm/ft²

CLOSED CELL CONTENT (ASTM D2856): >70%

TACK FREE TIME:

At 70°F, 40% RH Approx. 10 minutes

CUTTABLE:

1" bead at room conditions <1 hour

CURE TIME: 12-24 hours

VOC CONTENT: <20% (low emitting)

FLAMESPREAD (ASTM E84): 25

SMOKE DEVELOPED (ASTM E84): 50

YIELD:

	<u>12 oz.</u>	<u>24 oz.</u>
1/4" bead	1,644 linear ft	3,288 linear ft
3/8" bead	730 linear ft	1,460 linear ft
1/2" bead	411 linear ft	822 linear ft
Volume	.56 cubic ft	1.12 cubic ft