


12075 OPEN-EDGE GUARDRAIL

OPEN-EDGE GUARDRAIL #12075

- Nail plate with guardrail holder
- Provides fall protection, slide-guard and toeboard
- Installs and removes like a roof bracket
- Interleaves with shingles
- Use on rake-edges of any pitch & eaves under 4/12
- Slotted nail-holes for 16" or 24" rafter spacing
- Tested in a lab to meet OSHA's 2011 regulations
- Meets OSHA's 200lbs requirement both out & down
- Maximum spacing 8' apart (used with construction grade lumber)
- Can be used in all phases of construction
- Powder coated safety yellow
- Made in America

Use Acro's exclusive 12075 Open-edge Guardrail Brackets on rake-edges of any pitch and eave-edges under 4/12 pitch; in conjunction with Acro's proven 12070 Steep-pitch Guardrail Brackets along the eave-edges from 4/12 to 16/12 to form the backbone of a complete residential guardrail system. Two sets of 2 x 4's are used with a toe board to form a continuous guardrail around the entire roof edge. This innovative full guardrail system is easy to install, move & remove without damaging shingles on any roof 16/12 pitch and under. This allows the guardrails to be put up early in the new construction process or even prior to shingle removal on a tear off; and easily moved without having to take the system down. Acro now offers a way to comply fully with OSHA's 2011 requirements without the need of any other impeding safety equipment, Use your regular ACRO Building Systems Roof Brackets on the balance of the roof for shingle installation.



Please visit our website for install instructions, product videos and the benefits of passive fall protection systems.

Distributed by: [BEST MATERIALS LLC](#)

Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014

www.BestMaterials.com Email: Sales@BestMaterials.com

12075 Open-Edge Guardrail			
Model #	Description	Lbs.	Dimensions
12075	Complete System (w/ post)	11	43"x25"x12"
12055	Replacement Post	4	42"x5"x1"