



NOTES:

1. REMOVE ALL LEAD AND OTHER FLASHING.
2. PIPE SEAL MUST HAVE INTACT RIB AT TOP EDGE, REGARDLESS OF PIPE DIAMETER.
3. DECK FLANGES OF THE MOLDED PIPE SEAL SHALL NOT BE OVERLAPPED, CUT OR APPLIED OVER ANY ANGLE CHANGE.
4. 60-MIL THICK CURED EPDM FLASHING OVERLAY AT CUT IN FIELD MEMBRANE MUST EXTEND 3 INCHES BEYOND MOLDED PIPE SEAL FLASHING FLANGE ON 3 SIDES AND WITHIN 1 INCH OF THE EDGE OF THE FIELD MEMBRANE AS SHOWN ABOVE.
5. CENTER 9" WIDE PRESSURE-SENSITIVE FLASHING OVER THE MEMBRANE SPLICE EDGE AND EXTEND 3" BEYOND THE MEMBRANE OVERLAY AS SHOWN ABOVE.
6. SEAL ALL EDGES WITH LAP SEALANT AS SHOWN ABOVE.

30-YEAR WARRANTY

X3A-8

SURE-SEAL® PRESSURE-SENSITIVE MOLDED PIPE SEAL

CARLISLE
Carlisle SynTec