

DISTRIBUTED BY

Best MATERIALS.com[®]

3M Science.
Applied to Life.™

Protecta[®] Rebel™

Leading Edge Self-Retracting Lifelines

Introducing the Rebel Leading Edge Family

Now tie off at foot level with the 20', 33', 50', and 66' Rebel Leading Edge Self-Retracting Lifelines. We've expanded our product line to better meet your jobsite needs. These products are put through extensive sharp-edge testing to ensure protection against sharp, abrasive and leading edges found at construction sites.



now proudly
part of 3M:



With All The Features and Benefits You Trust, In Different Sizes


Lightweight, Durable and Affordable

The leading edge cable unit leverages our impressive Rebel technologies to continue to set the standard for performance and value.

Part #	3590540	3590543	3590546	3590548
Cable Length	20 ft	33 ft	50 ft	66 ft
L x W x H	42" x 10" x 4.5"	42" x 11" x 4.5"	46" x 13" x 5.5"	46" x 13" x 5.5"
Weight	17 lbs	19 lbs	25 lbs	26 lbs
*Cover Part #	3590010	35900011	3590012	3590012

Self-Retracting Lifeline Covers

Protect labels from everyday abuse on the jobsite.
(See part numbers above)



Carabiner Included
Unit is ready for connection to anchor point.

Top Swivel
Limits lifeline twisting.

Thermoplastic Housing
Thermoplastic is lightweight, compact and durable.

Model Shown:
3590540 (US)

Ergonomic Carrying Handle
Built-in handle adds comfort and ease-of-use when connecting to an anchor point.

Wire Rope
7/32 in. (5.6 mm) galvanized 5,600 lb. (2,540 kg) min tensile strength.

Energy Absorber
Fully integrated into lifeline. Specifically designed for foot level tie-off.

Standards
OSHA 1926.502, OSHA 1910.66, **ANSI Z359.14.**

310 lb. (141 kg) capacity and 1,350 lbs. (6kn) maximum arresting force.

