

PRODUCT SPECIFICATIONS

7035 Journeyman FLEX Steel

For more information
Or to buy this product
[Click here](#)

Journeyman FLEX Steel, Belted Construction

The Journeyman FLEX Steel continues the tradition of uncompromising performance you've come to rely on every day. New design elements have been incorporated into this jobsite workhorse for improved comfort, durability and reliability. The Journeyman FLEX Steel continues the tradition of keeping your team safe.

Features

- Durable alloy steel hardware
- Three D-rings; One Back and Two Hip
- Premium breathable padded air mesh shoulder yoke
- Quick Connect Visi-lock chest buckle
- 18" countoured leg pads
- Friction torso adjusters
- Tongue buckle Leg Adjusters
- Non-slip dorsal D-ring adjustment
- 6" torso-sewn Waist Support Positioning Pad

MATERIALS SPECIFICATIONS	
Webbing:	Polyester; Min. 5,000 lbs. tensile strength
Keepers:	Plastic
D-Rings:	Steel; Min. 5,000 lbs. tensile strength
Buckles/Adjusters:	Steel; Min. 3,375 lbs. tensile strength
Grommets:	Brass
Shoulder Adjusters:	Friction
Foam:	Open cell High density internal foam

PERFORMANCE SPECIFICATIONS	
Maximum Working Load:	425 lbs.
ANSI User Capacity:	130 to 310 lbs. Max.
OSHA User Capacity:	130 to 425 lbs. Max.

SIZES	
Style #	Description
PN 7035XS	X Small
PN 7035S	Small
PN 7035M	Medium
PN 7035L	Large
PN 7035XL	X Large
PN 70352XL	XX Large
PN 70353X	XXX Large
PN 70354X	XXXX Large

For shoulder and waist size ranges, please see Size Charts page.



7035
Journeyman FLEX Steel

RELEVANT STANDARDS	
ANSI:	Z359.11-2014
OSHA:	1926.502, 1910.66

WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a shock absorbing lanyard to a side D-Ring.