

# PRODUCT SPECIFICATIONS



## Contractor 20' SRL

## #727620

### Features

- Rugged, lightweight design. Full inertial brake mechanism.
- Load-indicating swivel carabiner with 3,600 lb. gate.
- Rated for one worker up to 310 lbs.
- Meets ANSI Z359.1-2007, ANSI A10.32 and applicable OSHA requirements.

### Material Specifications

<b>Cable:</b>	<i>3/16", 7X19 galvanized steel</i>
<b>Connector:</b>	<i>Alloy Steel; Min. 5,000 lbs. tensile strength</i>
<b>Connector Gates:</b>	<i>Alloy Steel; Min. 3,600 lbs. front load and side load</i>

### Performance Specifications

<b>Tensile Strength:</b>	<i>3,000 lbs.</i>
<b>Max. Capacity:</b>	<i>310 lbs.</i>
<b>Max. Freefall:</b>	<i>24"</i>
<b>Avg. Arrest Force:</b>	<i>916 LBS</i>
<b>Max. Elongation:</b>	<i>29"</i>
<b>ANSI:</b>	<i>Class B</i>

### Relevant Standards

<b>OSHA:</b>	<i>CFR1926.502, CFR1910.66</i>
<b>ANSI:</b>	<i>Z359.14-2012</i>

### Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a Restraint Lanyard to the front or side D-Rings.



For more information  
Or to buy this product  
[Click here](#)