

PRODUCT SPECIFICATIONS

60' 3-Way Recovery Unit

#7281

Features

- Fully functional SRL with inertial brake.
- Includes rescue winch for use in confined space rescue/evacuation.
- Includes load-indicating swivel carabiner.
- Leg bracket sold separately
- For use with 7276 Tripod

Material Specifications

- Housing/drum:** *Aluminum alloy.*
- Cable:** *3/16', 7x19 galvanized steel.*
- Connector Gates:** *Alloy Steel; Min. 3,600 lbs. front and side load.*

Performance Specifications

- Tensile Strength:** *Min. 3,000 lbs.*
- Max. Capacity:** *310 lbs.*
- Max. Freefall:** *2 feet*
- Average Arrest Force:** *Less than 900 lbs.*
- Max. Elongation:** *42 inches*

Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*
- ANSI:** *A10.32-2004*
Z359.1-2007

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- For use in overhead applications - **maximum allowable freefall = 2 feet!**
- Not for use in in confined space entry and retrieval - for rescue only.

For more information
Or to buy this product
[Click here](#)

