

# PRODUCT SPECIFICATIONS

## 50' Vertical Lifeline

8150

### Features

- Anchor-end snap hook and trailing end thimble.
- 5/8" polyester rope has a tensile strength of 8,500 lbs.
- Superior resistance to abrasion and UV light.
- Superior hockle resistance.
- Five-tuck splice for superior strength and safety.
- Exclusive steel thimble resist wear and extend the life of the line.
- Protective PVC shrink tubing protects the spliced ends.

### Material Specifications

<b>Rope:</b>	<i>5/8" Polyester; Min. 5,600 lbs. tensile strength</i>
<b>Connectors:</b>	<i>Alloy Steel; Min. 5,000 lbs. tensile strength</i>
<b>Thimble:</b>	<i>Alloy Steel</i>
<b>Connector Gates:</b>	<i>Alloy Steel; Min. 3,600 lbs. front and side load</i>

### Performance Specifications

<b>Tensile Strength:</b>	<i>Min. 5,600 lbs.</i>
<b>Max. Capacity:</b>	<i>310 lbs.</i>

### Relevant Standards

<b>OSHA:</b>	<i>CFR1926.502, CFR1910.66</i>
<b>ANSI:</b>	<i>A10.32-2004</i>

### Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

