

PRODUCT SPECIFICATIONS

Vertical Lifeline

81xxDH

Features

- Snap hook at the anchor-end at both end.
- Superior resistance to abrasion and UV light.
- Superior hockle resistance.
- Five-tuck splice for superior strength and safety.
- Exclusive steel thimble resist wear and extend the life of the line.
- Protective PVC shrink tubing protects the spliced ends.

Material Specifications

| | |
|-------------------------|---|
| Rope: | <i>5/8" Polyester; Min. 5,600 lbs. tensile strength</i> |
| Connectors: | <i>Alloy Steel; Min. 5,000 lbs. tensile strength</i> |
| Thimble: | <i>Alloy Steel</i> |
| Connector Gates: | <i>Alloy Steel; Min. 3,600 lbs. front and side load</i> |

Performance Specifications

| | |
|--------------------------|------------------------|
| Tensile Strength: | <i>Min. 5,600 lbs.</i> |
| Max. Capacity: | <i>310 lbs.</i> |

Relevant Standards

| | |
|--------------|--|
| OSHA: | <i>CFR1926.502, CFR1910.66</i> |
| ANSI: | <i>A10.32-2004, Z359.1-2007 Z359.12-2009</i> |

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

