



## Standard Sizes and Shipping Weights Floor Access Doors - With Drainage Channel Frame

APPLICATION	SIZE		ALUMINUM			STEEL		
	(width x length)		Model#	Weight		Model#	Weight	
	inches	mm		lbs.	kg.		lbs.	kg.
Reinforced for a 300 lb/ft <sup>2</sup> (1464 kg/m <sup>2</sup> ) Live Load	24 X 24	610 X 610	J-1AL	65	29	J-1	179	81
	30 X 30	762 X 762	J-2AL	88	40	J-2	231	105
	36 X 30	914 X 762	J-3AL	97	44	J-3	274	124
	36 X 36	914 X 914	J-4AL	108	49	J-4	300	136
	42 X 42	1067 X 1067	J-5AL	135	61	J-5	402	182
	30 X 48	762 X 1219	J-6AL	115	52	J-6	317	144
	36 X 48	914 X 1219	J-7AL	127	58	J-7	389	176
	30 X 60	762 X 1524	J-8AL	152	69	J-8	373	169
	36 X 60	914 X 1524	J-9AL	160	73	J-9	462	210
	36 X 72	914 X 1829	J-10AL	188	85	J-10	498	226
	48 X 30	1219 X 762	JD-1AL	145	66	JD-1	365	166
	48 X 48	1219 X 1219	JD-2AL	173	78	JD-2	498	226
	48 X 72	1219 X 1829	JD-3AL	234	106	JD-3	652	296
	60 X 60	1524 X 1524	JD-4AL	241	109	JD-4	663	301
Reinforced for an AASHTO H-20 Wheel Load	24 X 24	610 X 610	J-1ALH20	110	50	J-1H20	250	113
	30 X 30	762 X 762	J-2ALH20	124	56	J-2H20	350	159
	36 X 30	914 X 762	J-3ALH20	165	75	J-3H20	425	193
	36 X 36	914 X 914	J-4ALH20	174	79	J-4H20	490	222
	42 X 42	1067 X 1067	J-5ALH20	235	107	J-5H20	635	288
	48 X 30	1219 X 762	JD-1ALH20	201	91	JD-1H20	532	241
	48 X 48	1219 X 1219	JD-2ALH20	293	133	JD-2H20	815	370
	48 X 72	1219 X 1829	JD-3ALH20	485	220	JD-3H20	1235	560
	60 X 60	1524 X 1524	JD-4ALH20	500	227	JD-4H20	1180	535

Models with "D" in the model # indicate double leaf configuration



In addition to the standard sizes shown above, custom fabricated products are available to meet your special size requirements. Contact Best Materials for more information.