

Distributed by: BEST MATERIALS ® LLC
 Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014
www.BestMaterials.com Email: Sales@BestMaterials.com

Part Number	Diameter in in.	Length in ft.	Miniumem Break Strength in lbs.	Approximate Density lbs./100 ft.	Approximate Package Weight
CDB120600	3/8	600	5,000	4.5	27.0
CDB121200	3/8	1,200	5,000	4.5	54.0
CDB140600	7/16	600	7,500	6.1	37.0
CDB141200	7/16	1,200	7,500	6.1	74.0
CDB160300	1/2	300	9,500	8.1	25.0
CDB160600	1/2	600	9,500	8.1	49.0
CDB161200	1/2	1,200	9,500	8.1	98.0
CDB180300	9/16	300	16,150	10.0	30.0
CDB180600	9/16	600	16,150	10.0	60.0
CDB181200	9/16	1,200	16,150	10.0	120.0
CDB200300	5/8	300	18,000	13.0	39.0
CDB200600	5/8	600	18,000	13.0	78.0
CDB201200	5/8	1,200	18,000	13.0	156.0
CDB240300	3/4	300	26,000	18.0	54.0
CDB240600	3/4	600	26,000	18.0	108.0
CDB241200	3/4	1,200	26,000	18.0	216.0
CDB280300	7/8	300	32,000	25.0	75.0
CDB280600	7/8	600	32,000	25.0	150.0
CDB281200	7/8	1,200	32,000	25.0	300.0
CDB300300	1	300	42,000	32.0	96.0
CDB300600	1	600	42,000	32.0	192.0
CDB301200	1	1,200	42,000	32.0	384.0
CDB320600	1-1/8	600	47,900	46.0	276.0
CDB321200	1-1/8	1,200	47,900	46.0	552.0
CDB340600	1-1/4	600	56,200	54.0	324.0
CDB341200	1-1/4	1,200	56,200	54.0	648.0
CDB360600	1-1/2	600	73,380	75.0	450.0
CDB361200	1-1/2	1,200	73,380	75.0	900.0