

## Termination and Batten Bars

.050", .075", .090", .100", .125", 6" OC

For wall termination applications

- Manufactured from specially extruded aluminum without sharp edges.
- Reinforced strengthening ribs allow for use in high wind applications.


Distributed by: BEST MATERIALS®  
 Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014  
[www.BestMaterials.com](http://www.BestMaterials.com) Email: [Sales@BestMaterials.com](mailto:Sales@BestMaterials.com)

## Application

**Ribbed Term Bar w/ Lip**

Use with:

- #14 Dekfast Fastener
- #15 Dekfast Fastener
- Zac Anchor
- Zinc Nailin
- Dekspike™




Dimensions: .050" (edge) x .075" (ribs) x 1" wide x 10' long  
 Holes: .260" x .380" slotted at 6" O.C. spacing  
 Material: Extruded Aluminum

**Ribbed Term Bar**

Use with:

- #14 Dekfast Fastener
- #15 Dekfast Fastener
- Zac Anchor
- Zinc Nailin
- Dekspike





Dimensions: .075 (edge) x .100" (ribs) x 1" wide x 10' long  
 Holes: .260" x .380" slotted at 6" O.C. spacing  
 Material: Extruded Aluminum

**Lip & Ball Term Bar**

Use with:

- #14 Dekfast Fastener
- #15 Dekfast Fastener
- Zac Anchor
- Zinc Nailin
- Dekspike





Dimensions: .088" x 1" wide x 10' long  
 Holes: .280" x .380" slotted at 6" O.C. spacing  
 Material: Extruded Aluminum

**Gravel Stop/Drain Bar**

Use with:

- #14 Dekfast Fastener
- #15 Dekfast Fastener
- Zac Anchor
- Zinc Nailin
- Dekspike



Dimensions: .110" x 3.50" wide x 10' long  
 Holes: .300" x 1.62" slotted at 4" O.C. spacing  
 Material: Extruded Aluminum

**Notes**

Dimensions are nominal inches unless noted. Ultimate values listed are the result of laboratory testing. Pull out (pounds ultimate) strength values may vary from tabulated loads depending upon the uniqueness of the application. The specific job conditions should be considered and appropriate safety factors applied when specifying the proper fasteners.

Buy Now Here:

<http://www.bestmaterials.com/term-bars-518.html>

Continued on following page

## Termination and Batten Bars

.050" .075" .090" .100" .125" 6" OC

For wall termination applications

## Selection


Termination Product	Material No. Termination	North American Code	Carton Wt. (lbs)	Hole Spacing	Carton Qty.	Skid Qty.
.050" All Purpose	791391	TB-AP-.05x1x120-6o.c.-TUBE	45	6"	500 feet (50-10 ft pcs)	10,000
.075" Single Lip	791394	TB-SL-.075x1x120-6o.c.-TUBE	51	6"	500 feet (50-10 ft pcs)	10,000
.075" Ribbed Single Lip	791395	TB-RSL-.075x1x120-6o.c.-TUBE	51	6"	500 feet (50-10 ft pcs)	10,000
.100" Single Lip	791401	TB-SL-.1x1x120-6o.c.-TUBE	68	6"	500 feet (50-10 ft pcs)	10,000
.125" Flat	791403	TB-F-.125x1x120-6o.c.-TUBE	78	6"	500 feet (50-10 ft pcs)	10,000
.100" Ribbed Term Bar Flat	791404	TB-R-.1x1x120-6o.c.-TUBE	78	6"	500 feet (50-10 ft pcs)	10,000
Drain Bar/Gravel Stop	791410	TB-DB-.125X3.5x120-TUBE	42	6"	100 feet (10-10 ft pcs)	10,000
.090" Lip and Ball	791411	TB-LB-0.09-TUBE	86	6"	500 feet (50-10 ft pcs)	10,000
Flat Batten Bar (.050)	625833	TB-FBB-.05x1x120-6o.c.-TUBE	45	6"	500 feet (50-10 ft pcs)	10,000
Coiled Batten Bar (.260)	791434	BB-R-.08x.99x100-3o.c.-CTN	72	3"	500 feet (50-10 ft pcs)	10,000

## Approvals

Dekfast fasteners and plates are Factory Mutual approved for attachment of insulation board and/or roof cover to roof deck. Refer to FM Approval Guide and Supplements for current FM approved insulation fastening patterns. Termination products meet Factory Mutual corrosion-resistance Standard 4470.

## Options

ZAC® Anchors  
& Nailins



Distributed by: **BEST MATERIALS®**  
 Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014  
[www.BestMaterials.com](http://www.BestMaterials.com) Email: [Sales@BestMaterials.com](mailto:Sales@BestMaterials.com)