

EternaPrime

Distributed by: BEST MATERIALS LLC
Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014
www.BestMaterials.com Email: Sales@BestMaterials.com

Description

EternaPrime is a specially formulated primer developed specifically for **EternaBond** tapes. **EternaPrime**, based on a VOC exempt solvent, meets all federal standards for health and environmental safety.

EternaPrime is designed to work with all **EternaBond** tapes and was specifically developed for preparation of surfaces when installing **EternaBond** tapes in low ambient temperatures from 40° F down to -20° F. It is also widely used as a coalescing agent on surfaces which have difficult to remove dirt or conditions which may encapsulate the **EternaBond** tape.

*Do not use on PVC.

Basic Use

EternaPrime is used to prepare surfaces for application of all **EternaBond** tapes. Recommended uses include, but are not limited to dirty surfaces which are difficult to clean completely (tar and gravel), potentially loose surfaces (mortar), porous surfaces (wood or concrete), and anytime the **EternaBond** tape is applied at temperatures below 40° F ambient.

Composition

EternaPrime is based on a VOC exempt solvent with a blend of our elastomers and resins infused into the solvent.

Technical Data

| | |
|-------------------------|--|
| Application temperature | -20° F to 205° F |
| Coverage | 300+ Sq. Ft. per gallon |
| Drying time at 60° F | 15 minutes |
| Film thickness | +/- 4 mils when wet |
| Flash point | 110° F (43° C) |
| Standard can sizes | 14 oz spray 1 quart 1 gallon |
| Standard case quantity | 12 14 oz spray per case 12 quarts per case 1 gallon per case |
| Viscosity | 135 - 152 cps |
| Weight | 6 lbs. per gallon |

Values are typical performance properties and characteristics based on laboratory testing. This is intended as a guide for comparison purposes and does not constitute a specification or specification range.

Surface Preparation

Surface must be clean and dry. Remove heavy accumulations of loose rust and scale, dust, talc, and dirt. Oil and grease, and other contaminants should be removed with **EternaClean** or a non-residue cleaner. Do not use **EternaPrime** on PVC roofs as reactivation of some plasticizers may occur.

Application

EternaPrime can be sprayed, rolled, or brushed onto surface (stir frequently).

CAUTION: All statements and technical information in this document are based on tests or data that ADCO believes is reliable. However, ADCO does not warrant or guarantee the accuracy or completeness of this information. The user has sole knowledge and control of factors that can affect the performance of ADCO's products in the user's intended application. It is the user's responsibility to conduct tests to determine the compatibility of ADCO's product with the design, structure, and materials of the user's end product and the suitability of ADCO's product for the user's method of application and intended use. The user assumes all risk and liability arising out of such use.

Distributed by: BEST MATERIALS LLC
Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014
www.BestMaterials.com Email: Sales@BestMaterials.com

ADCO Products, Inc
Michigan Center MI

EternaBond, Inc.
Mundelein IL, USA

EternaBond EternaPrime R2 09/21/11

WARRANTY: ADCO warrants its products to conform to ADCO's specifications at the time of sale when tested according to ADCO standards. If a product is proven to be defective when tested according to ADCO standards, ADCO will, at its option, refund the purchase price or replace or repair the defective product. THIS LIMITED WARRANTY IS THE BUYERS SOLE AND EXCLUSIVE REMEDY AGAINST ADCO AND IS IN LIEU OF ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. In no event shall ADCO be liable for any special, incidental, consequential, or punitive damages arising out of any claims whether based on negligence, contract, warranty, strict liability or otherwise.

