

# FAMOCRETE™

## Instant Concrete Repair

**NON-SHRINKING**



Famocrete™ is a ridged, sag-resistant polyurethane repair product for broken or spalled concrete. Famocrete is easy to apply and is supplied in ready-to-use universal cartridge tubes. Famocrete is 100% solids and cures quickly to form a strong bond to concrete.

*Fast-Setting / Trowelable / Sandable / Grindable / Paintable*

Strong, Fast-Setting Adhesion  
Specifically Formulated to be Applied to Vertical Surfaces



### INDUSTRIES & APPLICATIONS

- Walls – fill voids or patch defects
- Pillars – repair damaged areas
- Sidewalks – transitions or spalls
- Curbs – broken or damaged areas
- Driveways – easy to apply

Distributed by: BEST MATERIALS LLC, Phoenix AZ  
800-474-7570 602-272-8128 [www.BestMaterials.com](http://www.BestMaterials.com)  
Email: [Sales@BestMaterials.com](mailto:Sales@BestMaterials.com)

# FAMOCRETE™

## PRODUCT CHARACTERISTICS & PROPERTIES

<b>CONCRETE ADHESION</b>	psi (MPa), ASTM D 4541 500 (3.4) 100% substrate
<b>APPLICATION TEMPERATURE</b>	Optimal temperature range is 65 °F to 85 °F (18 °C to 29 °C). May be applied at temperatures outside of this range (35 °F to 100 °F / 2 °C to 38 °C).
<b>FULL CURE TIME</b>	24 hours after application. <b>Note:</b> Polyurethanes cure faster at warmer temperatures and slower at cooler temperatures. Large repairs cure faster than small repairs.
<b>SOLIDS</b>	100% solids; No solvents
<b>UV RESISTANCE</b>	Polyurethane is not sensitive to UV degradation; however, certain colors may change slightly.
<b>SHORE HARDNESS</b>	Shore A/D, ASTM D2240 92/50
<b>HEAT RESISTANCE</b>	Cured resin has very good heat resistance. (250 °F / 121 °C).



**6.1 fl oz (180 mL) cartridge and 2 mix tubes**  
(Uses heavy duty cartridge gun. Not included with kit.)

## PRODUCT BENEFITS

<b>VOC %</b>	Less than 1% VOC. <b>Contains no solvents.</b>
<b>NON-SAG</b>	Can be applied onto flat, sloped, and/or vertical concrete
<b>NO SHRINKING</b>	Strong adhesion to concrete with no shrinking. Can be used for small or large voids or spalls.
<b>EXCELLENT WORKING PROPERTIES</b>	Easy to sand, grind, and paint. Sandable and paintable after 1 hour.
<b>WORKING TIME</b>	Material can be troweled for up to 3 minutes at optimal application temperatures.
<b>SET TIME</b>	Approximately 5 minutes
<b>QUALITY REPAIR</b>	Offers superior filling & patching of defects.
<b>COLOR</b>	Gray
<b>VISCOSITY</b>	16,000 cps, ASTM D 4878
<b>YIELD</b>	180 mL = 14.4 lineal ft at 1/4" (4.32m at 6.3mm)

**NOTE: Non-Structural Use** - Material will not impact structural rating or certification of any concrete repair.

Famocrete™ Instant Concrete Repair	Sales Part	Item UPC	Case Barcode	Case Weight	Case Dimensions	Case Cube
6.1 fl oz / 180 mL - Gray	1026801-180	0 76818 268017	2 00 76818 268011	10 lbs.	8.25" x 8.25" x 10.50"	.41 ft <sup>3</sup>