

MULTI-PORT MASTER FLASH®

**20
YEAR
WARRANTY**

Two Applications • One Design • Multiple Functions

ISO Quality, Price & Availability TWO COMPOUNDS

ADVANCED OZONE RESISTANCE tested to...	EPDM 70 hour @ 500 pphm	SILICONE 70 hour @ 500 pphm
HIGH TEMPERATURE RESISTANCE Tested to	+135°C (+275°F) +100°C (+212°F)	+260°C (+500°F) +225°C (+437°F)
LOW TEMPERATURE RESISTANCE tested to...	-55°C (-67°F)	-74°C (-101°F)
TENSILE SET maximum	10MPa (1450 psi)	5 MPa (700 psi)
COMPRESSION SET maximum...	25%	50%

*Complete specification data and testing methods are available upon request.

Accommodates FOUR

1/4" (6mm) lines and 1 pipe 1/4" - 2-3/4" (6 - 70mm)



Up to 4 Cables or Wires per flashing.



Ozone and UV Protection

Flashings are made of EPDM and Silicone, and designed for maximum resistance to all weather conditions.

No Hassle Gripper

Single stainless steel gripper to secure retrofit applications only.

Adaptable Base

The base is designed to mold to most panel configurations and roof pitches regardless of pipe location.



	PIPE RANGE	COMPOUND	PART NO.		FLASHING DETAILS	
MULTI-PORT	STANDARD 1/4"-2-3/4" (6 - 70mm)	BLACK EPDM	MP101BA		A-Base Diameter	Standard Only Closed
	RETROFIT 1-1/4"-2-1/4" (25 - 57mm)	SILICONE	MP101RA		B-Base Diameter	4-1/2" (114mm)

Distributed by: **BEST MATERIALS LLC, Phoenix AZ**
 Ph: 800-474-7570, 602-272-8128 Fx: 602-272-8014
www.BestMaterials.com Email: Sales@BestMaterials.com