

# CR-Base Sheet Fastener

## PRODUCT DATA SPECIFICATIONS

### PRODUCT DESCRIPTION

The OMG Assembled CR-Base Sheet Fasteners are one-piece, precision formed from G-90 galvanized steel, coated with CR-10 and assembled with a 2.75-in. (70mm) diameter Galvalume® plate. These fasteners are designed to secure base sheets to poured lightweight insulating concrete or various gypsums\*.

The OMG Assembled CR-Base Sheet Fastener is Factory Mutual and Miami-Dade County approved and is installed with an OMG MultiPogo or wooden mallet.

**\*Caution: Only the CR 1.2 Base Sheet Fastener can be installed in some gypsum decks.** A pull test is required to determine suitability.

### FEATURES & BENEFITS

- OMG Assembled CR-Base Sheet Fasteners are FM and Miami-Dade County approved.
- Assembled fasteners greatly reduce installation time and labor cost.
- CR-Base Sheet Fasteners are packaged for easy handling on the roof.
- Entire fastener "legs" are CR-10 coated to prevent in-place corrosion.

### COATING

OMG CR-10 corrosion resistant coating exceeds FM Approval Standard 4470.

### APPLICATION

Surfaces must be surface dry and reasonably smooth prior to roofing. For best performance, the fastener should always be installed perpendicular to the substrate.

**CR 1.2 BSF** – Are designed for use on minimum 1.25-in. (32mm) thick poured lightweight insulating concrete and some gypsum decks. A pull test is required to determine suitability.

**CR 1.75 BSF** – Are designed for use on minimum 2-in. (51mm) thick poured lightweight insulating concrete decks only.

**Not to be used on poured gypsum decks.**

OMG Assembled CR-Base Sheet Fasteners are FM approved and rated to 1-150 with certain fastener, base sheet and insulating concrete combinations. Consult the roofing system manufacturer for specific wind ratings.

**Note: Prior to job start, contact roof cover manufacturer to determine the correct fastening pattern.** On re-roofing applications, prior to job start, roof should be inspected and pull tests should be completed to determine the pullout values.

### ACCESSORIES

Use an OMG MultiPogo to install the fastener. See Accessories section.



### APPROVALS



**Factory Mutual listings refer to this product as C-R Assembled Base Sheet Fastener (1.2, 1.7).**



USE WITH  
**LWIC**  
**G**\*  
 DECK TYPES

### PHYSICAL DATA\*\*

The data below is constant for each OMG CR-Base Sheet Fastener.

HEAD		LEGS	
1.125" x 1" (28.57mm x 25.4mm)		1.2" (30mm)	1.75" (45mm)
MATERIAL		PLATE	
G-90 Galvanized CR-10 Coated Fastener .014" (0.36mm) Thickness		2.75" (70mm) Diameter Galvalume	

### ORDERING INFORMATION

CAT. NO.	LENGTH IN (MM)	PKG	WEIGHT LBS (KG)
CRBSA134	1.75 (45)	500	21 (9.53)
CRBSA120	1.20 (30)	1000	37 (16.79)
MULTIPOGO	39.5 (1000)	1	25 (11.35)

\*\*All sizes are nominal.

#### KEY:

<b>S</b> Steel	<b>SC</b> Structural Concrete
<b>W</b> Wood	<b>LC</b> Lightweight Concrete
<b>G</b> Gypsum	<b>LWIC</b> Lightweight Insulating Concrete
<b>P</b> Purlins	<b>CWF</b> Cementitious Wood Fiber

# CR-Base Sheet Fastener

## PRODUCT DATA SPECIFICATIONS

### SPECIFICATION

The fastener will be an OMG Assembled CR-Base Sheet Fastener (or CR 1.2 Base Sheet Fastener). The fastener comes assembled with a 2.75-in. (70mm) diameter Galvalume® plate. The fastener head and legs must be CR-10 coated. The fastener must be Factory Mutual approved.

### COATING REQUIREMENT

The fastener will be coated with the OMG CR-10 corrosion resistant coating. Fastener must meet Factory Mutual Approval Standard 4470. The plate must be Galvalume® and also meet Factory Mutual Approval Standard 4470.

### APPLICATION

OMG **1.75 CR-Base Sheet Fastener** will be embedded into a minimum of 2-in. (51mm) of poured lightweight insulating concrete. The OMG **CR 1.2 Base Sheet Fastener** will be embedded into a minimum of 1¼-in. (32mm) of poured lightweight insulating concrete or various gypsums. Substrates must be surface dry. For best performance, the fastener should always be installed perpendicular to the substrate. Installation of fasteners too far apart to too close together can result in interaction of forces on the substrate and lead to a reduction of fastener performance.

**Note: On re-roofing applications, prior to job bid, roof deck should be inspected or tested to determine the pullout values.**

### PHYSICAL DATA \*

The data below is constant for each OMG CR-Base Sheet Fastener.

HEAD		LEGS	
1.125" x 1" (28.57mm x 25.4mm)	1.2" (30mm)	1.75" (45mm)	
MATERIAL		PLATE	
G-90 Galvanized CR-10 Coated Fastener .014" (0.36mm) Thickness	2.75" (70mm) Diameter Galvalume®		
	PACKAGING		
	1000	500	

\*All sizes are nominal.

### FM APPROVED FASTENING PATTERNS

Due to frequent changes in Factory Mutual requirements for securing base sheets to various lightweight concrete and gypsum decks, please contact the roof cover manufacturer for up to date information on approved fastening patterns.



ROOFING PRODUCTS

153 BOWLES ROAD, AGAWAM, MA 01001 USA  
800-633-3800 413-789-0252 OMGROOFING.COM

Copyright © 2015 OMG, Inc. All rights reserved.

Superior productivity.  
Superior performance.

