

**MATERIAL SAFETY DATA SHEET**

-----  
MANUFACTURER: APPLIED TECHNOLOGIES, LLC  
P. O.Box 18476  
FAIRFIELD, OH 45018  
EMERGENCY TELEPHONE:  
CHEMTREC (800) 424-9300  
-----

**SECTION I - PRODUCT IDENTIFICATION**

-----  
**PRODUCT NAME:** POXY PASTE, PART A  
**SYNONYM:** THERMOSETTING RESIN  
**CHEMICAL FAMILY:** MODIFIED EPOXY RESIN  
**DATE:** JANUARY 1, 1995  
-----

**SECTION II - HAZARDOUS INGREDIENTS AND OTHER COMPONENTS**

<b>INGREDIENT</b>	<b>% BY WEIGHT</b>	<b>EXPOSURE LIMITS</b>	<b>CAS#</b>
BISPHENOL A/DIGLYCIDYL 25068-38-6 ETHER RESIN	50-90	N.E.	
INERT POWDERS 14807-96-6	10-50	N.E.	
FUMED SILICA	0-5		067762-90-7

**SECTION III - PHYSICAL DATA**

-----  
**BOILING POINT:** > 200<sup>o</sup> C  
**VP:** > 1 TORR @ 180 °C  
**VP:** > 1 (AIR =1)  
**SOLUBILITY IN WATER:** INSOLUBLE  
**EVAPORATION RATE:** < 1 (BUTYL ACETATE =1 )  
**SP GR:** > 1.32 (WATER = 1)  
**% VOLATILE BY VL:** NIL  
-----

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

-----  
**FLASH POINT:** > 200<sup>o</sup> F (TCC)  
**FLAMMABLE LIMITS:** ACRID SMOKE/FUMES  
**EXTINGUISHING MEDIA:** CARBON DIOXIDE, DRY CHEMICALS, FOAM, WATER SPRAY  
**EXPLOSIVE LIMITS:** LEL - N.E.  
UEL - N.E.  
-----

## POXY PASTE: PART A

---

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA (CONTINUED)

---

SPECIAL FIRE FIGHTING PROCEDURES : USE SELF-CONTAINED BREATHING APPARATUS.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: DECOMPOSITION AND COMBUSTION PRODUCTS  
MAY BE TOXIC.

---

### SECTION V - HEALTH HAZARD DATA

---

PRIMARY ROUTE(S) OF ENTRY: INHALATION, SKIN CONTACT

---

TOXICOLOGICAL DATA: LD SO'S PROVIDED ARE THE LOWEST VALUES FOR TYPED OF  
BISPHENOL A  
DIGLYCIDAL ETHER RESINS USED.  
ORAL LD, 0: (RABBITS) MODERATE IRRITATION  
EYE IRRITATION: (RABBITS) MILD IRRITATION  
SENSITIZATION: SENSITIZER

---

EFFECTS OF OVEREXPOSURE: IRRITATION, SENSITIZATION, AND DERMATITIS  
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: ALLERGY, ECZEMA, SKIN  
CONDITIONS  
CARCINOGENICITY: NONE OF THE COMPONENTS OF THIS MATERIAL ARE LISTED AS  
CARCINOGENS BY NTP, IARC, OR OSHA.

IN ORDER TO COMPLY WITH CALIFORNIA PROPOSITION 65, WE FEEL OBLIGATED TO ADVISE  
THAT SOME OF OUR PRODUCTS MAY CONCEIVABLY CONTAIN TRACE CONTAMINANTS OF  
SOME OF THE LISTED CHEMICALS. WHILE NOT NECESSARILY ADDED TO OUR PRODUCTS AS  
INGREDIENTS, SOME LISTED CHEMICALS MAY BE PRESENT IN THE RAW MATERIALS AS  
RECEIVED FROM SUPPLIERS AND OVER WHICH WE HAVE NO CONTROL. THEREFORE, COMPLY  
WITH CALIFORNIA LAW, WE FEEL OBLIGATED TO MAKE THE FOLLOWING STATEMENT:  
**WARNING: OUR PRODUCTS MAY CONTAIN TRACE AMOUNTS OF SOME CHEMICALS  
CONSIDERED BY THE STATE OF CALIFORNIA TO BE CARCINOGENS OR REPRODUCTIVE  
TOXICANTS.**

#### **EMERGENCY AND FIRST AID PROCEDURES:**

EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES, IF ANY ILL EFFECTS DEVELOP, SEEK  
MEDICAL ATTENTION.  
INHALATION: REMOVE TO FRESH AIR AND GIVE OXYGEN IF BREATHING IS DIFFICULT.  
INGESTION : GIVE LARGE QUANTITIES OF WATER AND INDUCE VOMITING, GET MEDICAL  
ATTENTION.

---

### SECTION VI REACTIVITY DATA

---

STABILITY: STABLE  
CONDITIONS TO AVOID: ELEVATED TEMPERATURES

INCOMPATIBILITY: ( MATERIALS TO AVOID): STRONG OXIDIZERS, STRONG ACIDS OR BASES IN BULK  
HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE, ALDEHYDES AND OTHER ORGANICS.

## **POXY PASTE: PART A**

---

### **SECTION VII SPILL OR LEAK PROCEDURES**

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: AVOID ALL PERSONAL CONTACT. WIPE WITH RAG FOR SMALL SPILLS. FOR LARGER SPILLS, USE ABSORBENT MATERIAL. COLLECT WASTE IN DESIGNATED CONTAINER. FLUSH CONTAMINATED AREA WITH WATER. WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH FEDERAL , STATE AND LOCAL REGULATIONS.

---

### **SECTION VIII-SPECIAL PROTECTION INFORMATION**

---

RESPIRATORY PROTECTION: AVOID BREATHING VAPORS. USE ADEQUATE VENTILATION.  
VENTILATION: GOOD MECHANICAL VENTILATION AND LOCAL EXHAUST  
EYE PROTECTION: SAFETY GLASSES  
PROTECTIVE GLOVES: RUBBER OR POLYETHYLENE  
OTHER PROTECTIVE EQUIPMENT : DISPOSABLE CONTAINERS AND PAPER ON WORK AREA. USE OF BARRIER CREAM RECOMMENDED. USE APPROPRIATE EQUIPMENT TO PREVENT EYE OR SKIN CONTACT.

---

### **SECTION IX-SPECIAL PRECAUTIONS**

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: CAUSES IRRITATION - MAY CAUSE ALLERGIC SKIN REACTION. AVOID CONTACT WITH EYES, SKIN OR CLOTHING. STORE IN COOL, DRY AREA IN CLOSED CARTRIDGES,  
OTHER PRECAUTIONS: AVOID BREATHING VAPORS. USE WITH GOOD VENTILATION. WASH HANDS THOROUGHLY WITH SOAP AND WATER AFTER EVERY USAGE  
HMIS CLASSIFICATION:  
HEALTH 2            FLAMMABILITY 1            REACTIVITY 0            PERSONAL  
PROTECTION B

ALL STATEMENTS TECHNICAL INFORMATION, AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON AVAILABLE SCIENTIFIC TEST OR DATA WHICH WE BELIEVE TO BE RELIABLE. SINCE WE CANNOT ANTICIPATE ALL CONDITIONS UNDER WHICH THIS INFORMATION AND OUR PRODUCTS OR THE PRODUCTS OF OTHER MANUFACTURERS IN COMBINATION WITH OUR PRODUCTS MAY BE USED, APPLIED TECHNOLOGIES, LLC MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION.

**MATERIAL SAFETY DATA SHEET**

- MANUFACTURER: APPLIED TECHNOLOGIES, LLC  
33 DONALD DR., SUITE 10  
FAIRFIELD, OH 45014  
EMERGENCY TELEPHONE:  
CHEMTREC: (800) 424-9300

**SECTION I - PRODUCT IDENTIFICATION**

**PRODUCT NAME:** POXY PASTE, PART B  
**SYNONYM:** EPOXY HARDENER  
**CHEMICAL FAMILY:** MODIFIED POLYMERCAPTAN  
**DATE:** JANUARY 1, 1995

**SECTION II - HAZARDOUS INGREDIENTS AND OTHER COMPONENTS**

<u>INGREDIENT</u>	<u>% BY WEIGHT</u>	<u>EXPOSURE LIMITS</u>	<u>CAS #</u>
PROPRIETARY POLYMERCAPTANS	20 - 40	N.E.	-----
INERT POWDERS	60 - 80	N.E.	14807-96-6
FUMED SILICA	0 - 5	N.E.	067762-90-7

**SECTION III - PHYSICAL DATA**

**APPEARANCE:** PASTE **COLOR:** BLACK  
**BOILING POINT:** NOT DETERMINED (>200° F) **VP:** N.D.  
**VD:** NOT DETERMINED (AIR =I) **% VOLATILE BY VL:** < 1  
**SOLUBILITY IN WATER:** APPRECIABLE **ODOR:** SKUNK LIKE, PINC -0.1  
**EVAPORATION RATE:** <1 (BUTYL ACETATE = 1)  
**SP GR:** > 1.91 +/- .02 (WATER = 1)

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT: 185° F PMCC FLAMMABLE LIMITS: UNKNOWN  
EXTINGUISHING MEDIA: FOAM, DRY CHEMICALS, CO2  
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE  
SPECIAL FIRE FIGHTING PROCEDURES: AVOID BREATHING SMOKE. SELF CONTAINED  
BREATHING APPARATUS.

## **POXY PASTE: PART B**

---

### **SECTION V - HEALTH HAZARD DATA**

---

PRIMARY ROUTE(S) OF ENTRY: INHALATION, SKIN CONTACT

---

TOXICOLOGICAL DATA: POLYAMINE RESIN: ORAL RAT LD50-<5 CC/KG

IRRITATION DATA: POLYAMINE RESIN EYE -(RABBIT) CONJUNCTIVAL IRRITANT

SKIN- (RABBIT) - MILD IRRITANT

---

#### **EFFECTS OF OVEREXPOSURE:**

ACUTE: WILL CAUSE BURNS TO SKIN AND EYES. HIGH CONCENTRATIONS OF VAPOR CAN CAUSE IRRITATION OF RESPIRATORY TRACT, NAUSEA AND VOMITING.

CHRONIC: PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: ALLERGY, ECZEMA, SKIN CONDITIONS.

CARCINOGENICITY: NONE OF THE COMPONENTS OF THIS MATERIAL ARE LISTED AS CARCINOGENS BY NTP, IARC, OR OSHA.

IN ORDER TO COMPLY WITH CALIFORNIA PROPOSITION 65, WE FEEL OBLIGATED TO ADVISE THAT SOME OF OUR PRODUCTS MAY CONCEIVABLY CONTAIN TRACE CONTAMINANTS OF SOME OF THE LISTED CHEMICALS. WHILE NOT NECESSARILY ADDED TO OUR PRODUCTS AS INGREDIENTS, SOME LISTED CHEMICALS MAY BE PRESENT IN THE RAW MATERIALS AS RECEIVED FROM SUPPLIERS AND OVER WHICH WE HAVE NO CONTROL. THEREFORE, EVEN THOUGH SOME OF THE LISTED SUBSTANCES MAY NOT REPRESENT A SIGNIFICANT RISK AS DEFINED BY THE REGULATIONS, IN ORDER TO COMPLY WITH CALIFORNIA LAW, WE FEEL OBLIGATED TO MAKE THE FOLLOWING STATEMENT.: **WARNING:** OUR PRODUCTS MAY CONTAIN TRACE AMOUNTS OF SOME CHEMICALS CONSIDERED BY THE STATE OF CALIFORNIA TO BE CARCINOGENS OR REPRODUCTIVE TOXICANTS.

#### **EMERGENCY AND FIRST AID PROCEDURES:**

EYES - FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

SKIN: IMMEDIATELY DELUGE SKIN WITH PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND SHOES.

INHALATION: REMOVE TO FRESH AIR. IF AFFECTED, ADMINISTER OXYGEN IF NECESSARY. SEEK MEDICAL ATTENTION.

INGESTION: IF SWALLOWED AND CONSCIOUS, GIVE PLENTY OF WATER AND INDUCE VOMITING. SEEK MEDICAL ATTENTION.

# POXY PASTE: PART B

---

## SECTION VI - REACTIVITY DATA

---

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS, ACIDS. HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE, NITROGEN OXIDES.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

CONDITIONS TO AVOID: MIXING WITH OXIDIZERS OR EPOXY RESINS IN QUANTITIES OVER 1#.

---

## SECTION VII - SPILL OR LEAK PROCEDURES

---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SOAK UP WITH INERT MATERIAL OR SCRAPE UP. COLLECT WASTE IN DESIGNATED WASTE CONTAINERS. AVOID PERSONAL CONTACT. FLUSH CONTAMINATED AREA WITH WATER. WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

---

## SECTION VIII - SPECIAL PROTECTION INFORMATION

---

RESPIRATORY PROTECTION: USE ADEQUATE VENTILATION. AVOID BREATHING VAPORS.

VENTILATION: NORMAL VENTILATION SHOULD BE ADEQUATE. LOCAL IF VAPORS ARE

VENTED. EYE PROTECTION: SAFETY GLASSES PROTECTIVE GLOVES: RUBBER OR IMPERVIOUS GLOVES RECOMMENDED.

---

## SECTION IX - SPECIAL PRECAUTIONS

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: STORE AWAY FROM HEAT AND OPEN FLAME.

OTHER PRECAUTIONS: AVOID BREATHING VAPORS OF HEATED MATERIAL. WASH HANDS WITH SOAP AND WATER AFTER EVERY USAGE USE ADEQUATE VENTILATION. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.

HMS CLASSIFICATION:

HEALTH 2

FLAMMABILITY 2

REACTIVITY 0

PERSONAL PROTECTION

B

ALL STATEMENTS, TECHNICAL INFORMATION, AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON AVAILABLE SCIENTIFIC TEST OR DATA WHICH WE BELIEVE TO BE RELIABLE. SINCE WE CANNOT ANTICIPATE ALL CONDITIONS UNDER WHICH THIS INFORMATION AND OUR PRODUCTS OR THE PRODUCTS OF OTHER MANUFACTURERS IN COMBINATION WITH OUR PRODUCTS MAY BE USED, APPLIED TECHNOLOGIES, LLC MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION.