

SOLAR-MULTI-PORT-LD MASTER FLASH®



Powder Coated Safe Lead base One Design • Multiple Functions

ISO Quality, Price & Availability / TWO COMPOUNDS

ADVANCED OZONE RESISTANCE tested to...	EPDM 70 hour @ 500 pphm	SILICONE 70 hour @ 500 pphm
HIGH TEMPERATURE RESISTANCE Tested to		
Intermittent	+135°C (+275°F)	+260°C (+500°F)
Continuous	+100°C (+212°F)	+225°C (+437°F)
LOW TEMPERATURE RESISTANCE tested to...	- 55°C (-67°F)	-74°C (-101°F)
COMPRESSION SET minimum...	25%	50%

*Complete specification data and testing methods are available upon request.

• Accommodates:

ONE 0" - 1-15/16" - (0 - 49mm) Pipe

TWO 3/8" (0.9525mm) pipe / cable

TWO 3/4" (20mm) pipe / cable

- 16" x 19-1/4" (410 x 490mm) Lead Base
- Up to 4 Cables or Wires per flashing
- Extra ports to accommodate Copper pipe and electrical cabling
- Easy install for Solar applications



Pipe Range	Compound	Part No.		Flashing Details	
Solar Multi-Port LD • One center port 0" - 1-15/16" (0 - 49mm) Pipe • Two ports up to 3/8" (0.9525mm) pipe / cable • Two ports up to 3/4" (20mm) pipe / cable	Black EPDM	SMP-LD101BA		A-Top Opening Diameter	0" - 1-15/16" (0 - 49mm)
	Silicone	SMP-LD102RA		B-Overall Height	2-1/2" (63.5mm)
				C-Base Diameter	16" x 19-1/4" (410 x 490mm)

