

## Collated Exterior Wood Screws



### SSWSCB Roofing Tile Screw


**Common Applications:**

Roofing tiles to wood

**Features:**

- Bugle head
- #2 square drive (driver bit in each box; replacement bit model BIT2S)
- Coarse threads
- Type-17 point
- Curved collation

**Codes/Standards:** Meets the requirements of the Tile Roofing Institute as described in ESR-2015P. A Miami-Dade compliant roofing product (2" and 2 1/2" only).



Type 305 Stainless Steel

Length (in.)	Shank Size	Carton Quantity	Model No.	PRORF	PRO300SRF
1 3/4	#8	2,000	SSWSC134BS	✓	✓
2	#8	2,000	SSWSC2BS	✓	✓
2 1/2	#8	1,500	SSWSC212BS	✓	✓

### WSCT Roofing Tile Screw


**Common Applications:**

Roofing tiles to wood

**Features:**

- Flat head
- #3 square drive (driver bit in each box; replacement bit model BIT3S)
- Twin threads
- Sharp point
- Curved collation

**Codes/Standards:** ASTM A641 (Class 1)



Heavy Zinc Electroplate

Length (in.)	Shank Size	Carton Quantity	Model No.	PRORF	PRO300SRF
2 1/2	#8	1,500	WSCT212S	✓	✓

### WSCD Roofing Tile Screw


**Common Applications:**

Roofing tiles to wood

**Features:**

- Flat head
- #3 square drive (driver bit in each box; replacement bit model BIT3SU)
- Twin threads
- Sharp point
- Curved collation

**Codes/Standards:** Meets the requirements of the Tile Roofing Institute as described in ESR-2015P. Miami-Dade Fastener Listing 10-0330.06



Mechanically Galvanized – Class 55

Length (in.)	Shank Size	Carton Quantity	Model No.	PRO RF	PRO 300SRF
2 1/2	#8	1,500	WSCD212S	✓	✓
3	#8	1,000	WSCD3S		✓