

CARLISLE'S



SURE-WELD[®] CUT-EDGE SEALANT



Overview

Carlisle's Cut-Edge Sealant is a medium solids content, free flowing, polymeric material designed to be used for sealing cut edges of Sure-Weld™ Reinforced Membrane. It is available in white or clear for use with various colors of Sure-Weld Membrane.

Intended Uses

Carlisle Cut-Edge Sealant is used to seal cut edges of Sure-Weld Membrane, providing a waterproof barrier where scrim reinforcement is exposed.

Features and Benefits

- Provides excellent sealing of exposed fabric at cut membrane edges
- Squeeze bottle packaging allows easy, no-mess application
- Available in white or clear for use with various colors of Sure-Weld membrane

Application

1. All surfaces to be sealed with Cut-Edge Sealant must be clean, dry and free from oil, grease, dirt and other foreign materials.
2. Apply a 1/8" (3mm) bead of Cut-Edge Sealant from the plastic squeeze bottle to seal cut edges of reinforced Sure-Weld Membrane. Do not apply Cut-Edge Sealant on vertical surfaces.
3. Sealant should be tack-free in 2 hours and fully cured in 24 hours depending on weather conditions and application thickness.

Precautions

1. Review the applicable Material Safety Data Sheet for complete safety information.
2. Cut-Edge Sealant is **FLAMMABLE** – it contains solvents that are dangerous fire and explosion hazards when exposed to heat, flame or spark. Do not smoke while applying. Do not use in a confined area or unventilated area. Vapors are heavier than air and may travel along the ground to a distant ignition source and flashback.
3. Avoid breathing vapors. Keep container closed when not in use. Use with adequate ventilation. If inhaled, remove to fresh air. If not breathing, perform artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately.
4. If swallowed, **DO NOT INDUCE VOMITING**. Call a physician immediately.
5. Avoid contact with eyes. Safety glasses or goggles are recommended. If splashed in eyes, immediately flush eyes with plenty of water for at least 15 minutes. Contact a physician immediately.
6. Avoid contact with skin. Permeation resistant gloves (that meet ANSI/ISEA 105-2005) recommended. Wash thoroughly after handling. In case of contact with skin, thoroughly wash affected area with soap and water.
7. Job site storage temperatures in excess of 90°F (32°C) may affect product shelf life. Should the Cut-Edge Sealant be stored at temperatures below 60°F (15°C), restore to room temperature prior to use.
8. **KEEP OUT OF THE REACH OF CHILDREN**

Coverage

Approximately 225' – 275' (70 – 85m) per bottle when applied with 1/8" (3mm) bead.

CARLISLE'S
 **SURE-WELD[®]**
CUT-EDGE SEALANT

Cut-Edge Sealant - White	
Typical Properties and Characteristics	
Base:	Synthetic Rubber
Color:	White
Solids:	25%
Viscosity:	2,000 cps
Flash Point:	81°F (27°C)
Net Weight Gallon:	7.8 lbs. (3.5 kg)
Resistance To:	
Ozone:	Excellent
UV:	Excellent
Water:	Excellent
VOC:	700 GPL
Packaging:	Eight 16 oz. Bottles/carton (3.8 L)
Shelf Life:	1 year

Cut-Edge Sealant - Clear	
Typical Properties and Characteristics	
Base:	Synthetic Rubber
Color:	Clear
Solids:	14%
Viscosity:	3,500 cps
Flash Point:	39°F (4°C)
Net Weight Gallon:	7.4 lbs. (3.3 kg)
Resistance To:	
Ozone:	Excellent
UV:	Excellent
Water:	Excellent
VOC:	750 GPL
Packaging:	Eight 16 oz. Bottles/carton (3.8 L)
Shelf Life:	1 year

**General Properties: Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

Distributed by: **BEST MATERIALS LLC**
Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014
Email: sales@bestmaterials.com www.bestmaterials.com