



Distributed by: **BEST MATERIALS®**
 Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014
www.BestMaterials.com Email: Sales@BestMaterials.com

Tech-Wrap Product Sheet

	TW-150 Econ Grey/Black 2 side Non-Slip 4 Layer P/P 110 GSM Fabric Weight	TW-150 Comp Grey/Black 2 side Non-Slip 4 Layer P/P 120 GSM Fabric Weight	TW-Ultimate Grey/Black 2 side High Non-Slip 4 Layer P/P 140 GSM Fabric Weight	TW-Supreme Tan/Black 2 side Extreme Non-Slip 4 Layer P/P 180 GSM Fabric weight
Length/Weight	48"x250'= 10 sq 24 lbs	48"x250'= 10 sq 24 lbs	48"x250'= 10 sq 30 lbs	48"x250'= 10 sq 40 lbs
Roofing Material	Asphalt Shingles, Metal, Shake, Slate, Clay Tile, Concrete Tile	Asphalt Shingles, Metal, Shake, Slate, Clay Tile, Concrete Tile	Asphalt Shingles, Metal, Shake, Slate, Clay Tile, Concrete Tile	Asphalt Shingles, Metal, Shake, Slate, Clay Tile, Concrete Tile
Slope/Pitch of Roof	All pitches/slopes	All pitches/slopes	All pitches/slopes	All pitches/slopes
Installation	Roofing nails, Plastic cap nails, Cap Staples, Staples*	Roofing nails, Plastic cap nails, Cap Staples, Staples*	Roofing nails, Plastic cap nails, Cap Staples, Stap- ples*	Roofing nails, Plastic cap nails, Cap Staples, Staples*
High Temp Rated for Metal	YES	YES	YES	YES
Exposure Time	30 days	90 days	06 months	12 months
Warranty	Lifetime Limited Warranty**	Lifetime Limited Warranty**	Lifetime Limited Warranty**	Lifetime Limited Warranty**
Private Label	YES 4 pallets minimum 08 weeks lead time	YES 4 pallets minimum 08 weeks lead time	YES 4 pallets minimum 08 weeks lead time	YES 4 pallets minimum 08 weeks lead time
USA Code Compliance	ICC ESR-AC 188 FBC- #FL- 17194 ASTM D226/1489 Class A Fire Rated Air, Water, and Vapor Barrier	ICC ESR-AC 188 FBC- #FL- 17194 ASTM D226/1489 Class A Fire Rated Air, Water, and Vapor Barrier	ICC ESR- 3293 FBC- #FL- 17194 ASTM D226/1489 Class A Fire Rated Air, Water, and Vapor Barrier	ICC ESR- 3293 FBC- #FL- 17194 ASTM D226/1489 Class A Fire Rated Air, Water and Vapor Barrier
Canada Code Compliance	CAN/CSA A123.3 Type II Asphalt - Saturated Organic Roofing Felt	CAN/CSA A123.3 Type II Asphalt - Saturated Organic Roofing Felt	CAN/CSA A123.3 Type II Asphalt - Saturated Organic Roofing Felt	CAN/CSA A123.3 Type II Asphalt - Saturated Organic Roofing Felt
Rolls Per Pallet	56	56	42	36
Truckload Qty	32 pallets/56 rolls per pallet	32 pallets/56 rolls per pallet	32 pallets/42 rolls per pallet	30 Pallets/36 rolls per pallet

**See website for the details of Lifetime Limited Warranty.