

Distributed by: BEST MATERIALS LLC  
Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014  
Email: sales@bestmaterials.com www.bestmaterials.com

# Wall Coatings



 **BASF**

The Chemical Company

Solutions for  
Protection & Appearance

For project quotes or more information about any of these items, email [sales@bestmaterials.com](mailto:sales@bestmaterials.com)

Keeping surfaces beautiful and walls dry requires protection more powerful than the elements. Your strategy: assess environmental exposure to sun, wind, rain, and temperature. Determine performance objectives. Select the most effective solution: high-build coatings, including smooth, textured, or elastomeric, that enhance the value of structures and life within surrounding environments.

# Wall Coatings

## High Build Acrylic Coatings

Above grade waterproofing, protection and decoration on concrete, masonry and stucco. For use on commercial, institutional and residential buildings.

## Applications

### New Construction

### Renovation

### Exterior Walls

- Above Grade
- Over Masonry, Concrete, Stucco, and previously painted surfaces

## Market Segments

### Commercial Buildings

- Retail Chain Shops
- Strip Malls and Shopping Malls
- Office Buildings
- Hotels
- Warehouses
- Parking Garages

### Institutional Buildings

- Healthcare
- Schools
- Public
- Amusements

### Residential Buildings

- Condos and Apartments
- Single Houses

### Transportation

- Bridges

## Technologies

- 100% Acrylic
- Styrene-modified Acrylic
- Silicone-modified Acrylic
- Water-based
- Water-borne
- Solvent-based
- Silica-sand / Perlite Aggregates

## Colors and Services

Thoro® coatings are available in 48 standard colors, found in our Elements color card (Form 1019055). Sonneborn® coatings are available in 40 Most Popular Colors, found in the Color Portfolio for Wall Coatings (Form 1017995), and the 470 colors of the Sonneborn® fan deck (Form 1018148). The 470 colors are indexed to match the colors of Sonneborn® two-component polyurethane sealants.

Thoro® and Sonneborn® provide either bases or factory tinted coatings from the manufacturing plants at Bristol (PA), Mattawan (MI), and Newark (CA). Thoro® supports local tinting and custom color matching at distributor sites through the Paintmaker program. For more information contact your local sales representative or BASF Customer Service.



## Where to Apply

Application Surfaces	Wall Coatings							
	Thorocoat®	Thorolastic®	Thorocoat® 200	Thoro® 35	Thoro® 20	Sififlex®	Colorflex™	Flexcoat™
<b>CMU</b>								
Porous	●*	●*	■*	●*	●*	●*	●*	●*
Regular	■/●*	●*	■*	●*	●*	●*	●*	●*
Split-Face	●*	●*	●*	●*	●*	■*	●*	●*
<b>Brick</b>	●	■	●	■	■	■	■	■
<b>Cast-in-Place Concrete</b>								
Plain	●	●	●	●	●	●	●	●
Tilt-up	●	■	●	●	●	■	■	■
<b>Pre-Cast Concrete</b>	●	■**	●	●	●	■**	■**	■**
<b>Green Concrete</b>				■	●			
<b>Cement Plaster</b>	●	●	●	■	■	●	●	●
<b>EIFS</b>	■	●	■			●	●	●
<b>Previously Painted Surfaces</b>								
Plain	●	●	●	●	●	●	●	●
Elastomeric		■				■	■	■

\* After applying Block Filler

\*\* After applying Primer 2K or Chalky Surface Primer VOC



For project quotes or more information about any of these items,  
email [sales@bestmaterials.com](mailto:sales@bestmaterials.com)

PRODUCT	TEXTURE	DESCRIPTION	TYPICAL APPLICATION	KEY BENEFITS
<b>Thorocoat®</b>	Smooth, Fine, Coarse	High-build, water-based, 100% acrylic coating	Building exterior: over masonry, concrete and EIFS	Waterproofing against wind-driven rain, breathability, abrasion and impact resistance
<b>Thorocoat® A+</b>	Smooth	Algae-resistant, high build, water-based, 100% acrylic coating	Building exterior: in warm and humid climates	Algae-resistance, waterproofing against wind-driven rain
<b>Thorocoat® 200</b>	Smooth	Water-based, 100% acrylic coating	Building exterior: over masonry, concrete, stucco and EIFS	Airless spray application; light reflectivity, waterproofing against wind-driven rain
<b>Thorocoat® Heavy Tex</b>	Highly Coarse	High-build, perlite textured, water-based, 100% acrylic coating	Building exterior: over tilt-up, precast and cast-in-place concrete	Hides minor defects in one coat, waterproofing against wind driven rain
<b>Thoro® TW Coating</b>	Highly Coarse	Perlite textured, water-based, acrylic coating	Building exterior: over tilt-up, precast and cast-in-place	Hides minor defects in one coat
<b>Thorocoat® DOT</b>	Fine	High-build, water-based, 100% acrylic coating	Exterior: for concrete bridges and infrastructures	One coat application; abrasion and impact resistance
<b>Thoro® 35 Coating</b>	Smooth, Fine	High-build, waterborne, acrylic coating	Building exterior: over concrete, masonry and stucco	Application down to 35°F, use over green concrete, breathability
<b>Thoro® 20</b>	Smooth, Fine	High-build, solvent-based, acrylic sealer	Building exterior: over masonry and concrete	Application down to 20°F, use over green concrete, breathability
<b>Thorolastic®</b>	Smooth, Fine, Coarse	Elastomeric, high-build, water-based, 100% acrylic coating	Building exterior: over stucco, masonry, concrete and EIFS	Crack bridging, waterproofing against wind-driven rain, CO <sub>2</sub> resistance
<b>Thorogard®</b>	Smooth	Elastomeric, water-based, acrylic coating	Building exterior: recoat over acrylic paints/coatings	Elongation, waterproofing against wind-driven rain
<b>Thorosheen®</b>	Smooth	Water-based, 100% acrylic, emulsion coating	Exterior/interior walls: over stucco and EIFS	Color retention, breathability
<b>Thoro® Pigmented Sealer</b>	Smooth	Water-based, acrylic, tinted, stain	Exterior/interior: over concrete, stucco and EIFS	Uniforms the substrate color, breathability
<b>Thoro® CM Primer</b>	Smooth, Sand	Acrylic, water-based, tintable primer	Building exterior: over concrete, stucco, CMUs and EIFS	Tintable, equalizes absorption rate, breathability
<b>Thoro® Primer 2K</b>	Semi-opaque	Waterborne, acrylic, semi-opaque, primer	Exterior/interior: surfaces that exhibit chalk/dust after cleaning	Enhances adhesion, cool temperature application
<b>Thoro® Block Filler</b> (White color)		Water-based, acrylic, block filler	Building exterior: over all CMUs	Fills pores, improves coating coverage
<b>Flexcoat™</b>	Smooth, Fine, Medium	Elastomeric, water-based, 100% acrylic coating	Building exterior: over stucco, masonry, concrete and EIFS	Elongation, waterproofing against wind-driven rain
<b>Colorflex™</b>	Smooth	Elastomeric, water-based, 100% acrylic coating	Building exterior: over stucco, masonry, concrete and EIFS	Elongation, waterproofing against wind-driven rain, CO <sub>2</sub> resistance
<b>Silflex®</b>	Smooth	Elastomeric, silicone-modified, water-based, acrylic coating	Building exterior: over stucco, masonry, concrete and EIFS	High elongation, waterproofing against wind-driven rain, CO <sub>2</sub> resistance
<b>Super Colorcoat™ VOC</b>	Smooth, Fine	High-build, waterborne acrylic coating	Building exterior: over concrete, masonry and stucco	Application down to 35° F, CO <sub>2</sub> resistance, breathability
<b>Sealcoat™</b>	Smooth, Coarse	Water-based, 100% acrylic coating	Building exterior: over concrete, masonry, stucco and EIFS	High breathability, waterproofing against wind-driven rain
<b>Chalky Surface Primer VOC</b>		Waterborne, clear, acrylic primer	Building exterior: over chalky painted surfaces, new concrete and stucco	Improves adhesion, cool temperature application
<b>Block Filler 749</b>		Water-based, acrylic block filler	Building exterior: over all CMUs	Fills pores, improves coating coverage

**BASF Construction Chemicals – Building Systems is an industry leader in the manufacture of construction chemicals and building products for the construction industry.**

Its widely recognized brands – Sonneborn®, Thoro®, MBT Protection and Repair, Hydrozo®, SELBY®, UCRETE®, and SRS DEGADUR® provide an expansive product offering that includes joint sealants, grouts, waterproofing membranes, concrete repair products, clear sealers, performance flooring, and wall coatings.



**Building Systems** has a truly unique ability to bundle its products into comprehensive “building systems” that offer designers and contractors effective single-source solutions to their building and construction problems. Our sales force, technical services, and research & development groups, work together to ensure we meet your project needs.

**For every building challenge there's a Building Systems solution... everything you need to build, repair and protect.**

Distributed by: **BEST MATERIALS LLC**  
Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014  
Email: [sales@bestmaterials.com](mailto:sales@bestmaterials.com) [www.bestmaterials.com](http://www.bestmaterials.com)

**BASF Construction Chemicals, LLC  
Building Systems**

889 Valley Park Drive  
Shakopee, MN 55379

[www.BuildingSystems.BASF.com](http://www.BuildingSystems.BASF.com)

**Customer Service** 800-433-9517  
**Technical Service** 800-243-6739

LIMITED WARRANTY NOTICE Every reasonable effort is made to apply BASF's exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, BASF MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and BASF shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the BASF Technical Manager.

This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, BASF disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. BASF SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. BASF reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

**For professional use only. Not for sale to or use by the general public.**

Form No. 1024900 © 2009 BASF 3/09 Printed in U.S.A.