

15/16 Gauge Finish Nailer

SPOTNAILS®

XB1564

Applications

Cabinet Assembly, Door & Window Manufacturing,
Drawer Assembly, Finish Carpentry, Hardwood
Flooring, Trim Molding



For Best Results Use Spotnails® Collated Fasteners

Specifications

Fastener Length	1" to 2-1/2"
Fastener Gauge	15/16 Gauge
Capacity	100 Brads
Firing Mode	Restrictive
Length	10" x 3" x 10-1/2"
Weight	4.4 lbs

Features

360° Adjustable Exhaust, Adjustable
Depth Control, No Mar Tips, Quick
Clear Nose, Rear Load Magazine,
Rubber Grip For Comfort, Bump
Fire Trigger Included

Includes

Plastic Carrying Case, Safety
Glasses, Tool Oil, Manual,
Parts Diagram

15 Gauge Brads

Stock No.	Length	Desc.	M/Bx	Bx/ Cs	M/Cs	Lbs/ Cs	Cs/ Skid
1512PG	1-1/2"	Galv.	2.5	10	25.0	43.30	64
1514PG	1-3/4"	Galv.	2.5	10	25.0	50.10	60
1516PG	2"	Galv.	2.5	10	25.0	56.10	48
1520PG-15M	2-1/2"	Galv.	2.5	6	15.0	42.70	48

16 Gauge Brads

5M BOXES

16516	1"	Galv.	5.0	6	30.0	24.70	90
16520	1-1/4"	Galv.	5.0	6	30.0	31.70	72
16524	1-1/2"	Galv.	5.0	6	30.0	37.70	54
16528	1-3/4"	Galv.	5.0	6	30.0	42.80	48
16532	2"	Galv.	5.0	4	20.0	32.90	60
16536	2-1/4"	Galv.	5.0	4	20.0	37.20	60
16540	2-1/2"	Galv.	5.0	4	20.0	41.40	60

2.5M BOXES

16220	1-1/4"	Galv.	2.5	10	25.0	26.80	64
16224	1-1/2"	Galv.	2.5	10	25.0	30.90	60
16228	1-3/4"	Galv.	2.5	10	25.0	35.90	60
16232	2"	Galv.	2.5	10	25.0	40.20	60
16236	2-1/4"	Galv.	2.5	10	25.0	47.00	45
16240	2-1/2"	Galv.	2.5	10	25.0	50.90	48

304 Stainless Steel - 2.5M BOXES

16224SS	1-1/2"	304 SS	2.5	10	25.0	30.00	180
16232SS	2"	304 SS	2.5	10	25.0	40.00	180
16240SS	2-1/2"	304 SS	2.5	10	25.0	50.00	180

1M Clamshell Pack

16124	1-1/2"	Galv.	1.0	8	8.0	10.00	180
16132	2"	Galv.	1.0	8	8.0	13.20	180
16140	2-1/2"	Galv.	1.0	8	8.0	16.50	180

304 Stainless Steel - 1M Clamshell Pack

16124SS-8M	1-1/2"	304 SS	1.0	8	8.0	10.00	180
16132SS-8M	2"	304 SS	1.0	8	8.0	13.20	180
16140SS-8M	2-1/2"	304 SS	1.0	8	8.0	16.50	180

316 Stainless Steel - 1M Clamshell Pack

16124SS-8M-316	1-1/2"	316 SS	1.0	8	8.0	10.00	180
16132SS-8M-316	2"	316 SS	1.0	8	8.0	13.20	180
16140SS-8M-316	2-1/2"	316 SS	1.0	8	8.0	16.50	180