



The Chemical Company

Technical Bulletin

07

Cementitious
Waterproofing

MasterSeal[®] Traffic 1500 Pedestrian System

FORMERLY SONOGUARD[®] AND SONOSHIELD[®] 590/595

MasterSeal Traffic 1500 Pedestrian System has been evaluated for compatibility and performance in the State of Florida. This combined system provides a decorative pedestrian surface with the added benefit of a waterproofing membrane, with limited crack bridging capabilities.

The following is an outline for the recommended products and procedures for applying our MasterSeal Traffic 1500 system.

- MasterSeal M 200 — Surface preparation and application should be conducted as stated in our published product data guide.
- MasterSeal TC 225 — Apply 20 wet mils using a notched squeegee at 80 ft²/gallon. Immediately back roll to level the coating and while the coating is still wet, broadcast 60 mesh aggregate to refusal (approximately 50 – 60 lbs/100 ft².) Allow to cure overnight. Remove all loose aggregate by sweeping or vacuuming surface.

HEALTH , SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting www.master-builders-solutions.basf.us, e-mailing your request to basfbscst@basf.com or calling 1(800) 433-9517. Use only as directed. For medical emergencies only, call ChemTrec® 1(800)424-9300.

LIMITED WARRANTY NOTICE

BASF warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. **BASF MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS.** The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is the replacement of product or refund of the purchase price, at the sole option of BASF. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. **BASF WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.**

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. BASF reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.