



The Chemical Company

January 13, 2014

**MasterSeal® HLM 5000 (Formerly HLM 5000)  
Product Information Statement for LEED® 2009 Credit Documentation**

MasterSeal® HLM 5000 is a single component, moisture curing, bitumen modified polyurethane elastomeric waterproofing membrane.

BASF Corporation certifies the following information for MasterSeal® HLM 5000:

**Recycled Content**

MasterSeal® HLM 5000 recycled content is not available at this time and should be assumed to be 0% for the purposes of LEED reporting.

**Regional Materials**

MasterSeal® HLM 5000 is manufactured in **Brighton, CO**. Extraction and processing location is not available at this time.

**VOC Content**

MasterSeal® HLM 5000 has a VOC (Volatile Organic Compound) content as follows:

Trowel Grade	132 g/L	Self-leveling Grade	183 g/L
Roller Grade	180 g/L	Spray Grade	190 g/L

Based upon the above information, BASF Corporation certifies that MasterSeal® HLM 5000 could contribute to the following LEED NC Credits:

**IEQ Credit 4.2:** Low Emitting Materials: Paints & Coatings

Respectfully,  
LEED Administrator  
BASF Corporation  
Tel: 800-243-6739



"LEED" is a trademark of the  
U.S. Green Building Council

BASF Corporation  
Construction Systems  
889 Valley Park Drive  
Shakopee, MN 55379

Distributed by: **BEST MATERIALS®**  
Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014  
[www.BestMaterials.com](http://www.BestMaterials.com) Email: [Sales@BestMaterials.com](mailto:Sales@BestMaterials.com)

