

Product Data Sheet EverGuard® Sealants

Description

GAF EverGuard® single-ply roofing systems include a full line of EverGuard®/GAF sealants.

Note: EverGuard®/GAF sealants are specially formulated for specific applications: be sure to use the correct sealant for the application. The following EverGuard®/GAF sealants are available:

Product	Description	Benefit/Application	Units Per Carton	Carton Weight
EverGuard® Water Block	One-part butyl-based high-viscosity sealant	<ul style="list-style-type: none"> • Suitable for sealing between flashing membrane and substrate surface behind exposed termination bars • Suitable for sealing between roofing membrane and drain flanges 	25 10.5 oz. cartridges	13 lbs.
EverGuard® 2-Part Pourable Sealant	100% solids urethane-based two-part sealant	<ul style="list-style-type: none"> • Suitable for filling sealant pans at irregularly-shaped penetrations 	1 kit = 1 gal Part A and 1 pint Part B 2 kits per carton	18 lbs.
EverGuard® TPO & PVC Cut Edge Sealant	Sealant used at any non-factory edge of TPO and PVC membrane	<ul style="list-style-type: none"> • Used to seal non-factory edges (out edges) as a final step in reinforced membrane installation • PVC Cut Edge with PVC • TPO Cut Edge with TPO 	<ul style="list-style-type: none"> • 12 pints/ctn. • 100 lineal feet per pint @ 1/8" diameter bead. 	12 lbs.

Storage: • Store sealants in original containers on pallets or shelving in a dry area.
 • Store sealants in 50-100°F conditioned area away from open flame or other combustion source.
 • Do not allow to freeze.