



A Skellerup Industries Company

Retrofit™ Original



When it has to flash around, not over

CHECK THE BENEFITS!

- ✓ Fast & Efficient installation
Wraps around existing or difficult to access pipes
- ✓ Snaps together in seconds
The built-in crimp means no loose clips or rivets
- ✓ Grips tight and stays tight
Made from DEKS'S quality polymer compound
- ✓ Our base makes easy work
Aluminum base conforms to roof with ease
- ✓ Twenty year warranty
Just fit it and forget it – we've got you covered



FS 520679
QUALITY ISO9001

Distributed by: **BEST MATERIALS®**
Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014
www.BestMaterials.com Email: Sales@BestMaterials.com

Installation Instructions



1

Trim cone to suit pipe size using tin snips.



2

With clip in downstream position, wrap top of cone around pipe and engage metal teeth in opposing pockets starting at the top.



3

To assist locating clip into pocket, place hand behind seam. Fasten clip with pliers or multigrips, working from top to base. Do not over crimp.



4

Apply sealant to underside of Dektite® base and shape to roof by hand.



5

Fasten flashing down and secure clip by placing a fastener either side of clip first.



6

Apply sealant to top of crimp closure and any other potential leak areas.

EASY SELECTION GUIDE

Code No	Pipe mm	Pipe inch	Base mm	Pitch	Base inches
RF 801	20-70	3/4 - 2 3/4"	160	0-40° or 10/12	6 1/8"
RF 802	50-190	2 - 7 1/2"	273	0-40° or 10/12	10 3/4"
RF 803	85-255	3 1/4 - 10"	369	0-40° or 10/12	14 1/2"
RFS 4	235-425	9 1/4 - 16 3/4"	762 x 680	0-40° or 10/12	30 x 26 3/4"

Black (EPDM)*

Grey (EPDM)*

Code No	Pipe mm	Pipe inch	Base mm	Pitch	Base inches
RF 901	20-70	3/4 - 2 3/4"	160	0-40° or 10/12	6 1/8"
RF 902	50-190	2 - 7 1/2"	273	0-40° or 10/12	10 3/4"
RF 903	85-255	3 1/4 - 10"	369	0-40° or 10/12	14 1/2"
RFS24	235-425	9 1/4 - 16 3/4"	762 x 680	0-40° or 10/12	30 x 26 3/4"

Red Silicone

Available in Black and Grey EPDM or Red Silicone

EPDM will withstand constant temperatures at the roofline of -50°C (-122°F) to 115°C (239°F) & up to 150°C (302°F) intermittently.

Red Silicone will withstand constant temperatures at the roofline of -50°C (-112°F) to 200°C (392°F) & up to 250°C (482°F) intermittently.

For higher temperatures always use the Dektite Silicone range. Go to www.deks.com.au for more information on the full range.



Need to flash a square penetration? Contact DEKS to discuss the square flashing range.

Distributed by: **BEST MATERIALS ®**

Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014

www.BestMaterials.com Email: Sales@BestMaterials.com