

**CHEM LINK Products, LLC**

Distributed by: **BEST MATERIALS**®  
Ph: 800-474-7570, 602-272-8128  
Fax: 602-272-8014  
[www.BestMaterials.com](http://www.BestMaterials.com)  
Email: [Sales@BestMaterials.com](mailto:Sales@BestMaterials.com)

Last Revision: 02/20/13  
Document No. L1360

**Product Description**

**E-Curb** penetration seals replace old-style roof boots and metal pitch pans with versatile, precast components and 100% solid, gun grade sealants. CHEM LINK's **E-Curb** system can usually be installed in under 15 minutes and never require flashing or mechanical attachment.

**E-Curbs** are designed for use on sloped substrates and metal standing seam roofing. **E-Curbs** are specified for most all types of roofing materials. **DuraLink's** adhesion to difficult surfaces permits its use on anodized metal and coatings such as Kynar 500® PVDF.

**Special Characteristics**

- Rapid installation - "Slip-fit" light weight curb design reduces labor significantly.
- Excellent adhesion to most roofing materials.
- No flashing or mechanical attachment required.
- Service Temperature -40°F to 200°F (-40°C to 93°C)
- For substrate or penetration temperatures exceeding 200°F (93°C), substitute **DuraSil™** high performance adhesive sealant for **DuraLink™**. Refer to the **DuraSil** Data Guide for limitations.
- Bonds to Kynar 500® PVDF coated metal.
- Paintable after 24 hours. Refer to the **DuraLink** Data Guide for limitations.

**Restrictions**

- Do not apply below 30°F (-1°C)
- Do not apply if rain is anticipated within 4 hours
- Do not use **DuraLink** on copper roofing. Use **DuraSil** for this application.
- Do not use on Hypalon or smooth APP modified bitumen membrane. For smooth APP, torch down a target of granulated APP before installation.
- TPO Primer must be used for TPO applications.
- Do not prime bonding surfaces with asphalt primer.
- Do not use asphalt cement as a "night sealant." Use **DuraLink** for this purpose.
- Do not use petroleum based cleaners.
- **E-Curb** kits are designed to contain enough **DuraLink** to fill each curb with displacement in consideration. Refer to our penetration calculator under contractor resources at [chemlink.com](http://chemlink.com) to verify volumes.



**E-Curb System Components**

- **E-Curb** exterior rings, straights, and corners.
- **DuraLink** Super Adhesion Sealant used for bonding the **E-Curb** components, sealing and priming the penetration.
- **DuraLink** is also used to form a durable, water-tight seal around the roof penetration.

**DuraLink** Super Adhesion Sealant is a durable, self-fixturing moisture cure mastic. Cartridges of **DuraLink** are supplied in each E-Curb Kit. Components are also sold separately.

**E-Curb** precast form components are composed of light weight nylon resin. The E-Curb is 2-inches high and is available in a variety of shapes and sizes. Sizes available include: bisected circular pieces having inside diameters of 3, 4, 6, or 9 inches. Corner pieces having a 2-inch, radius and 8-inch straight pieces are also available to create larger sizes. The outer surface is impervious to ice, corrosion, UV (ultraviolet) light and ponding water.

When installed properly, this system forms a durable, waterproof, rubber seal around penetrations. An extended warranty against leaks is activated with submittal of a completed warranty card.

### Step 1

Remove all previously applied caulk, mastic, cement, asphalt, and other contaminants from penetrations with a wire brush. Clean all smooth substrates with isopropyl or denatured alcohol. DO NOT use petroleum solvents. Seal the base of each penetration with **DuraLink**. Coat penetrations with **DuraLink** to 3" above the roof line.



### Step 2

Hold a section of **E-Curb**, flat side up, and apply a 1/4" bead of **DuraLink** to the entire bottom perimeter. Apply 1 additional 1/4" bead of **DuraLink** down the center of the section. Do not tool the beads flat. Place the **E-Curb** section on the roof surface to form a half circle around the penetration(s). Press down firmly until **DuraLink** extrudes from the outside edges.



### Step 3

Apply **DuraLink** to the second section of **E-Curb** as described above. Place the second section of curb on the roof surface to form a circle with the first section. Press firmly in place until excess adhesive extrudes from the outside edges. Apply a bead of **DuraLink** around the outside base of the installed **E-Curb** and tool to form a smooth fillet.



### Step 4

Pump the **E-Curb** full with **DuraLink**. Use the provided tongue depressor to smooth and level **DuraLink** to finish.

**Note:** To provide an adequate rubber seal, maintain a 1" distance between penetrations and inside edge of the E-Curb.



All properties described in this document are derived from testing conducted in laboratory conditions. Properties and performance will vary depending on environmental conditions and application technique. Test and evaluate to determine appropriate usage. Visit [www.chemlink.com](http://www.chemlink.com) for the Material Safety Data Sheet, Technical Data Guides and full warranty for this product.

LIMITED WARRANTY: **CHEM LINK Products, LLC** warrants this product's performance, provided it is properly stored and applied within 1 year. If not satisfied, return remaining product and purchase receipt for refund or replacement of product exclusive of labor or cost of labor. This is the sole and exclusive remedy for defects or failure of this product. User must read and follow the direction of the current Technical Data Guide and MSDS prior to product use. User determines suitability of product for intended use and assumes all risks. Manufacturer shall not be liable for damages (including consequential or incidental damages) in excess of the purchase price, except where such exclusion or limitation is prohibited by state law. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, STATUTORY, EXPRESS OR IMPLIED INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE; except for the above express warranty given by manufacturer, the product is sold with all faults. **CHEM LINK PRODUCTS, LLC** SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS. This warranty gives you specific legal rights, and you may also have other rights in the U.S. which vary from state to state. For warranty claim information, call 800-826-1681.

