



## GREAT STUFF PRO™ WINDOW & DOOR INSULATING FOAM SEALANT

Distributed by Best Materials® LLC  
For more information call:  
1-800-474-7570, 602-272-8128  
Website: [www.bestmaterials.com](http://www.bestmaterials.com)  
E-mail: [sales@BestMaterials.com](mailto:sales@BestMaterials.com)

### PRODUCT NAME

GREAT STUFF PRO™ Window & Door  
Insulating Foam Sealant

### MANUFACTURER

The Dow Chemical Company  
Dow Building Solutions  
200 Larkin  
Midland, MI 48674  
1-866-583-BLUE (2583)  
Fax 1-989-832-1465

Dow Chemical Canada ULC  
Dow Building Solutions  
450 – 1st St. SW, Suite 2100  
Calgary, AB T2P 5H1  
1-866-583-BLUE (2583) (English)  
1-800-363-6210 (French)

[www.dowgreatstuff.com](http://www.dowgreatstuff.com)

### PRODUCT DESCRIPTION

GREAT STUFF PRO™ Window & Door Insulating Foam Sealant is a one-component, minimal expanding, low pressure-build,\* flexible polyurethane foam exclusively formulated to air seal the gap around a window or door frame and the rough opening. The foam expands to generate an effective seal, and when applied properly is proven not to distort or bow window and door frames.

### BASIC USE

GREAT STUFF PRO™ Window & Door Insulating Foam Sealant is designed to form a durable, airtight, water-resistant bond to vinyl, wood and metal surfaces. Its foam skin repels and deflects water, which can help reduce the potential for moisture damage in frame openings.

GREAT STUFF PRO™ Window & Door:

- Expands to take the shape of cracks and voids, helping stop drafts
- Reduces pathways where insects can enter
- Is tack-free in 5-10 minutes, trims within 1 hour, fully cured in 12 hours\*\*

### SIZES

GREAT STUFF PRO™ Window & Door Insulating Foam Sealant is available in gun- and straw-applied versions. See Table 1 for size and estimated yields.

### ACCESSORIES

Using one of several PRO Series foam dispensing guns simplifies the application of GREAT STUFF PRO™ Window & Door. In addition to enabling pinpoint application control, an airtight and moisture-tight seal between the gun and the can prevents the foam from curing and blocking the dispensing valve, allowing a can to be reused.

GREAT STUFF PRO™ Gun Cleaner simplifies cleanup of uncured polyurethane foam from dispensing guns.

### TECHNICAL DATA

#### APPLICABLE STANDARDS

GREAT STUFF PRO™ Window & Door Insulating Foam Sealant conforms to ASTM E2112 – Standard Practice for Installation of Exterior Windows, Doors and Skylights. It has also been tested to the following standards using a 1 cm-wide gap assembly:

- ASTM E84 – Standard Test Method for Surface Burning Characteristics of Building Materials
- ASTM E283 – Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Curtain Walls and Doors Under Specified Pressure Differences Across the Specimen
- ASTM E331 – Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors and Curtain Walls by Uniform Static Air Pressure Difference
- ASTM E547 – Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors and Curtain Walls by Cyclic Static Air Pressure Difference
- ASTM C1620 – Standard Specification for Aerosol Polyurethane and Aerosol Latex Foam Sealants
- CAN/ULC S710.1 – Standard for Thermal Insulation – Bead-Applied One Component Polyurethane Air Sealant Foam, Part 1: Material Specification

For more information on standards/test approvals and classifications, see Table 2.

Contact your Dow sales representative or local authorities for state/provincial and local building code requirements and related acceptances.

#### PHYSICAL PROPERTIES

GREAT STUFF PRO™ Window & Door Insulating Foam Sealant exhibits the typical physical properties indicated in Table 3 when tested as represented.

#### INSTALLATION

GREAT STUFF PRO™ Window & Door should be applied at temperatures between 40°F and 100°F (4°C and 38°C) at relative humidity  $\geq$  20 percent. Surface where applied should be free of dust, grease, oil, wax and release agents. Damp surfaces will not impair the bond.

#### SAFETY AND CONDITIONS OF USE

- Read the label and Material Safety Data Sheet carefully before use.
- GREAT STUFF PRO™ Insulating Foam Sealants contain isocyanate and a flammable blowing agent. Vapor may travel to other rooms. Ensure adequate ventilation. Shut off all pilot lights and extinguish open flames; eliminate all sources of ignition before use. Do not smoke or use lighters or matches while dispensing foam.
- Do not breathe vapor or mist. Use in well-ventilated areas or wear proper respiratory protection. Isocyanate is irritating to the eyes, skin and respiratory system, and may cause sensitization by inhalation or skin contact.

**TABLE 1: SIZE AND ESTIMATED YIELDS FOR GREAT STUFF PRO™ WINDOW & DOOR INSULATING FOAM SEALANT**

CAN SIZE, OZ (G)	DELIVERY	NO. OF WINDOWS <sup>(1)</sup>
20 (567)	Straw	6-9
20 (567)	Gun	8-11

<sup>(1)</sup> Estimated yield under ideal conditions for 36" x 60" (0.9 m x 1.5 m) window, 3/8" (0.9 cm) wide gap, 1" (25 mm) deep, 3/8" bead

**TABLE 2: GREAT STUFF PRO™ WINDOW & DOOR INSULATING FOAM SEALANT APPROVALS/CLASSIFICATIONS**

STANDARD	RESULT
ASTM E283	Air leakage <0.01 cfm/ft <sup>2</sup> at 6.24 psf pressure (or 50 mph wind speed) in 1 cm-wide gap
ASTM E331/E547	No water leakage at 12 psf negative pressure in 1 cm-wide gap
AAMA 812-04	Conforms to standard at 0.08 psi pressure-build (gun foam)
ABAA Specifications	Meets sealant component air barrier requirements
UL Classified	Classified per UL 723 as under UL File R13655
CCMC 13074-L CAN/ULC S710.1	Meets stringent CAN/ULC durability requirements as air leakage control sealant
ICC-ES ESR-1961	Evaluated as an insulating sealant

- GREAT STUFF PRO™ foam is very sticky and will adhere to most surfaces and skin. Do not get foam on skin. Wear long sleeves, gloves, and goggles or safety glasses. Cured foam must be mechanically removed or allowed to wear off in time.
- The contents are under pressure. The can may burst if left in areas susceptible to high temperatures, such as motor vehicles, or near radiators, stoves or other sources of heat. Do not place can in hot water. Do not puncture, incinerate or store at temperatures above 120°F (49°C).
- Cured GREAT STUFF PRO™ foam is combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). GREAT STUFF PRO™ foam should not be used around heaters, furnaces, fireplaces, recessed lighting fixtures or other applications where the foam may come in contact with heat-conducting surfaces. For proper ventilation of combustion appliances, visit [www.epa.gov/iaq/homes/hip-ventilation.html](http://www.epa.gov/iaq/homes/hip-ventilation.html).
- Do not inject GREAT STUFF PRO™ foam into large or confined cavities such as behind holes in drywall or under tub wall surrounds where flammable vapors may collect. Foam must be exposed to atmospheric moisture to thoroughly cure.

Visit [www.dowbuildingsolutions.com](http://www.dowbuildingsolutions.com) or contact a local Dow representative for more specific instructions.

#### AVAILABILITY

GREAT STUFF PRO™ Window & Door Insulating Foam Sealant is distributed through an extensive network. For more information, call: 1-800-232-2436 (English) 1-800-565-1255 (French)

#### WARRANTY

GREAT STUFF PRO™ Window & Door Insulating Foam Sealant is expressly warranted for a period of 10 years when used as part of a WEATHERMATE™ Weather Barrier Solutions installation. See warranty document (Form No. 179-07374) or [www.dowbuildingsolutions.com](http://www.dowbuildingsolutions.com) for details.

#### MAINTENANCE

GREAT STUFF PRO™ Window & Door has a shelf life of 18 months when stored at 75°F (24°C).

#### TECHNICAL SERVICES

Dow can provide technical information to help address questions when using GREAT STUFF PRO™ Window & Door Insulating Foam Sealant. For technical assistance, call:

1-866-583-BLUE (2583) (English)  
1-800-363-6210 (French)

#### FILING SYSTEMS

[www.dowbuildingsolutions.com](http://www.dowbuildingsolutions.com)  
[www.sweets.com](http://www.sweets.com)

**TABLE 3: TYPICAL PHYSICAL PROPERTIES<sup>(1)</sup> OF GREAT STUFF PRO™ WINDOW & DOOR INSULATING FOAM SEALANT**

PROPERTY AND TEST METHOD	VALUE
Flexural Strength, ASTM C203, Parallel to rise, psi (kPa), min.	5.2 (35.9)
Apparent Aged k-factor (Thermal Conductivity) per inch (25 mm), ASTM C518 @75°F (24°C) mean temp., Btu•in/ft <sup>2</sup> •hr•°F (W/m•°C), min.	0.262 (0.038)
Compressive Strength, ASTM D1621, Parallel to rise, psi (kPa)	2.8 (19.2)
Apparent Density, ASTM D1622, pcf (kg/m <sup>3</sup> )	1.63 (26)
Dimensional Stability, ASTM D2126, % Volume Change 100°F/100%RH@1wk -40°F/ambRH@1wk	-0.646 1.306
Open Cell Content, ASTM D6226, %	<88.00
Tensile Strength, ASTM D1623, Parallel to rise, psi (kPa)	5.7 (39.3)
Elongation, %, "Test immed. after cut"	19.6
Shear Strength, ASTM C273, Parallel to rise, psi (kPa)	7.07 (48.7)
Flame Spread/Smoke Developed <sup>(2)</sup> , ASTM E84	10/20

<sup>(1)</sup> Not to be considered sales specifications

<sup>(2)</sup> This numerical flame spread rating is not intended to reflect hazards presented by this or any other material under actual fire conditions.

NOTICE: No freedom from any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries or regions. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DOW. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult MSDS, call Dow at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

GREAT STUFF PRO™ Insulating Foam Sealants contain isocyanate and a flammable blowing agent. Read the label and Material Safety Data Sheet carefully before use. Eliminate all sources of ignition before use. Wear long sleeves, gloves, and safety glasses or goggles. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure.

GREAT STUFF PRO™ Gun Cleaner is flammable and contains acetone and propane. Read the label and Material Safety Data Sheet carefully before use. Eliminate all sources of ignition before use. Wear gloves, and goggles or safety glasses. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

#### IN THE U.S.

FOR TECHNICAL INFORMATION: 1-866-583-BLUE (2583)

FOR SALES INFORMATION: 1-800-232-2436

THE DOW CHEMICAL COMPANY

Dow Building Solutions • 200 Larkin • Midland, MI 48674

#### IN CANADA

FOR TECHNICAL INFORMATION: 1-866-583-BLUE (2583) (English) • 1-800-363-6210 (French)

FOR SALES INFORMATION: 1-800-232-2436 (English) • 1-800-565-1255 (French)

DOW CHEMICAL CANADA ULC

Dow Building Solutions • Suite 2100 • 450 – 1st St. SW • Calgary, AB T2P 5H1

a proud partner of



Printed in U.S.A.

[www.dowgreatstuff.com](http://www.dowgreatstuff.com)

Form No. 179-07324X-1212MCK  
178-00746X-1212MCK

