



GENERAL INFORMATION

**ROOFING FASTENERS**  
**ROOFING SPIKE®**  
 Anchor

**GENERAL INFORMATION**

## ROOFING SPIKE®

Anchor

**PRODUCT DESCRIPTION**

For roofing applications, the Spike is a one-piece, vibration resistant anchor available for use to fasten insulation, single-ply membrane, wood, and metal to structural concrete roof decks. This version of the Spike has a Perma-Seal™ coating, and is designed for use in conjunction with Powers stress plates for insulation and membrane attachments.

**GENERAL APPLICATION AND USES**

- Fastening insulation, single-ply membrane, wood and metal to structural concrete decks.

**APPROVALS AND LISTINGS**

- FM Global (FM Approvals) - see listings  
 Structural Concrete Deck – J.I. 1K6A7.AM, J.I. 0N9A2.AM, J.I. 1M4A5.AM  
 Fully Adhered Single-Ply and Modified Bitumen Coverings (All Decks) – J.I. 1T9A4.AM


**MATERIAL SPECIFICATIONS**

| Anchor component | Component Material     |
|------------------|------------------------|
| Fastener Body    | Grade 8.2 Carbon Steel |
| Coating          | Perma-Seal             |


**INSTALLATION SPECIFICATIONS**

| Dimension                    | Mushroom Head Roofing Spike |
|------------------------------|-----------------------------|
| ANSI Drill Bit Size (in.)    | 1/4                         |
| Fixture Clearance Hole (in.) | 5/16                        |
| Head Size, O.D. (in.)        | 1/2                         |
| Head Height (in.)            | 7/64                        |

**INSTALLATION GUIDELINE**



Drill a hole into the base material to the depth of at least 1/2" deeper than the embedment required. The tolerances of the drill bit used should meet the requirements of ANSI Standard B212.15. Remove the dust and debris from the hole during drilling (e.g. dust extractor, hollow bit) or following drilling (e.g. suction, forced air) to extract loose particles created by drilling.



Drive the anchor through the plate into the anchor hole until the head is firmly seated. Be sure the anchor is driven to the required embedment depth.

**SECTION CONTENTS**

General Information..... 1  
 Installation Guideline..... 1  
 Performance Data..... 2  
 Ordering Information..... 2



ROOFING SPIKE

**ANCHOR MATERIALS**

- Perma-Seal Coated Carbon Steel

**ANCHOR SIZE RANGE (TYP.)**

- 1/4" x 1-1/4" to 1/4" x 14"

**SUITABLE BASE MATERIALS**

- Normal-Weight Concrete
- Grouted Concrete Masonry (CMU)

For more information  
 Or to buy this product  
[Click here](#)

**PERFORMANCE DATA**

**Ultimate Load Capacities for Roofing Spike in Normal-Weight Concrete<sup>1</sup>**

| Anchor Diameter in. (mm) | Minimum Embedment Depth in. (mm) | Minimum Concrete Compressive Strength (f'c) |                 |                      |                 |                      |                 |
|--------------------------|----------------------------------|---|-----------------|----------------------|-----------------|----------------------|-----------------|
|                          |                                  | 3,000 psi (20.7 MPa)                        |                 | 4,000 psi (27.6 MPa) |                 | 5,000 psi (34.5 MPa) |                 |
|                          |                                  | Tension lbs. (kN)                           | Shear lbs. (kN) | Tension lbs. (kN)    | Shear lbs. (kN) | Tension lbs. (kN)    | Shear lbs. (kN) |
| 1/4 (6.4)                | 1-1/4 (31.8)                     | 1,100 (5.0)                                 | 2,500 (11.3)    | 1,500 (7.0)          | 2,750 (12.4)    | 1,700 (7.7)          | 2,750 (12.4)    |

1. The values listed above are ultimate load capacities which should be reduced by a minimum safety factor of 4.0 or greater to determine the allowable working load.

**Allowable Load Capacities for Roofing Spike in Normal-Weight Concrete<sup>1,2</sup>**

| Anchor Diameter in. (mm) | Minimum Embedment Depth in. (mm) | Minimum Concrete Compressive Strength (f'c) |                 |                      |                 |                      |                 |
|--------------------------|----------------------------------|---|-----------------|----------------------|-----------------|----------------------|-----------------|
|                          |                                  | 3,000 psi (20.7 MPa)                        |                 | 4,000 psi (27.6 MPa) |                 | 5,000 psi (34.5 MPa) |                 |
|                          |                                  | Tension lbs. (kN)                           | Shear lbs. (kN) | Tension lbs. (kN)    | Shear lbs. (kN) | Tension lbs. (kN)    | Shear lbs. (kN) |
| 1/4 (6.4)                | 1-1/4 (31.8)                     | 275 (1.2)                                   | 625 (2.8)       | 390 (1.8)            | 690 (3.1)       | 425 (1.9)            | 690 (3.1)       |

1. Allowable load capacities listed are calculated using an applied safety factor of 4.0.

2. Linear interpolation may be used to determine allowable loads for intermediate compressive strengths.

**Ultimate and Allowable Load Capacities for Roofing Spike in Grouted Concrete Masonry<sup>1,2</sup>**

| Anchor Diameter in. (mm) | Minimum Embedment Depth in. (mm) | f'm ≥ 2,000 psi (13.7 MPa) |                 |                   |                 |
|--------------------------|----------------------------------|----------------------------|-----------------|-------------------|-----------------|
|                          |                                  | Ultimate Load              |                 | Allowable Load    |                 |
|                          |                                  | Tension lbs. (kN)          | Shear lbs. (kN) | Tension lbs. (kN) | Shear lbs. (kN) |
| 1/4 (6.4)                | 1-1/4 (31.8)                     | 800 (3.6)                  | 2,100 (9.5)     | 160 (0.7)         | 420 (1.9)       |

1. Tabulated load values are for anchors installed in minimum 6-inch wide, Grade N, Type II, medium and normal-weight concrete masonry units. Mortar must be minimum Type N. Grout must be coarse grout complying with ASTM C476. Masonry prism compressive strength must be 2,000 psi minimum at the time of installation.

2. Allowable loads are based on average ultimate values using a safety factor of 5.0.

**ORDERING INFORMATION**

**Roofing Spike**

| Cat. No. | Anchor Size   | Drill Diameter | Min. Embed. | Box Qty. | Carton Qty. |
|----------|---------------|----------------|-------------|----------|-------------|
| 3811     | 1/4" x 1-1/4" | 1/4"           | 7/8"        | 500      | 500         |
| 3723     | 1/4" x 1-1/2" | 1/4"           | 1-1/4"      | 500      | 500         |
| 3725     | 1/4" x 2"     | 1/4"           | 1-1/4"      | 500      | 500         |
| 3727     | 1/4" x 2-1/2" | 1/4"           | 1-1/4"      | 500      | 500         |
| 3729     | 1/4" x 3"     | 1/4"           | 1-1/4"      | 500      | 500         |
| 3731     | 1/4" x 3-1/2" | 1/4"           | 1-1/4"      | 500      | 500         |
| 3733     | 1/4" x 4"     | 1/4"           | 1-1/4"      | 500      | 500         |
| 3735     | 1/4" x 4-1/2" | 1/4"           | 1-1/4"      | 500      | 500         |
| 3737     | 1/4" x 5"     | 1/4"           | 1-1/4"      | 500      | 500         |
| 3739     | 1/4" x 5-1/2" | 1/4"           | 1-1/4"      | 500      | 500         |
| 3741     | 1/4" x 6"     | 1/4"           | 1-1/4"      | 250      | 250         |
| 3743     | 1/4" x 6-1/2" | 1/4"           | 1-1/4"      | 250      | 250         |
| 3745     | 1/4" x 7"     | 1/4"           | 1-1/4"      | 250      | 250         |
| 3747     | 1/4" x 7-1/2" | 1/4"           | 1-1/4"      | 250      | 250         |
| 3749     | 1/4" x 8"     | 1/4"           | 1-1/4"      | 250      | 250         |
| 3753     | 1/4" x 9"     | 1/4"           | 1-1/4"      | 250      | 250         |
| 3757     | 1/4" x 10"    | 1/4"           | 1-1/4"      | 250      | 250         |
| 3765     | 1/4" x 11"    | 1/4"           | 1-1/4"      | 100      | 100         |
| 3769     | 1/4" x 12"    | 1/4"           | 1-1/4"      | 100      | 100         |
| 3773     | 1/4" x 13"    | 1/4"           | 1-1/4"      | 100      | 100         |
| 3777     | 1/4" x 14"    | 1/4"           | 1-1/4"      | 100      | 100         |



**Roofing Spike Installation Tool**

| Cat. No. | Description       | Guide I.D. | Std. Box |
|----------|-------------------|------------|----------|
| 3790     | Spike Driver 1000 | 1/2"       | 1        |



TECH MANUAL – ROOFING FASTENERS ©2019 POWERS – REV.A