


Distributed by: BEST MATERIALS LLC, Phoenix AZ
 800-474-7570 602-272-8128 www.BestMaterials.com
 Email: Sales@BestMaterials.com

RUBBER DRAIN TO PIPE COUPLINGS

1056 Series



1056 Series - Cast Iron or Plastic to Cast Iron or Plastic

| Part No. | Side A | | Side B | | Width C | |
|---------------------|--------|-----|--------|-----|---------|-----|
| | inches | mm | inches | mm | inches | mm |
| <u>1056-125</u> | 1.63 | 41 | 1.63 | 41 | 3.45 | 88 |
| <u>1056-150/125</u> | 1.94 | 49 | 1.63 | 41 | 3.45 | 88 |
| <u>1056-150</u> | 1.94 | 49 | 1.94 | 49 | 3.43 | 87 |
| <u>1056-215</u> | 2.41 | 61 | 1.84 | 47 | 3.39 | 86 |
| <u>1056-222</u> | | | | | | |
| <u>1056-22</u> | 2.41 | 61 | 2.41 | 61 | 3.45 | 88 |
| <u>1056-315</u> | 3.35 | 85 | 1.91 | 49 | 3.87 | 98 |
| <u>1056-350</u> | | | | | | |
| <u>1056-32</u> | 3.52 | 89 | 2.38 | 60 | 3.96 | 101 |
| <u>1056-33</u> | 3.46 | 88 | 3.46 | 88 | 3.98 | 101 |
| <u>1056-415</u> | 4.40 | 112 | 1.91 | 49 | 3.96 | 101 |
| <u>1056-42</u> | 4.40 | 112 | 2.35 | 60 | 3.88 | 99 |
| <u>1056-43</u> | 4.46 | 113 | 3.52 | 89 | 4.03 | 102 |
| <u>1056-44</u> | 4.58 | 116 | 4.58 | 116 | 4.02 | 102 |
| <u>1056-44XL</u> | | | | | | |
| <u>1056-53</u> * | 5.56 | 141 | 3.53 | 90 | 3.90 | 99 |
| <u>1056-54</u> | 5.57 | 141 | 4.26 | 108 | 3.95 | 100 |

| Part No. | Side A | | Side B | | Width C | |
|--------------------|---------------|-----|---------------|-----|----------------|-----|
| <u>1056-55</u> | 5.52 | 140 | 5.52 | 140 | 3.97 | 101 |
| <u>1056-63</u> * | 6.61 | 168 | 3.38 | 86 | 5.75 | 146 |
| <u>1056-64</u> | 6.61 | 168 | 4.46 | 113 | 5.75 | 146 |
| <u>1056-65</u> | 6.48 | 165 | 5.46 | 139 | 5.77 | 147 |
| <u>1056-66</u> | 6.60 | 168 | 6.60 | 168 | 5.74 | 146 |
| <u>1056-84</u> * | 8.51 | 216 | 4.38 | 111 | 5.99 | 152 |
| <u>1056-86</u> | 8.51 | 216 | 6.38 | 162 | 5.99 | 152 |
| <u>1056-88</u> | 8.64 | 219 | 8.64 | 219 | 6.04 | 153 |
| <u>1056-10-6</u> | 10.25 | 260 | 6.38 | 162 | 6.23 | 158 |
| <u>1056-10-8</u> | 10.25 | 260 | 8.42 | 214 | 5.98 | 152 |
| <u>1056-1010</u> | 10.63 | 270 | 10.63 | 270 | 5.89 | 150 |
| <u>1056-1210</u> | 12.50 | 318 | 10.65 | 271 | 6.37 | 162 |
| <u>1056-1212</u> | 12.52 | 318 | 12.52 | 318 | 6.32 | 161 |
| <u>1056-1512</u> | 15.75 | 400 | 12.25 | 311 | 5.71 | 145 |
| <u>1056-1515</u> | 15.44 | 392 | 15.44 | 392 | 10.00 | 254 |
| <u>1056-1815</u> * | 19.00 | 483 | 15.30 | 389 | 9.89 | 251 |
| <u>1056-1818</u> | 19.00 | 483 | 19.00 | 483 | 9.89 | 251 |
| <u>1056-2121</u> | 22.50 | 572 | 22.50 | 572 | 9.89 | 251 |
| <u>1056-2424</u> | 25.10 | 638 | 25.10 | 638 | 9.89 | 251 |
| <u>1056-2727</u> | 28.30 | 719 | 28.30 | 719 | 9.89 | 251 |

1056 Series - Condensate Pipe Connectors

| Part No. | Side A | | Side B | | Width C | |
|-----------------|---------------|-----------|---------------|-----------|----------------|-----------|
| | inches | mm | inches | mm | inches | mm |
| 1056-075 | 1.05 | 27 | 1.05 | 27 | 2.38 | 60 |
| 1056-100 | 1.31 | 33 | 1.31 | 33 | 2.40 | 61 |

* Supplied with reducer.

Maximum Test Pressure: 4.3 PSI (29.6 KPA)

Maximum Operating Temperature: 140° F nonconsistent