



## SEYMOUR ROOF PAINT

A professional grade roof paint that closely matches the original color of most roofing materials. Seamlessly blend the appearance of roofing accessories to asphalt shingles. Touch-up scratches & abrasions before or after installation. Not for anodized aluminum.

### Suggested Uses:

Flashing  
Vents  
Skylights  
Chimney caps  
Satellite dishes  
Window frames  
Siding  
Gutters

### Benefits:

Fast dry  
Easy application  
Closely matches original colors  
Durable long-term protection  
Resists fading  
Protects against rust and corrosion  
Excellent adhesion

### Packaging:

Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

### Properties:

Flammability	"Extremely Flammable"
Flash point	-4° F
Specific Gravity	0.80
Solids Content	~20%
VOC content	~59%, cannot exceed 60%
MIR value	~1.08, cannot exceed 1.20
HAPs content	9%
Storage Temperature	40-90° F
Application Temperature	50-100° F
Durability	Very Good
Abrasion Resistance	Good
Heat Resistance	250° F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years
Food contact rating	No

### Dry Time\*:

To touch	5 minutes
To recoat	20 minutes

\*At 72° F, 50% humidity,  
1.5 mil thickness

\*\*Curing/Recoat time is extended with  
multiple coats and excessively thick coats\*\*

**Gloss\*:** Flat, <5

\*as measured on a 60° gloss meter

### Available Colors:

Part #	Description	UPC Code	Part #	Description	UPC Code
16-1700	Weathered Wood	043281000628	16-1704	Birchwood	043281000666
16-1701	Cedar	043281000635	16-1705	Slate Gray	043281000673
16-1702	Hickory	043281000642	16-1706	Flat Black	043281000680
16-1703	Charcoal	043281000659	16-1710	Tile Red	043281000727