

Technical Data Sheet



**Full Fine Thread, Piercing Point, Clear Zinc, Flat Head,
PAMDrive recess, Wood to 14-18 Gauge Steel
Sub-Flooring Screws
SPCZ8200 #8 x 2" SP, CZ
PAM Fastening Technology, Inc.**

Head Diameter	8.00 – 8.50mm
Major Diameter	4.10 – 4.35mm
Minor Diameter	2.70-2.95mm
Length	50.80+-1.0mm
Access Depth	1.65 – 2.08mm
Wire Diameter	3.30mm
Surface Hardness	500-750 HV
Core Hardness	250 – 450 HV
Breaking Torque	min. 42 (KG/CM)
Penetration	$\frac{3}{4}$ "
Withdrawal	625 LBS.
Material	AISI 1022
Salt Spray Test (ASTM B-117)	24 Hours
Bent Testing	15°+

All fasteners manufactured for PAM Fastening Technology, Inc. are of a non-chemical hazardous nature.

Important Notice: The details in our sheets and other PAM publications are provided to the best of our knowledge. The contents, however, are not legally binding. In all cases we recommend that preliminary tests be carried out by the customer. In all respects our general terms of sale shall apply.

PAM®

Distributed by: [BEST MATERIALS ® LLC](#)
Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014
www.BestMaterials.com Email: Sales@BestMaterials.com