

VERSI-TITE®

Where do you use it?

Window and Door Frames
Corner Joints
Sillplate Junctions
Floor/Wall Junctions
Headers
HVAC Duct Penetrations
Utility Penetrations
Plumbing Stacks
Plumbing Shafts
Exterior Cracks
Baseboards
Electrical Outlets
Siding Edges
Vent Hoods
Roof Vents
Dryer Vents
Outside Water Faucets

By sealing off air leaks with VERSI-TITE®, you can deter drafts, evenly distribute room temperatures, inhibit mold and mildew, eliminate excess humidity, and keep pests outside of your home.



Distributed by:
BEST MATERIALS LLC
800-474-7570 602-272-8128
Email: Sales@bestmaterials.com
www.bestmaterials.com

If you need to fill large gaps or cover a large area, use VERSI-FOAM®, our two-component foam dispensing system.

VERSI-FOAM® kits include everything you need. No special training is required. No outside power source is required. It is disposable. VERSI-FOAM® has superior insulation values and sealant properties. Contact us for an information packet.



Versi Tite

Complete Home Sealing Solutions

Versi-Foam
systems

Call 800.657.0702



Versi Tite

Your Home Sealing Solution

RHH FOAM SYSTEMS, INC

Air leaks cause 40% of the heat loss in the average home.

VERSI-TITE® is a one-component polyurethane foam that can seal the many small gaps and crevices around your home to keep the conditioned air in and the elements out.

VERSI-TITE® is UL Classified (File #R13919 Caulking and Sealants) and meets ASTM E-84 Class I with a 25 Flame Spread and a 50 Smoke Developed Rating.

VERSI-TITE® is dispensed as a caulking bead to fill small cavities. Because of its minimal expansion, you can use it around doors and windows without distortion. You should fill only 35% to 50% of the cavity. The foam will expand. You can trim the excess in as little as one hour. It cures fully in 12 to 24 hours.

As a moisture-cured product, it draws humidity from the air to cure. The more humid the conditions, the faster the cure.

Ideally, VERSI-TITE® should be used in temperatures between 65°F and 100°F (18°C and 38°C). It can be used in temperatures as low as 40°F (5°C) and as high as 115°F (46°C). When used in exterior applications where the foam is exposed to sunlight, it must be covered or painted to protect it from ultraviolet rays.

VERSI-TITE® is available in 12 oz. cans and 24 oz. cans with a straw applicator, 24 oz. cans to be attached to a dispensing gun, and in a 16 lb. cylinder for large scale applications. The table to the right lists the yields for each product, along with their other physical properties.

(800) 657-0702

TECHNICAL DATA

	12 oz. Can	24 oz. Can	16 lb. Cylinder
Density	1.25 - 1.4 lb/ft ³	1.25 - 1.4 lb/ft ³	1.4 lb/ft ³
R-Factor	4 to 5 per inch	4 to 5 per inch	4 to 5 per inch
Air Barrier Properties			
ASTM E-283	< 0.01 cfm/ft ²	< 0.01 cfm/ft ²	< 0.01 cfm/ft ²
@6.24 psf	< 0.0025 cfm/ft ²	< 0.0025 cfm/ft ²	< 0.0025 cfm/ft ²
@1.57 psf	>70%	>70%	>70%
Closed Cell Content			
Tack-Free Time	Approx. 10 min.	Approx. 10 min.	Approx. 10 min.
Cutable	< 1 hour	< 1 hour	< 1 hour
Cure Time	12 to 24 hours	12 to 24 hours	12 to 24 hours
Yield*			
1/4" caulking bead	1,644 linear ft.	3,288 linear ft.	33,400 linear ft.
3/8" caulking bead	730 linear ft.	1,460 linear ft.	14,800 linear ft.
1/2" caulking bead	411 linear ft.	822 linear ft.	8,380 linear ft.
Volume	.56 cubic ft.	1.12 cubic ft.	11.4 cubic ft.

*Yields are based on theoretical calculations for comparison purposes and will vary depending on ambient conditions and particular application. Photo credits: bigstockphoto.com: "Chateau" © 2008 Jason Hines; istockphoto.com: "Luxury Home Entry" © 2008 Digital Savant LLC; "Dollar House" © 2008 Wish Photograf.



VERSI-TITE® can seal air leaks as recommended by the Energy Star® Home Sealing Process. For more information, visit: energystar.gov or call 888-782-7937.



Seal and Save!

