

1. Identification

Product Name: A-Tech 212 LV, EHV Epoxy, Part A
Synonym: Thermosetting Resin
Chemical Family: Epoxide
Manufacturer/Supplier: Applied Technologies
P.O. Box 18476
Fairfield, OH 45018
Emergency Telephone: 800-424-9300

2. Hazard(s) Identification

Signal Word: WARNING 

Skin Contact: (Rabbit) Exposure may cause moderate irritation. May cause allergic skin reaction.

Eye Contact: (Rabbit) May cause mild eye irritation.

Inhalation:

Ingestion: Oral LDO: (Rabbit) > 4000 mg/kg

Medical Conditions Generally Aggravated by Exposure: Allergy, eczema, skin conditions.

Precautionary Statements: Do not handle until all safety precautions have been read and understood. Do not breathe the vapors. In case of inadequate ventilation wear respiratory protection. Wear protective gloves and eye protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Store locked up. Keep away from children. Dispose of contents and container in accordance with applicable local, regional and national regulations.

Hazard Statements:

- Causes mild irritation to skin and eyes.
- May cause allergy or asthma symptoms.
- May cause allergic skin reaction.
- May cause respiratory irritation.

Effects of Overexposure: Irritation, sensitization and dermatitis.

Carcinogenicity: In order to comply with California Proposition 65, we feel obligated to advise that some of our products may conceivably contain trace contaminants of some of the listed chemicals. While not necessarily added to our products as ingredients, some listed chemicals may be present in the raw materials from suppliers and over which we have no control. Therefore, even though some of the listed substances may not be present, a significant risk as defined by the regulations in order to comply with California law, we feel obligated to make the following statement:

Warning: Our products may contain trace amounts of some chemicals considered by the State of California to be carcinogens or reproductive toxicants.

OSHA	ACGIH	NTP	IARC	OTHER
N/A	N/A	N/A	N/A	N/A

3. Composition / Information on Ingredients

Ingredient	% by Weight	Exposure Limit	Cas #
Diglycidyl ether resin mixture	65-95%	N.E.	25068-38-6
Proprietary diluent	5-35%	50 PPM-PEL	98-00-0
N-Butyl glycidylether	0-10%		2426-08-6

4. First Aid Measures

Eyes: Open lids wide and flush with large quantities of water for at least 15 minutes. Call a physician, preferable an eye specialist.

Skin: wash with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse, discard shoes. Consult a physician if irritation develops.

Ingestion: Do not induce vomiting without medical advice. If conscious give water. Prevent aspiration of vomit (turn victim's head to side). Consult a physician.

SP GR:

Inhalation: Remove the patients from the contaminated area to fresh air. Administer oxygen or artificial respiration as needed. Call a physician if after effects occur.

5. Fire Fighting Measures

Flash Point: > 490 DEG F CI

Flammable Limits: UK

Fire Degradation Products: Toxic fumes are released in fire situations. Acrid smoke/fumes.

Extinguishing Media: Carbon dioxide, dry chemicals, foam. Where the fire is of major proportions, water spray may also be used. Water or foam may cause frothing if liquid is burning, but it still may be a useful extinguishing agent if carefully applied to the fire.

Protective Equipment: In case of fire, use normal firefighting equipment including a NIOSH approved, self contained breathing apparatus (SCBA). Use water to cool containers.

Explosion Hazards: Decomposition and combustion products may be toxic.

6. Accidental Release Measures

Small Spill: Absorb with rag. Wear proper personal protective equipment. Place in a chemical waste container for proper disposal.

Large Spill: Absorb with dry chemical absorbent, earth, sand or any other inert material. Wear proper personal protective equipment. Place in a chemical waste container for proper disposal. Flush contaminated areas with water.

Disposal: Any disposal practice must be in compliance with all federal, state and local laws and regulations. Chemical additions, processing, storage, or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance is the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

7. Handling and Storage

Storage: Store in tightly sealed containers. Store in a cool, dry, well ventilated area away from heat and open flame. Protect from moisture.

Handling: Avoid contact with skin, eyes, and clothing. Do not take internally. Use personal protective equipment when transferring material to or from drums, totes or other containers. Safety glasses and gloves are the minimum protection. Additional precautions must be used when splash hazards are present.

Shelf Life:

Other Precautions: Avoid breathing vapors, use with good ventilation. Wash hands thoroughly with soap and water after every use.

8. Exposure Controls / Personal Protection

Respiratory Protection: Avoid breathing vapors. Use adequate ventilation.

Ventilation: Good mechanical ventilation and local exhaust.

Protection Gloves: Rubber or polyethylene.

Eye Protection: Chemical splash goggles or safety glasses.

Protective Clothing: Wear impervious clothing and gloves. Materials may include butyl rubber, nitrile rubber, neoprene and Saranex coated Tyvek.

Protective Equipment: Disposable containers and paper on work area. Use of barrier cream recommended. Use appropriate equipment to prevent eye or skin contact.

Other Precautions: Avoid breathing vapors, use with good ventilation. Wash hands thoroughly with soap and water after every use.

9. Physical and Chemical Properties

VP: N.A.

VD: N.A.

Color: Clear

Solubility In Water: Slight

Evaporation Rate: N.A.

SP GR: 1.1 - 1.2

% Volatile by VL: < 3%

Boiling Point: > 200 °F

Flash Point: > 490 °F CL

10. Stability and Reactivity

Stability: Stable under recommended storage conditions.

Reactivity:

Incompatibility Materials to Avoid: Strong oxidizers, strong acids or bases in bulk.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, aldehydes and other organics.

Conditions to Avoid: Elevated temperatures, container contamination.

11. Toxicological Information

Toxicological Data: LD SOs provided are the lowest values for type of bisphenol A diglycidal ether resins used

Oral LDO: (rabbit) > 4000 mg/kg

Routes of Entry: Inhalation, skin contact.

Effects of Overexposure: Irritation, sensitization and dermatitis.

Inhalation:

Medical Conditions of Exposure: allergy eczema, skin conditions.

Carcinogenic Categories:

NTP: Not classified as a carcinogen

IARC: Not classified as a carcinogen

OSHA: Not classified as a carcinogen

12. Ecological Information

Comments: No information.

13. Disposal Considerations

Disposal: Any disposal practice must be in compliance with all federal, state and local laws and regulations. Chemical additions, processing, storage, or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance is the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

Refer to RCRA 4 CFR 216 and/or any other appropriate federal, state or local requirements for proper classification information.

Container Disposal: Drums/containers should be decontaminated and either passed to an approved drum recycler or destroyed.

RCRA/EPA Waste Information: The generation of waste should be avoided or minimized whenever possible. Chemical waste, even small quantities, should never be poured down drains, sewers or waterways.

14. Transport Information

DOT (Domestic Surface): Shipping name; Compound resin. Not regulated (Class 55).

IMO (Ocean): Not restricted.

ICAO (Air): Not restricted.

15. Regulatory Information

TSCA Status: All ingredients are not required to be listed on the TSCA inventory

SARA Title III:

Section 311/312 Hazard Categories: This chemical is classified as a hazardous chemical due to the potential for allergic skin reaction.

Section 313 Toxic Chemicals: o the best of our knowledge this product contains no chemical subject to Sara Title III Section 313.

OSHA: This chemical is classified as a hazardous chemical due to the potential for allergic skin reaction. Standard 29 CFR 1910.1200

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal whether a material containing the product or derived from the product should be classified as a hazardous waste (40 CFR 261.20-24)

CEPA Canadian Environmental Protection Act: All ingredients in this product are listed on the DSL or are not required to be listed.

16. Other Information

All statements, technical information and recommendations contained herein are based upon available scientific test or data which we believe to be reliable since we cannot anticipate all conditions under which this information and our products or the products of other manufacturers in combination with our products may be used. Applied Technologies makes no warranties, express or implied, and assumes no responsibility in connection with any use of this information.

Personal Protection: B

NFPA Ratings:



HMIS Ratings:



1. Identification

Product Name: A-Tech 212 LV, EHV Epoxy, Part B
Synonym: Epoxy Hardener
Chemical Family: Modified Polyamine/Polyamide Composition
Manufacturer/Supplier: Applied Technologies
 P.O. Box 18476
 Fairfield, OH 45018
Emergency Telephone: 800-424-9300

2. Hazard(s) Identification

Signal Word: **WARNING** 

Skin Contact: Mild irritation.

Eye Contact: (Polyamine resin - conjunctival irritant.

Inhalation: Oral LD50 (rat) < 5 CC/KG

Ingestion: Oral LDO: (Rabbit) > 4000 mg/kg

Medical Conditions Generally Aggravated by Exposure: Allergy, eczema, skin conditions.

Precautionary Statements: Do not handle until all safety precautions have been read and understood. Do not breathe the vapors. In case of inadequate ventilation wear respiratory protection. Wear protective gloves and eye protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Store locked up. Keep away from children. Dispose of contents and container in accordance with applicable local, regional and national regulations.

Signal Word: **DANGER**

Acute: Effects of Overexposure: Can cause skin, respiratory and eye burns. High concentrations of vapor can cause irritation of respiratory tract, nausea, and vomiting.

Chronic: Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic response.

Hazard Statements:

Overexposure may cause burns to skin, respiratory and eyes.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Effects of Overexposure:

Carcinogenicity: In order to comply with California Proposition 65, we feel obligated to advise that some of our products may conceivably contain trace contaminants of some of the listed chemicals. While not necessarily added to our products as ingredients, some listed chemicals may be present in the raw materials from suppliers and over which we have no control. Therefore, even though some of the listed substances may not be present, a significant risk as defined by the regulations in order to comply with California law, we feel obligated to make the following statement:

Warning: Our products may contain trace amounts of some chemicals considered by the State of California to be carcinogens or reproductive toxicants.

3. Composition / Information on Ingredients

Ingredient	% by Weight	Exposure Limit	Cas #
Proprietary Polyamine/Polyamide Blend	< 70	N.E.	UK
Proprietary Diluent	10 - 15	10 PPM ACGIH TWA	98-00-0
Diethylene Triamine	< 5	1 PPM SKIN ACGIH	111-40-0
Proprietary Polymercaptan	< 15	N.E.	N.E.

4. First Aid Measures

Eyes: Open lids wide and flush with large quantities of water for at least 15 minutes. Call a physician, preferably an eye specialist.

Skin: Immediately deluge skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse, discard shoes. Consult a physician if irritation develops.

Ingestion: Do not induce vomiting without medical advice. If conscious give water. Prevent aspiration of vomit (turn victim's head to side). Consult a physician.

Inhalation: Remove the patients from the contaminated area to fresh air. Administer oxygen or artificial respiration as needed. Call a physician if after effects occur.

5. Fire Fighting Measures

Flash Point: 185 oF PMCC

Flammable Limits: UK

Fire Degradation Products:

Extinguishing Media: Foam, dry chemicals, CO2. Where the fire is of major proportions, water spray may also be used. Water or foam may cause frothing if liquid is burning, but it still may be a useful extinguishing agent if carefully applied to the fire.

Protective Equipment: In case of fire, use normal firefighting equipment including a NIOSH approved, self contained breathing apparatus (SCBA). Use water to cool containers.

Explosion Hazards: None.

6. Accidental Release Measures

Small Spill: Absorb with rag. Wear proper personal protective equipment. Place in a chemical waste container for proper disposal.

Large Spill: Absorb with dry chemical absorbent, earth, sand or any other inert material. Wear proper personal protective equipment. Place in a chemical waste container for proper disposal. Flush contaminated areas with water.

Disposal: Any disposal practice must be in compliance with all federal, state and local laws and regulations. Chemical additions, processing, storage, or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance is the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

7. Handling and Storage

Storage: Store in tightly sealed containers. Store in a cool, dry, well ventilated area away from heat and open flame. Protect from moisture.

Handling: Avoid contact with skin, eyes, and clothing. Do not take internally. Use personal protective equipment when transferring material to or from drums, totes or other containers. Safety glasses and gloves are the minimum protection. Additional precautions must be used when splash hazards are present.

Shelf Life:

Other Precautions:

8. Exposure Controls / Personal Protection

Respiratory Protection: Avoid breathing vapors. Use adequate ventilation.

Ventilation: Normal ventilation should be adequate. Local if vapors are vented.

Protection Gloves: Rubber or impervious gloves recommended.

Eye Protection: Chemical splash goggles or safety glasses.

Protective Clothing: Wear impervious clothing and gloves. Materials may include butyl rubber, nitrile rubber, neoprene and Saranex coated Tyvek.

Protective Equipment: Use appropriate equipment to prevent eye or skin contact.

Other Precautions: Avoid breathing vapors, use with good ventilation. Wash hands thoroughly with soap and water after every use.

9. Physical and Chemical Properties

VD: N.D.

Color: Straw

% Volatile by VL: < 3%

Boiling Point: Not Determined (> 200 oF)

Solubility in Water: Slight
Evaporation Rate: N.A.
pH:
Odor:

Flash Point: 185 oF (PMCC)
SP GR: .98 - .99
Physical State:
VP: N.D.

10. Stability and Reactivity

Stability: Stable.

Reactivity:

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, nitrogen oxides.

Incompatibility Materials to Avoid: Strong Strong oxidizing agents, acids.

Conditions to Avoid: Mixing with oxidizers or epoxy resins in quantities over 1#.

Hazardous Polymerization: Will not occur.

11. Toxicological Information

Toxicological Data: Polyamine Resin

Oral LDO: (rat) LD50-<5 CC/KG

Routes of Entry: Inhalation, skin contact.

Effects of Overexposure: Will cause burns to skin and eyes. High concentrations of vapor can cause irritation of respiratory tract, nausea, and vomiting.

Inhalation:

Medical Conditions of Exposure:

Chronic: Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic response.

Carcinogenic Categories:

NTP: Not classified as a carcinogen

IARC: Not classified as a carcinogen

OSHA: Not classified as a carcinogen

12. Ecological Information

Comments: No information.

13. Disposal Considerations

Disposal: Any disposal practice must be in compliance with all federal, state and local laws and regulations. Chemical additions, processing, storage, or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance is the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

Refer to RCRA 4 CFR 216 and/or any other appropriate federal, state or local requirements for proper classification information.

Container Disposal: Drums/containers should be decontaminated and either passed to an approved drum recycler or destroyed.

RCRA/EPA Waste Information: The generation of waste should be avoided or minimized whenever possible. Chemical waste, even small quantities, should never be poured down drains, sewers or waterways.

14. Transport Information

DOT (Domestic Surface): Shipping name; Compound resin. Not regulated (Class 55).

IMO (Ocean): Not restricted.

ICAO (Air): Not restricted.

15. Regulatory Information

TSCA Status: All ingredients are not required to be listed on the TSCA inventory
SARA Title III:

Section 311/312 Hazard Categories: This chemical is classified as a hazardous chemical due to the potential for allergic skin reaction.

Section 313 Toxic Chemicals: o the best of our knowledge this product contains no chemical subject to Sara Title III Section 313.

OSHA: This chemical is classified as a hazardous chemical due to the potential for allergic skin reaction. Standard 29 CFR 1910.1200

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal whether a material containing the product or derived from the product should be classified as a hazardous waste (40 CFR 261.20-24)

CEPA Canadian Environmental Protection Act: All ingredients in this product are listed on the DSL or are not required to be listed.

16. Other Information

All statements, technical information and recommendations contained herein are based upon available scientific test or data which we believe to be reliable since we cannot anticipate all conditions under which this information and our products or the products of other manufacturers in combination with our products may be used. Applied Technologies makes no warranties, express or implied, and assumes no responsibility in connection with any use of this information.

Personal Protection: B

NFPA Ratings:



HMIS Ratings:

