



W V C O

# Material Safety Data Sheet

FASTPATCH LV RESIN GRAY

## 1. Product and company identification

<b>Product name</b>	: FASTPATCH LV RESIN GRAY
<b>Supplier</b>	: Willamette Valley Company 1075 Arrowsmith Eugene, OR 97402 541-484-9621
<b>Material uses</b>	: Not available.
<b>Manufacturer</b>	: Willamette Valley Company 1075 Arrowsmith Eugene, OR 97402 541-484-9621
<b>Code</b>	: 1020276
<b>Validation date</b>	: <b>7/14/2010.</b>
<b>Print date</b>	: 7/14/2010.
<b>Responsible name</b>	: <b>Regulatory Compliance</b>
<b><u>In case of emergency</u></b>	: CALL INFOTRAC 800-535-5053 001-352-323-3500

## 2. Hazards identification

<b>Physical state</b>	: Liquid.
<b>Emergency overview</b>	: WARNING !  CAUSES EYE AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED. MAY CAUSE RESPIRATORY TRACT IRRITATION.  Harmful if swallowed. Irritating to eyes and skin. Slightly irritating to the respiratory system. Do not ingest. Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
<b>Routes of entry</b>	: Dermal contact. Eye contact. Inhalation.
<b><u>Potential acute health effects</u></b>	
<b>Inhalation</b>	: Slightly irritating to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
<b>Ingestion</b>	: Harmful if swallowed.
<b>Skin</b>	: Irritating to skin.
<b>Eyes</b>	: Irritating to eyes.
<b><u>Potential chronic health effects</u></b>	
<b>Chronic effects</b>	: No known significant effects or critical hazards.
<b>Carcinogenicity</b>	: No known significant effects or critical hazards.
<b>Mutagenicity</b>	: No known significant effects or critical hazards.
<b>Teratogenicity</b>	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
<b>Fertility effects</b>	: No known significant effects or critical hazards.
<b>Target organs</b>	: Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin.
<b><u>Over-exposure signs/symptoms</u></b>	
<b>Inhalation</b>	: Adverse symptoms may include the following: respiratory tract irritation coughing
<b>Ingestion</b>	: No specific data.

## 2 . Hazards identification

- Skin** : Adverse symptoms may include the following:  
irritation  
redness
- Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Medical conditions aggravated by over-exposure** : Pre-existing digestive disorders may be aggravated by over-exposure to this product.

See toxicological information (section 11)

## 3 . Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Tetrahydroxypropylethylenediamine	102-60-3	30-60
2,2,4-Trimethyl-1,3-Pentanediol Diisobutryate	6846-50-0	30-60
Titanium Dioxide	13463-67-7	1-5
Solution Of Foam Destroying Polysiloxanes	Mixture	1-5
Carbon Black	1333-86-4	<1

**There are no ingredients or additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## 4 . First aid measures

- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

## 5 . Fire-fighting measures

- Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
  - Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides  
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8 . Exposure controls/personal protection

### Product name

Titanium Dioxide

### Exposure limits

**ACGIH TLV (United States, 1/2009).** Notes: Substance identified by other sources as a suspected or confirmed human carcinogen. 1996 Adoption Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124) :36338-33351, June 30, 1993, for revised OSHA PEL. Refers to Appendix A - Carcinogens.

TWA: 10 mg/m<sup>3</sup> 8 hour(s).

**OSHA PEL (United States, 11/2006).**

TWA: 15 mg/m<sup>3</sup> 8 hour(s). Form: Total dust

**OSHA PEL 1989 (United States, 3/1989).**

TWA: 10 mg/m<sup>3</sup> 8 hour(s). Form: Total dust

Carbon Black

**ACGIH TLV (United States, 1/2009).** Notes: Substance identified by other sources as a suspected or confirmed human carcinogen. 1996 Adoption Refers to Appendix A -- Carcinogens.

TWA: 3.5 mg/m<sup>3</sup> 8 hour(s).

**NIOSH REL (United States, 6/2008).** Notes: See Appendix A - NIOSH Potential Occupational Carcinogen See Appendix C - Supplemental Exposure Limits

TWA: 3.5 mg/m<sup>3</sup> 10 hour(s).

**NIOSH REL (United States, 6/2008).** Notes: Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs) See Appendix A - NIOSH Potential Occupational Carcinogen See Appendix C - Supplemental Exposure Limits

TWA: 0.1 mg of PAHs/cm<sup>3</sup> 10 hour(s).

**OSHA PEL (United States, 11/2006).**

TWA: 3.5 mg/m<sup>3</sup> 8 hour(s).

**OSHA PEL 1989 (United States, 3/1989).**

TWA: 3.5 mg/m<sup>3</sup> 8 hour(s).

### Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

### Engineering measures

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Personal protection

#### Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

#### Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

#### Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## 8 . Exposure controls/personal protection

- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Precautions to be taken in use:** : This product may contain materials classified as nuisance particulates, which may be present at hazardous levels only during sanding or abrading of the dried film. Wear a dust/mist respirator approved for dust when dusts are generated from sanding or abrading the dried film.

## 9 . Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Open cup: >128°C (>262.4°F)
- Color** : Gray.
- Odor** : Slight
- Boiling/condensation point** : >100°C (>212°F)
- Specific gravity** : 1.03
- Vapor pressure** : 0.000088 kPa (0.00066 mm Hg)
- Estimated Vapor Density** : >1 [Air = 1]
- VOC %** : 2.2573%
- Evaporation rate** : 1 (Water = 1)
- Solubility** : Very slightly soluble in the following materials: water.

## 10 . Stability and reactivity

- Stability** : The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur.
- Conditions to avoid** : No specific data.
- Materials to avoid** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Hazardous polymerization** : Will not occur.

## 11 . Toxicological information

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Tetrahydroxypropylethylenediamine	LD Intravenous	Rat	>500 mg/kg	-
	LD Oral	Rat	>500 mg/kg	-
Titanium Dioxide	LD Intratracheal	Rat	>100 ug/kg	-
	TDLo	Rat	5 mg/kg	-
	Intratracheal			
	TDLo	Rat	1.6 mg/kg	-
Carbon Black	Intratracheal			
	TDLo	Rat	1.25 mg/kg	-
	TDLo Oral	Rat	60 gm/kg	-
	LD50 Dermal	Rabbit	>3 g/kg	-
	LD50 Oral	Rat	>15400 mg/kg	-
	TDLo	Rat	15 mg/kg	-
	Intratracheal			
	TDLo	Rat	10 mg/kg	-
	Intratracheal			
	TDLo	Rat	16 mg/kg	-
Intratracheal				

### Carcinogenicity

#### Conclusion/Summary

## 11 . Toxicological information

The International Agency for Research on Cancer (IARC) Monograph No. 93 reports there is sufficient evidence in experimental animals exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans. Human studies do not suggest an association between occupational exposure to titanium dioxide dust and an increased risk of cancer. The IARC summary concludes, "that no significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint".

### Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Titanium Dioxide	-	2B	-	-	-	-
Carbon Black	-	2B	-	+	-	-

**IDLH** : Not available.

**Synergistic products** : Not available.

## 12 . Ecological information

**Environmental effects** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
Titanium Dioxide	-	Acute EC50 >1000000 ug/L Fresh water	Daphnia - Daphnia magna	48 hours
	-	Acute LC50 5.5 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	-	Acute LC50 >1000000 ug/L Marine water	Fish - Fundulus heteroclitus	96 hours
	-	Chronic NOEC 500 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	-	Chronic NOEC 1 ppm Fresh water	Daphnia - Daphnia magna	48 hours

**Conclusion/Summary** : Not available.

### Biodegradability

**Conclusion/Summary** : Not available.

## 13 . Disposal considerations

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14 . Transport information

## 14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>DOT Classification</b>	Not regulated.	-	-	-		-
<b>TDG Classification</b>	Not regulated.	-	-	-		-
<b>IMDG Class</b>	Not regulated.	-	-	-		-
<b>IATA-DGR Class</b>	Not regulated.	-	-	-		-

PG\* : Packing group

## 15 . Regulatory information

**United States inventory (TSCA 8b):** All components are listed or exempted.  
SARA 311/312 - Acute, Chronic

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer.

#### Ingredient name

Carbon Black

#### Cancer

Yes.

#### Reproductive

No.

### Canada

#### **WHMIS (Canada)**

: Class D-2A: Material causing other toxic effects (Very toxic).

#### **Canadian lists**

: **CEPA Toxic substances:** None of the components are listed.

**Canadian NPRI:** None of the components are listed.

#### **Canada inventory**

: **Canada inventory:** Not determined.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

### Mexico

#### **Classification**

:



### EU regulations

#### **Risk phrases**

: This product is not classified according to EU legislation.

### International regulations

#### **International lists**

: **Australia inventory (AICS):** Not determined.  
**China inventory (IECSC):** Not determined.  
**Korea inventory (KECI):** Not determined.  
**Philippines inventory (PICCS):** Not determined.  
**Japan inventory (ENCS):** Not determined.

**Europe inventory:** All components are listed or exempted.

## 16 . Other information

**Hazardous Material Information System (U.S.A.)** :

Health	*	2
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (U.S.A.)** :



**Date of printing** : 7/14/2010.  
**Date of issue** : 7/14/2010.  
**Date of previous issue** : 12/31/2009.  
**Version** : 1.02

☑ Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.