

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08
Version: 3.0

Page: 1/12
(51707000/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

MasterSeal CR 125 also SONOMERIC 1

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: No applicable information available.

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Flam. Liq.	3	Flammable liquids
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Resp. Sens.	1	Respiratory sensitization
Skin Sens.	1	Skin sensitization
Muta.	1B	Germ cell mutagenicity
Carc.	1B	Carcinogenicity
STOT RE	1	Specific target organ toxicity — repeated exposure

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08
Version: 3.0

Page: 2/12
(51707000/SDS_GEN_US/EN)

Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H350	May cause cancer.
H340	May cause genetic defects.
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/gas/mist/vapours.
P202	Do not handle until all safety precautions have been read and understood.
P273	Avoid release to the environment.
P243	Take precautionary measures against static discharge.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P270	Do not eat, drink or smoke when using this product.
P264	Wash with plenty of water and soap thoroughly after handling.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use... to extinguish.

Precautionary Statements (Storage):

P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08
Version: 3.0

Page: 3/12
(51707000/SDS_GEN_US/EN)

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
14807-96-6	>= 7.0 - < 10.0%	talc
8052-41-3	>= 5.0 - < 10.0%	Stoddard solvent
1305-78-8	>= 5.0 - < 7.0%	calcium oxide
64742-52-5	>= 3.0 - < 7.0%	Distillates (petroleum), hydrotreated heavy naphthenic
64742-95-6	>= 3.0 - < 5.0%	solvent naphtha
95-63-6	>= 1.0 - < 3.0%	1,2,4-trimethylbenzene
64742-53-6	>= 0.0 - < 3.0%	Distillates (petroleum), hydrotreated light naphthenic
25340-17-4	>= 0.1 - < 0.2%	Benzene, diethyl-

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin:

Wash thoroughly with soap and water. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting due to aspiration hazard. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08
Version: 3.0

Page: 4/12
(51707000/SDS_GEN_US/EN)

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
dry powder, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Containers may rocket or explode in heat of fire. Keep containers cool by spraying with water if exposed to fire. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid prolonged inhalation. Avoid contact with the skin, eyes and clothing. Avoid all sources of ignition: heat, sparks, open flame.

Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers). Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For large amounts: Pump off product.
For residues: Pick up with inert absorbent material (e.g. sand, earth etc.). Correctly dispose of recovered product immediately.

7. Handling and Storage

Precautions for safe handling

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking. Provide good room ventilation even at ground level (vapours are heavier than air).

Protection against fire and explosion:

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08

Version: 3.0

Page: 5/12

(51707000/SDS_GEN_US/EN)

Sources of ignition should be kept well clear. Take precautionary measures against static discharges. Substance/product can form explosive mixture with air. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Suitable materials for containers: tinned carbon steel (Tinplate), Stove-lacquer Polyamerica 100-C102

Further information on storage conditions: Keep container tightly closed and in a well-ventilated place. Keep away from heat. Avoid all sources of ignition: heat, sparks, open flame.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

1,2,4-trimethylbenzene	OSHA PEL ACGIH TLV	TWA value 25 ppm 125 mg/m ³ ; TWA value 25 ppm ;
toluene-2,4-diisocyanate	OSHA PEL ACGIH TLV	CLV 0.02 ppm 0.14 mg/m ³ ; TWA value 0.005 ppm 0.04 mg/m ³ ; STEL value 0.02 ppm 0.15 mg/m ³ ; TWA value 0.005 ppm ; STEL value 0.02 ppm ;
calcium oxide	OSHA PEL ACGIH TLV	PEL 5 mg/m ³ ; TWA value 5 mg/m ³ ; TWA value 2 mg/m ³ ;
Stoddard solvent	OSHA PEL ACGIH TLV	PEL 500 ppm 2,900 mg/m ³ ; TWA value 100 ppm ;
Asphalt	ACGIH TLV	TWA value 0.5 mg/m ³ Inhalable fraction (benzene solubles);

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08
Version: 3.0

Page: 6/12
(51707000/SDS_GEN_US/EN)

talc	OSHA PEL	<p>TWA value 20 millions of particles per cubic foot of air ; TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$, using a value of 100% SiO₂. Lower percentages of SiO₂ will yield higher exposure limits. TWA value 0.1 mg/m³ Respirable ; The exposure limit is calculated from the equation, $10/(\%SiO_2+2)$, using a value of 100% SiO₂. Lower percentages of SiO₂ will yield higher exposure limits. TWA value 0.3 mg/m³ Total dust ; The exposure limit is calculated from the equation, $30/(\%SiO_2+2)$, using a value of 100% SiO₂. Lower percentages of SiO₂ will yield higher exposure limits. TWA value 2 mg/m³ Respirable dust ; TWA value 0.3 mg/m³ Total dust ; The exposure limit is calculated from the equation, $30/(\%SiO_2+2)$, using a value of 100% SiO₂. Lower percentages of SiO₂ will yield higher exposure limits. TWA value 0.1 mg/m³ Respirable ; The exposure limit is calculated from the equation, $10/(\%SiO_2+2)$, using a value of 100% SiO₂. Lower percentages of SiO₂ will yield higher exposure limits. TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$, using a value of 100% SiO₂. Lower percentages of SiO₂ will yield higher exposure limits.</p>
	ACGIH TLV	<p>TWA value 20 millions of particles per cubic foot of air ; TWA value 2 mg/m³ Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.</p>
Stoddard solvent	OSHA PEL ACGIH TLV	<p>PEL 500 ppm 2,900 mg/m³ ; TWA value 100 ppm ;</p>
Distillates (petroleum), hydrotreated heavy naphthenic	OSHA PEL	<p>PEL 5 mg/m³ Mist ; PEL 500 ppm 2,000 mg/m³ ; TWA value 5 mg/m³ Mist ;</p>
Distillates (petroleum), hydrotreated light naphthenic	OSHA PEL ACGIH TLV	<p>PEL 5 mg/m³ Mist ; PEL 500 ppm 2,000 mg/m³ ; TWA value 5 mg/m³ Mist ; ; Exposure by all routes should be carefully controlled to levels as low as possible. ; Included in the regulation, but with no data values - See the regulation for further details</p>

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08
Version: 3.0

Page: 7/12
(51707000/SDS_GEN_US/EN)

Advice on system design:

No applicable information available.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection:

Wear chemical resistant protective gloves.

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure., Antistatic apron

General safety and hygiene measures:

Avoid inhalation of dusts/mists/vapours. Avoid contact with the skin, eyes and clothing. Avoid prolonged and/or repeated contact with the skin. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid
Odour:	solvent-like
Odour threshold:	No applicable information available.
Colour:	black
pH value:	not applicable
Melting temperature:	The product has not been tested.
Boiling point:	307 °F
boiling temperature:	153 - 350 °C
Sublimation point:	No applicable information available.
Flash point:	134 °F (ASTM D56)
Flammability:	Flammable.
Lower explosion limit:	approx. 0.9 %(V)
Upper explosion limit:	7 %(V)
Vapour pressure:	The product has not been tested.
Density:	approx. 9 lb/USg (72 °F) approx. 1.08 g/cm3 (approx. 20 °C)
Relative density:	No applicable information available.
Vapour density:	not determined
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.
Thermal decomposition:	Vapours may form explosive mixture with air. No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	approx. 200 mm2/s (20 °C)
Solubility in water:	(20 °C) slightly soluble

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08
Version: 3.0

Page: 8/12
(51707000/SDS_GEN_US/EN)

Miscibility with water:	(20 °C) not soluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	not determined

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

strong oxidizing agents

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

Vapours may form explosive mixture with air. No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Based on available Data, the classification criteria are not met.

Oral

No applicable information available.

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08
Version: 3.0

Page: 9/12
(51707000/SDS_GEN_US/EN)

No applicable information available.

Irritation / corrosion

Assessment of irritating effects: May cause skin irritation. May cause severe damage to the eyes.

Sensitization

Assessment of sensitization: Sensitization after skin contact possible. The substance may cause sensitization of the respiratory tract.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No reliable data was available concerning repeated dose toxicity. Based on available Data, the classification criteria are not met.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

May cause long-term adverse effects in the aquatic environment. Acutely harmful for aquatic organisms.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Inherently biodegradable. The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

The polymer component of the product is poorly biodegradable.

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08
Version: 3.0

Page: 10/12
(51707000/SDS_GEN_US/EN)

Bioaccumulative potential

Assessment bioaccumulation potential

Discharge into the environment must be avoided.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport

USDOT

Hazard class:	C
Packing group:	III
ID number:	NA 1993
Hazard label:	CBL
Proper shipping name:	COMBUSTIBLE LIQUID, N.O.S. (contains SOLVENT NAPHTHA, STODDARD SOLVENT) Classified as combustible liquid in containers greater than 119 gallons.

Sea transport

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1993
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	FLAMMABLE LIQUID, N.O.S. (contains SOLVENT NAPHTHA, STODDARD SOLVENT)

Air transport

IATA/ICAO

Hazard class:	3
Packing group:	III

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08
Version: 3.0

Page: 11/12
(51707000/SDS_GEN_US/EN)

ID number: UN 1993
Hazard label: 3
Proper shipping name: FLAMMABLE LIQUID, N.O.S. (contains SOLVENT NAPHTHA, STODDARD SOLVENT)

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

TSCA § 5 proposed Significant New Use Restriction (SNUR)
This product contains a substance subject to a pending SNUR.
40 CFR 721.10789

EPCRA 311/312 (Hazard categories): Acute; Chronic; Fire

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
5000 LBS	7664-38-2; 98-82-8	phosphoric acid; cumene
1000 LBS	100-41-4; 108-88-3	ethylbenzene; Toluene
100 LBS	1330-20-7; 78-84-2; 584-84-9; 91-08-7	Xylene; isobutyraldehyde; toluene-2,4-diisocyanate; toluene-2,6-diisocyanate

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>	
PA	8052-41-3	Stoddard solvent	
	1333-86-4	carbon black	
	584-84-9	toluene-2,4-diisocyanate	
	14807-96-6	talc	
	1305-78-8	calcium oxide	
	95-63-6	1,2,4-trimethylbenzene	
	64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	
	64742-53-6	Distillates (petroleum), hydrotreated light naphthenic	
	MA	8052-41-3	Stoddard solvent
		1333-86-4	carbon black
584-84-9		toluene-2,4-diisocyanate	
14807-96-6		talc	
1305-78-8		calcium oxide	
95-63-6		1,2,4-trimethylbenzene	
64742-52-5		Distillates (petroleum), hydrotreated heavy naphthenic	
64742-53-6		Distillates (petroleum), hydrotreated light naphthenic	
NJ		8052-41-3	Stoddard solvent
		1333-86-4	carbon black
	14807-96-6	talc	
	1305-78-8	calcium oxide	
	95-63-6	1,2,4-trimethylbenzene	
	64742-93-4	Asphalt, oxidized	
	584-84-9	toluene-2,4-diisocyanate	
	64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	
	64742-53-6	Distillates (petroleum), hydrotreated light naphthenic	

Safety Data Sheet

MasterSeal CR 125 also SONOMERIC 1

Revision date : 2015/07/08
Version: 3.0

Page: 12/12
(51707000/SDS_GEN_US/EN)

CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NFPA Hazard codes:

Health : 3 Fire: 2 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2015/07/08

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET