

# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 1/12  
(53065337/SDS\_GEN\_US/EN)

### 1. Identification

**Product identifier used on the label**

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

**Recommended use of the chemical and restriction on use**

Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

**Details of the supplier of the safety data sheet**

Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

**Emergency telephone number**

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

**Other means of identification**

Chemical family: Coating

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

**Classification of the product**

Acute Tox.	2 (Inhalation - mist)	Acute toxicity
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Resp. Sens.	1	Respiratory sensitization
Skin Sens.	1	Skin sensitization
Aquatic Acute	3	Hazardous to the aquatic environment - acute

# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 2/12  
(53065337/SDS\_GEN\_US/EN)

Aquatic Chronic

3

Hazardous to the aquatic environment - chronic

### Label elements

Pictogram:



Signal Word:

Danger

Hazard Statement:

H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H330 Fatal if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H402 Harmful to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves and eye/face protection.  
P260 Do not breathe mist or vapour.  
P273 Avoid release to the environment.  
P284 In case of inadequate ventilation wear respiratory protection.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P264 Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P310 Immediately call a POISON CENTER or doctor/physician.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Labeling of special preparations (GHS):

# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 3/12  
(53065337/SDS\_GEN\_US/EN)

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 89 % Inhalation - mist

### According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

#### Emergency overview

##### DANGER:

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

Avoid contact with the skin, eyes and clothing.

### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
4098-71-9	>= 10.0 - < 15.0%	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
1333-86-4	>= 0.3 - < 1.0%	carbon black

#### According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
4098-71-9	>= 7.0 - <= 13.0%	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
1333-86-4	>= 0.5 - <= 1.5%	carbon black

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

##### If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

##### If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

##### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 4/12  
(53065337/SDS\_GEN\_US/EN)

### **If swallowed:**

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

### **Most important symptoms and effects, both acute and delayed**

Symptoms: allergic symptoms, coughing, sickness

Hazards: Respiratory sensitization may result in allergic (asthma-like) signs in the lower respiratory tract including wheezing, shortness of breath and difficulty breathing, the onset of which may be delayed. Repeated inhalation of high concentrations may cause lung damage, including reduced lung function, which may be permanent. Substances eliciting lower respiratory tract irritation may worsen the asthma-like reactions that may be produced by product exposures.

### **Indication of any immediate medical attention and special treatment needed**

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

### **Extinguishing media**

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

### **Special hazards arising from the substance or mixture**

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, nitrogen oxides, fumes/smoke, carbon black, isocyanate, vapour

### **Advice for fire-fighters**

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### **Further information:**

Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## 6. Accidental release measures

### **Personal precautions, protective equipment and emergency procedures**

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

### **Environmental precautions**

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 5/12  
(53065337/SDS\_GEN\_US/EN)

### Methods and material for containment and cleaning up

For small amounts: Absorb isocyanate with suitable absorbent material (see § 40 CFR, sections 260, 264 and 265 for further information). Shovel into open container. Do not make container pressure tight. Move container to a well-ventilated area (outside). Spill area can be decontaminated with the following recommended decontamination solution: Mixture of 90 % water, 8 % concentrated ammonia, 2 % detergent. Add at a 10 to 1 ratio.

For large amounts: If temporary control of isocyanate vapor is required, a blanket of protein foam or other suitable foam (available from most fire departments) may be placed over the spill. Transfer as much liquid as possible via pump or vacuum device into closed but not sealed containers for disposal.

For residues: The following measures should be taken for final cleanup: Wash down spill area with decontamination solution. Allow solution to stand for at least 10 minutes.

Dike spillage.

---

## 7. Handling and Storage

### Precautions for safe handling

Provide suitable exhaust ventilation at the processing machines. Ensure thorough ventilation of stores and work areas. Avoid aerosol formation. When handling heated product, vapours of the product should be ventilated, and respiratory protection used. Wear respiratory protection when spraying. Danger of bursting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

### Conditions for safe storage, including any incompatibilities

No applicable information available.

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

---

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	OSHA PEL	STEL value 0.02 ppm ; TWA value 0.005 ppm ; SKIN_FINAL ; The substance can be absorbed through the skin.
	ACGIH TLV	TWA value 0.005 ppm ;

### Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

### Personal protective equipment

#### Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place. For emergency or non-routine, high exposure situations, including confined space entry,

# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 6/12  
(53065337/SDS\_GEN\_US/EN)

use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

### Hand protection:

Chemical resistant protective gloves should be worn to prevent all skin contact., Suitable materials may include, chloroprene rubber (Neoprene), nitrile rubber (Buna N), chlorinated polyethylene, polyvinylchloride (Pylox), fluoroelastomer (Viton), butyl rubber, depending upon conditions of use.

### Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

### Body protection:

Cover as much of the exposed skin as possible to prevent all skin contact., Suitable materials may include, saran-coated material, depending upon conditions of use.

### General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. Wear protective clothing as necessary to prevent contact. Eye wash fountains and safety showers must be easily accessible. Observe the appropriate PEL or TLV value. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

## 9. Physical and Chemical Properties

Form:	liquid
Odour:	mild
Odour threshold:	No applicable information available.
Colour:	amber
pH value:	not applicable
Melting point:	No applicable information available.
Boiling point:	105 - 157.78 °C
Sublimation point:	No applicable information available.
Flash point:	321 °F
Flammability:	not determined
Lower explosion limit:	No data available.
Upper explosion limit:	No data available.
Vapour pressure:	No applicable information available.
Density:	8.7 lb/USg ( 25 °C)
Relative density:	No applicable information available.
Vapour density:	Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):	No data available.
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	No applicable information available.
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 7/12  
(53065337/SDS\_GEN\_US/EN)

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

#### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

#### Conditions to avoid

See MSDS section 7 - Handling and storage.

#### Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

#### Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

---

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: Inhalation of vapours may cause irritation of the mucous membranes of the nose, throat or trachea, breathlessness, chest discomfort, difficult breathing and reduced pulmonary function. Inhalation exposure well above the PEL may result additionally in eye irritation, headache, chemical bronchitis, asthma-like findings or pulmonary edema. Isocyanates have also been reported to cause hypersensitivity pneumonitis, which is characterized by flu-like symptoms, the onset of which may be delayed.

##### Oral

No applicable information available.

*Information on: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate*

*Type of value: LD50*

*Species: rat (male/female)*

*Value: 4,814 mg/kg (OECD Guideline 401)*

-----

# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 8/12  
(53065337/SDS\_GEN\_US/EN)

### Inhalation

Type of value: ATE  
Value: 0.28 mg/l  
Determined for mist

*Information on: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate*

*Type of value: LC50*

*Species: rat (male/female)*

*Value: 0.031 mg/l (OECD Guideline 403)*

*Exposure time: 4 h*

*An aerosol with respirable particles was tested.*

*The European Union (EU) has classified this substance as 'toxic'.*

### Dermal

No applicable information available.

*Information on: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate*

*Type of value: LD50*

*Species: rat (male/female)*

*Value: > 7,000 mg/kg (OECD Guideline 402)*

### Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

### Irritation / corrosion

Assessment of irritating effects: Irritating to eyes, respiratory system and skin. Skin contact may result in dermatitis, either irritative or allergic.

### Skin

*Information on: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate*

*Species: rabbit*

*Result: Severely irritating.*

*Method: OECD Guideline 404*

### Eye

*Information on: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate*

*Species: rabbit*

*Result: Irritant.*

*Method: OECD Guideline 405*

### Sensitization

Assessment of sensitization: The substance may cause sensitization of the respiratory tract.

Sensitization after skin contact possible. As a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the PEL/TLV. These symptoms, which include chest tightness, wheezing, cough, shortness of breath, or asthmatic attack, could be immediate or delayed up to several hours after exposure. Similar to many non-specific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air, or other irritants. This increased lung sensitivity can



# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 9/12  
(53065337/SDS\_GEN\_US/EN)

persist for weeks and in severe cases for several years. Chronic overexposure to isocyanates has also been reported to cause lung damage, including a decrease in lung function, which may be permanent. Prolonged contact can cause reddening, swelling, rash, scaling, or blistering. In those who have developed a skin sensitization, these symptoms can develop as a result of contact with very small amounts of liquid material, or even as a result of vapour-only exposure. Animal tests indicate that skin contact may play a role in causing respiratory sensitization.

### Aspiration Hazard

Study scientifically not justified.

### **Chronic Toxicity/Effects**

#### Repeated dose toxicity

Assessment of repeated dose toxicity: The substance may cause damage to the olfactory epithelium after repeated inhalation. The substance may cause damage to the lung after repeated inhalation. These effects are not relevant to humans at occupational levels of exposure.

*Information on: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate*

*Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation.*

#### Carcinogenicity

Assessment of carcinogenicity: Contains a suspect carcinogen.

*Information on: carbon black*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was observed. A clear indication of an increased risk of cancer in humans has so far not been shown. No carcinogenic potential can be deduced from other studies with rats and mice.*

#### Teratogenicity

*Information on: 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate*

*Assessment of teratogenicity: Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals.*

#### Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

### **Symptoms of Exposure**

allergic symptoms, coughing, sickness

---

## 12. Ecological Information

### **Toxicity**

# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 10/12  
(53065337/SDS\_GEN\_US/EN)

Aquatic toxicity  
Assessment of aquatic toxicity:  
Acutely harmful for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

### Persistence and degradability

Assessment of stability in water  
In contact with water the substance will hydrolyse rapidly.

### Mobility in soil

Assessment transport between environmental compartments  
Study scientifically not justified.

### Additional information

Other ecotoxicological advice:  
Acutely harmful for aquatic organisms. Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

## 13. Disposal considerations

### Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

### Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

---

## 14. Transport Information

### Land transport

USDOT

Not classified as a dangerous good under transport regulations

### Sea transport

IMDG

Not classified as a dangerous good under transport regulations

### Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

---

## 15. Regulatory Information

### Federal Regulations

# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 11/12  
(53065337/SDS\_GEN\_US/EN)

### Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Acute; Chronic

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
5000 LBS	7664-38-2	phosphoric acid
1000 LBS	108-88-3	Toluene
100 LBS	108-90-7	chlorobenzene

### State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
PA	4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl
	1333-86-4	isocyanate carbon black
MA	4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl
	1333-86-4	isocyanate carbon black
NJ	4098-71-9	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl
	1333-86-4	isocyanate carbon black

### CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

### NFPA Hazard codes:

Health : 3 Fire: 1 Reactivity: 0 Special:

### HMIS III rating

Health: 3<sup>+</sup> Flammability: 1 Physical hazard: 1

---

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations  
SDS Prepared on: 2016/02/24

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT

# Safety Data Sheet

## MasterSeal M 265 PART B also CONIPUR 265Z BASE COAT PTB

Revision date : 2016/02/24  
Version: 4.0

Page: 12/12  
(53065337/SDS\_GEN\_US/EN)

PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET