

Safety Data Sheet

MasterSeal NP 2 Ist also SONOLASTIC NP2 LIMESTONE

Revision date : 2015/04/29

Page: 1/9

Version: 1.1

(51377022/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

MasterSeal NP 2 Ist also SONOLASTIC NP2 LIMESTONE

Recommended use of the chemical and restriction on use

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: No applicable information available.

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
STOT RE	1	Specific target organ toxicity — repeated exposure
Aquatic Acute	1	Hazardous to the aquatic environment - acute
Aquatic Chronic	1	Hazardous to the aquatic environment - chronic

Label elements

Safety Data Sheet

MasterSeal NP 2 Ist also SONOLASTIC NP2 LIMESTONE

Revision date : 2015/04/29

Page: 2/9

Version: 1.1

(51377022/SDS_GEN_US/EN)

Pictogram:



Signal Word:

Danger

Hazard Statement:

H319

Causes serious eye irritation.

H372

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

H400

Very toxic to aquatic life.

H410

Very toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P273

Avoid release to the environment.

P280

Wear eye/face protection.

P260

Do not breathe dust/gas/mist/vapours.

P270

Do not eat, drink or smoke when using this product.

P264

Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P311

If eye irritation persists: Call a POISON CENTER or doctor/physician.

P391

Collect spillage.

Precautionary Statements (Disposal):

P501

Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

No applicable information available.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
471-34-1	>= 7.0 - < 20.0 %	Calcium carbonate
8052-41-3	>= 7.0 - < 10.0 %	Stoddard solvent
110-30-5	>= 3.0 - < 5.0 %	N,N'-ethylenedi(stearamide)
13463-67-7	>= 3.0 - < 5.0 %	Titanium dioxide
1305-78-8	>= 0.3 - < 1.0 %	calcium oxide
2530-83-8	>= 0.3 - < 1.0 %	trimethoxy(3-(oxiranylmethoxy)propyl)silane

4. First-Aid Measures

Description of first aid measures

Safety Data Sheet

MasterSeal NP 2 Ist also SONOLASTIC NP2 LIMESTONE

Revision date : 2015/04/29

Page: 3/9

Version: 1.1

(51377022/SDS_GEN_US/EN)

General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Wash affected areas thoroughly with soap and water. Consult a doctor if skin irritation persists.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Immediate medical attention required.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, foam, carbon dioxide

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Sealed containers should be protected against heat as this results in pressure build-up.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Safety Data Sheet

MasterSeal NP 2 Ist also SONOLASTIC NP2 LIMESTONE

Revision date : 2015/04/29

Page: 4/9

Version: 1.1

(51377022/SDS_GEN_US/EN)

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.
For large amounts: Contain spillage. Pick up with suitable absorbent material. Sweep/shovel up.
Dispose of absorbed material in accordance with regulations.
Ensure adequate ventilation. Avoid sources of ignition.

7. Handling and Storage

Precautions for safe handling

Avoid contact with the skin, eyes and clothing. Avoid excessive temperatures. Avoid humidity.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Calcium carbonate	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;
calcium oxide	OSHA PEL ACGIH TLV	PEL 5 mg/m3 ; TWA value 5 mg/m3 ; TWA value 2 mg/m3 ;
Limestone	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;
Titanium dioxide	OSHA PEL ACGIH TLV	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ; TWA value 10 mg/m3 ;
Stoddard solvent	OSHA PEL ACGIH TLV	PEL 500 ppm 2,900 mg/m3 ; TWA value 100 ppm ;

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Safety Data Sheet

MasterSeal NP 2 Ist also SONOLASTIC NP2 LIMESTONE

Revision date : 2015/04/29

Page: 5/9

Version: 1.1

(51377022/SDS_GEN_US/EN)

Personal protective equipment

Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection:

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields. Wear face shield if splashing hazard exists.

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid	
Odour:	acrylic-like	
Odour threshold:		No applicable information available.
Colour:	milky white	
pH value:		The product has not been tested.
Melting point:		No applicable information available.
Boiling point:	242.78 °C	The product has not been tested.
Sublimation point:		No applicable information available.
Flash point:	115.56 °C	
Flammability:	not determined	
Lower explosion limit:	0.7 %(V)	
Upper explosion limit:	9.4 %(V)	
Autoignition:		No data available.
Vapour pressure:		No applicable information available.
Density:	1.0312 g/cm3	(20 °C)
Relative density:		No applicable information available.
Vapour density:		Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):		No data available.
Thermal decomposition:	No applicable information available.	
Viscosity, dynamic:		No applicable information available.
Viscosity, kinematic:		No applicable information available.
Solubility (quantitative):		No applicable information available.
Solubility (qualitative):	No applicable information available.	
Evaporation rate:		No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

10. Stability and Reactivity

Reactivity

Safety Data Sheet

MasterSeal NP 2 Ist also SONOLASTIC NP2 LIMESTONE

Revision date : 2015/04/29

Page: 6/9

Version: 1.1

(51377022/SDS_GEN_US/EN)

No applicable information available.

Chemical stability

No applicable information available.

Possibility of hazardous reactions

The product is chemically stable.

Conditions to avoid

Avoid moisture. Avoid prolonged exposure to extreme heat. Avoid sources of ignition.

Incompatible materials

water, alcohols, strong bases, oxidizing agents, Substances/products that react with isocyanates.

Hazardous decomposition products

Decomposition products:
carbon oxides, nitrogen oxides

Thermal decomposition:
No applicable information available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Based on available Data, the classification criteria are not met.

Oral

No applicable information available.

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

No applicable information available.

Irritation / corrosion

Assessment of irritating effects: No irritation is expected under intended use and appropriate handling. Based on available Data, the classification criteria are not met.

Sensitization

Assessment of sensitization: Based on available Data, the classification criteria are not met.

Chronic Toxicity/Effects

Safety Data Sheet

MasterSeal NP 2 Ist also SONOLASTIC NP2 LIMESTONE

Revision date : 2015/04/29

Page: 7/9

Version: 1.1

(51377022/SDS_GEN_US/EN)

Repeated dose toxicity

Assessment of repeated dose toxicity: No reliable data was available concerning repeated dose toxicity. Based on available Data, the classification criteria are not met.

Genetic toxicity

Assessment of mutagenicity: No applicable information available.

Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Reproductive toxicity

Assessment of reproduction toxicity: No applicable information available.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely toxic for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Inherently biodegradable. The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

The polymer component of the product is poorly biodegradable.

Safety Data Sheet

MasterSeal NP 2 Ist also SONOLASTIC NP2 LIMESTONE

Revision date : 2015/04/29

Page: 8/9

Version: 1.1

(51377022/SDS_GEN_US/EN)

Bioaccumulative potential

Assessment bioaccumulation potential

Discharge into the environment must be avoided.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories):

Acute; Chronic

Safety Data Sheet

MasterSeal NP 2 Ist also SONOLASTIC NP2 LIMESTONE

Revision date : 2015/04/29

Page: 9/9

Version: 1.1

(51377022/SDS_GEN_US/EN)

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
5000 LBS	7664-38-2	phosphoric acid
1000 LBS	108-88-3	Toluene
100 LBS	75-35-4; 107-13-1; 75-28-5	1,1-dichloroethylene; acrylonitrile; Propane, 2-methyl-

State regulations

CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NFPA Hazard codes:

Health : 2 Fire: 1 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2015/04/29

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET