

Safety Data Sheet

MasterSeal P 173 also PRIMER 733

Revision date : 2015/04/17
Version: 3.0

Page: 1/11
(50380469/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

MasterSeal P 173 also PRIMER 733

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: No data available.

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Asp. Tox.	1	Aspiration hazard
Flam. Liq.	2	Flammable liquids
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Skin Sens.	1	Skin sensitization
Carc.	2	Carcinogenicity
Repr.	2 (unborn child)	Reproductive toxicity
STOT SE	3 (Vapours may cause drowsiness and	Specific target organ toxicity — single exposure

Safety Data Sheet

MasterSeal P 173 also PRIMER 733

Revision date : 2015/04/17
Version: 3.0

Page: 2/11
(50380469/SDS_GEN_US/EN)

STOT RE	dizziness.) 2	Specific target organ toxicity — repeated exposure
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361	Suspected of damaging the unborn child.
H373	May cause damage to organs (Auditory organ, Central nervous system, Liver, Kidney) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/gas/mist/vapours.
P201	Obtain special instructions before use.
P271	Use only outdoors or in a well-ventilated area.
P243	Take precautionary measures against static discharge.
P273	Avoid release to the environment.
P202	Do not handle until all safety precautions have been read and understood.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

Safety Data Sheet

MasterSeal P 173 also PRIMER 733

Revision date : 2015/04/17
Version: 3.0

Page: 3/11
(50380469/SDS_GEN_US/EN)

P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P314	Get medical advice/attention if you feel unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash before reuse.
P337 + P311	If eye irritation persists: Call a POISON CENTER or doctor/physician.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use alcohol-resistant foam, carbon dioxide, dry powder or water spray for extinction.

Precautionary Statements (Storage):

P233	Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
108-88-3	>= 25.0 - < 50.0 %	Toluene
22527-63-5	>= 10.0 - < 15.0 %	Propanoic acid, 2-methyl-, 3-(benzoyloxy)-2,2,4-trimethylpentyl ester
1305-78-8	>= 1.0 - < 3.0 %	calcium oxide
1330-20-7	>= 1.0 - < 3.0 %	Xylene
100-41-4	>= 0.3 - < 1.0 %	ethylbenzene

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If breathing difficulties develop, aid in breathing and seek immediate medical attention.

Safety Data Sheet

MasterSeal P 173 also PRIMER 733

Revision date : 2015/04/17
Version: 3.0

Page: 4/11
(50380469/SDS_GEN_US/EN)

If on skin:

Wash thoroughly with soap and water. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting due to aspiration hazard. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed

Symptoms: Overexposure may cause: , unconsciousness, death, dilation of pupils, incoordination, lethargy, confusion, headache, dizziness, lacrimation
Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
dry powder, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Containers may rocket or explode in heat of fire. Keep containers cool by spraying with water if exposed to fire. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Safety Data Sheet

MasterSeal P 173 also PRIMER 733

Revision date : 2015/04/17

Page: 5/11

Version: 3.0

(50380469/SDS_GEN_US/EN)

Use personal protective clothing. Avoid prolonged inhalation. Avoid contact with the skin, eyes and clothing. Avoid all sources of ignition: heat, sparks, open flame.

Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers). Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with inert absorbent material (e.g. sand, earth etc.). Correctly dispose of recovered product immediately.

7. Handling and Storage

Precautions for safe handling

Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking. Provide good room ventilation even at ground level (vapours are heavier than air).

Protection against fire and explosion:

Sources of ignition should be kept well clear. Take precautionary measures against static discharges. Substance/product can form explosive mixture with air. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds.

Suitable materials for containers: tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container tightly closed and in a well-ventilated place. Keep away from heat. Avoid all sources of ignition: heat, sparks, open flame.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

ethylbenzene	OSHA PEL	PEL 100 ppm 435 mg/m ³ ; STEL value 125 ppm 545 mg/m ³ ; TWA value 100 ppm 435 mg/m ³ ;
	ACGIH TLV	TWA value 20 ppm ;
Toluene	OSHA PEL	max. conc. 500 ppm ; CLV 300 ppm ; TWA value 200 ppm ; STEL value 150 ppm 560 mg/m ³ ; TWA value 100 ppm 375 mg/m ³ ;
	ACGIH TLV	TWA value 20 ppm ;
calcium oxide	OSHA PEL	PEL 5 mg/m ³ ; TWA value 5 mg/m ³ ;
	ACGIH TLV	TWA value 2 mg/m ³ ;
Xylene	OSHA PEL	PEL 100 ppm 435 mg/m ³ ; STEL value 150 ppm 655 mg/m ³ ; TWA value 100 ppm 435 mg/m ³ ;
	ACGIH TLV	TWA value 100 ppm ; STEL value 150 ppm ;

Advice on system design:

No applicable information available.

Safety Data Sheet

MasterSeal P 173 also PRIMER 733

Revision date : 2015/04/17
Version: 3.0

Page: 6/11
(50380469/SDS_GEN_US/EN)

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection:

Wear chemical resistant protective gloves.

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure., Antistatic apron

General safety and hygiene measures:

Avoid inhalation of dusts/mists/vapours. Avoid contact with the skin, eyes and clothing. Avoid prolonged and/or repeated contact with the skin. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid	
Odour:	strong, solvent-like	
Odour threshold:		No applicable information available.
Colour:	amber	
pH value:		not applicable
Melting point:		No applicable information available.
Boiling point:	approx. 111.11 - 251.11 °C	
Sublimation point:		No applicable information available.
Flash point:	18.33 °C	
Flammability:	Highly flammable.	
Lower explosion limit:	1.0 %(V)	
Upper explosion limit:	7.1 %(V)	
Vapour pressure:		The product has not been tested.
Density:	approx. 1.07 g/cm ³	(20 °C)
Relative density:		No applicable information available.
Vapour density:		Heavier than air.
Partitioning coefficient n- octanol/water (log Pow):		No applicable information available.
Thermal decomposition:	Vapours may form explosive mixture with air. No decomposition if stored and handled as prescribed/indicated.	
Viscosity, kinematic:		No applicable information available.
Solubility in water:		(20 °C) not soluble
Miscibility with water:		(20 °C) immiscible
Solubility (quantitative):		No applicable information available.
Solubility (qualitative):	No applicable information available.	
Evaporation rate:		No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

Safety Data Sheet

MasterSeal P 173 also PRIMER 733

Revision date : 2015/04/17
Version: 3.0

Page: 7/11
(50380469/SDS_GEN_US/EN)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions if stored and handled as prescribed/indicated.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

strong oxidizing agents

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

Vapours may form explosive mixture with air. No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Based on available Data, the classification criteria are not met.

Oral

No applicable information available.

Inhalation

No applicable information available.

Dermal

No applicable information available.

Assessment other acute effects

Assessment of STOT single:
Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause slight irritation to the eyes.

Safety Data Sheet

MasterSeal P 173 also PRIMER 733

Revision date : 2015/04/17
Version: 3.0

Page: 8/11
(50380469/SDS_GEN_US/EN)

Sensitization

Assessment of sensitization: Skin sensitizing effects were not observed in animal studies.
May cause sensitization by skin contact.

Aspiration Hazard

May also damage the lung at swallowing (aspiration hazard).

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: The substance may cause damage to the central nervous system after repeated ingestion of high doses. The substance may cause deafness after repeated inhalation.

Overexposure may cause liver and kidney toxicity.

Genetic toxicity

Assessment of mutagenicity: No mutagenic effect was found in various tests with bacteria, microorganisms and mammalian cell culture. The substance was not mutagenic in studies with mammals. Literature data.

Carcinogenicity

Assessment of carcinogenicity: Contains a suspect carcinogen.

Information on: ethylbenzene

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). NTP listed carcinogen

Reproductive toxicity

Assessment of reproduction toxicity: The results of animal studies gave no indication of a fertility impairing effect.

Teratogenicity

Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

Overexposure may cause:., unconsciousness, death, dilation of pupils, incoordination, lethargy, confusion, headache, dizziness, lacrimation

Safety Data Sheet

MasterSeal P 173 also PRIMER 733

Revision date : 2015/04/17
Version: 3.0

Page: 9/11
(50380469/SDS_GEN_US/EN)

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Acutely toxic for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Readily biodegradable (according to OECD criteria).

Bioaccumulative potential

Assessment bioaccumulation potential

Does not significantly accumulate in organisms.

Bioaccumulation potential

Bioconcentration factor: 90 (3 d), *Leuciscus idus melanotus*

Literature data.

Mobility in soil

Assessment transport between environmental compartments

The substance will rapidly evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is not expected.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statement has been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport

USDOT

Hazard class: 3

Packing group: II

Safety Data Sheet

MasterSeal P 173 also PRIMER 733

Revision date : 2015/04/17
Version: 3.0

Page: 10/11
(50380469/SDS_GEN_US/EN)

ID number: UN 1263
Hazard label: 3
Proper shipping name: PAINT

Sea transport

IMDG

Hazard class: 3
Packing group: II
ID number: UN 1263
Hazard label: 3
Marine pollutant: NO
Proper shipping name: PAINT

Air transport

IATA/ICAO

Hazard class: 3
Packing group: II
ID number: UN 1263
Hazard label: 3
Proper shipping name: PAINT

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Acute; Chronic; Fire; Sudden release of pressure

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
1000 LBS	100-41-4; 108-88-3	ethylbenzene; Toluene
100 LBS	1330-20-7; 584-84-9; 91-08-7	Xylene; toluene-2,4-diisocyanate; toluene-2,6-diisocyanate
10 LBS	56-23-5	tetrachloromethane

State regulations

CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NFPA Hazard codes:

Health : 2 Fire: 3 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2015/04/17

Safety Data Sheet

MasterSeal P 173 also PRIMER 733

Revision date : 2015/04/17
Version: 3.0

Page: 11/11
(50380469/SDS_GEN_US/EN)

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET