

# Safety Data Sheet

## MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB

Revision date : 2014/07/11  
Version: 2.0

Page: 1/11  
(55517382/SDS\_GEN\_US/EN)

### 1. Identification

**Product identifier used on the label**

**MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB**

**Recommended use of the chemical and restriction on use**

Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

**Details of the supplier of the safety data sheet**

Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

**Emergency telephone number**

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

**Other means of identification**

Chemical family: No data available.

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

**Classification of the product**

Asp. Tox.	1	Aspiration hazard
Flam. Liq.	3	Flammable liquid
Acute Tox.	3 (Inhalation - vapour)	Acute toxicity
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Resp. Sens.	1	Respiratory sensitization

# Safety Data Sheet

## MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB

Revision date : 2014/07/11  
Version: 2.0

Page: 2/11  
(55517382/SDS\_GEN\_US/EN)

Skin Sens.	1	Skin sensitization
Carc.	2	Carcinogenicity
Repr.	1B (fertility)	Reproductive toxicity
Repr.	1B (unborn child)	Reproductive toxicity
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

### Label elements

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H304	May be fatal if swallowed and enters airways.
H351	Suspected of causing cancer.
H360	May damage fertility. May damage the unborn child.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P260	Do not breathe mist or vapour.
P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P273	Avoid release to the environment.
P243	Take precautionary measures against static discharge.
P202	Do not handle until all safety precautions have been read and understood.
P284	[In case of inadequate ventilation] wear respiratory protection.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash with plenty of water and soap thoroughly after handling.
P242	Use only non-sparking tools.
P240	Ground/bond container and receiving equipment.

Precautionary Statements (Response):

# Safety Data Sheet

## MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB

Revision date : 2014/07/11  
Version: 2.0

Page: 3/11  
(55517382/SDS\_GEN\_US/EN)

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P341 + P311	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P352	IF ON SKIN (on hair): Wash with plenty of soap and water.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333 + P311	If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.
P362 + P364	Take off contaminated clothing and wash before reuse.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P337 + P311	If eye irritation persists: Call a POISON CENTER or doctor/physician.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.

#### Precautionary Statements (Storage):

P403 + P235	Store in a well-ventilated place. Keep cool.
P233	Keep container tightly closed.
P405	Store locked up.

#### Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

**According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

### Emergency overview

DANGER:

HARMFUL IF INHALED.

COMBUSTIBLE LIQUID.

SENSITIZATION CAN OCCUR IN SOME INDIVIDUALS, LEADING TO ASTHMA-LIKE SPASMS OF THE BRONCHIAL TUBES AND DIFFICULTY BREATHING. INDIVIDUALS WITH A HISTORY OF RESPIRATORY ILLNESS, ASTHMATIC CONDITIONS, EYE DAMAGE OR TDI SENSITIZATION SHOULD NOT BE EXPOSED TO THIS PRODUCT. TDI IS INCLUDED IN THE NTP ANNUAL REPORT ON CARCINOGENS. RESULTS FROM A TDI HEALTH STUDY INDICATE THAT OVEREXPOSURE TO A RESPIRATORY IRRITANT, RESULTING IN LOWER RESPIRATORY TRACT SYMPTOMS COULD INCREASE THE RISKS OF DEVELOPING ASTHMA-LIKE REACTIONS FROM SUBSEQUENT TDI EXPOSURE.

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Overexposure may cause CNS depression including headache, dizziness, nausea and loss of consciousness.

# Safety Data Sheet

## MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB

Revision date : 2014/07/11  
Version: 2.0

Page: 4/11  
(55517382/SDS\_GEN\_US/EN)

Irritating to eyes, respiratory system and skin.  
Avoid contact with the skin, eyes and clothing.

### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
8052-41-3	>= 10.0 - < 15.0 %	Stoddard solvent
5124-30-1	>= 10.0 - < 15.0 %	4,4'-methylenedicyclohexyl diisoncyanate
41556-26-7	>= 0.3 - < 1.0 %	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate
77-58-7	>= 0.3 - < 1.0 %	dibutyltin dilaurate
82919-37-7	>= 0.1 - < 0.2 %	Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

#### According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
8052-41-3	>= 10.0 - <= 30.0 %	Stoddard solvent
5124-30-1	>= 10.0 - <= 30.0 %	4,4'-methylenedicyclohexyl diisoncyanate
14807-96-6	>= 7.0 - <= 13.0 %	talc
1317-65-3	>= 1.0 - <= 5.0 %	Limestone
112945-52-5	>= 1.0 - <= 5.0 %	Silica

The product contains:

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
14807-96-6	>= 10.0 - < 15.0 %	talc
1317-65-3	>= 1.0 - < 3.0 %	Limestone

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

##### If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

##### If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

##### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

##### If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

# Safety Data Sheet

## MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB

Revision date : 2014/07/11  
Version: 2.0

Page: 5/11  
(55517382/SDS\_GEN\_US/EN)

---

### Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Wear a self-contained breathing apparatus.

### Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

# Safety Data Sheet

## MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB

Revision date : 2014/07/11  
Version: 2.0

Page: 6/11  
(55517382/SDS\_GEN\_US/EN)

For large amounts: Pump off product.

### 7. Handling and Storage

#### Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

#### Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: Steel with polyethylene liner

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

4,4'-methylenedicyclohexyl diisoncyanate	ACGIH TLV	TWA value 0.005 ppm ;
Stoddard solvent	OSHA PEL ACGIH TLV	PEL 500 ppm 2,900 mg/m <sup>3</sup> ; TWA value 100 ppm ;
talc	ACGIH TLV	TWA value 2 mg/m <sup>3</sup> Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
Limestone	OSHA PEL	PEL 5 mg/m <sup>3</sup> Respirable fraction ; PEL 15 mg/m <sup>3</sup> Total dust ;

#### Advice on system design:

No applicable information available.

#### Personal protective equipment

##### Respiratory protection:

Wear appropriate certified respirator when exposure limits may be exceeded.

##### Hand protection:

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

##### Eye protection:

Safety glasses with side-shields.

# Safety Data Sheet

## MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB

Revision date : 2014/07/11  
Version: 2.0

Page: 7/11  
(55517382/SDS\_GEN\_US/EN)

### Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

### General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	solvent-like	
Odour threshold:		No applicable information available.
Colour:	various colours	
pH value:		not applicable
Melting point:		No applicable information available.
Boiling point:	105.56 - 260 °C	
Sublimation point:		No applicable information available.
Flash point:	105 °F	(ASTM D3278)
Flammability:	Flammable.	
Lower explosion limit:	1.0 %(V)	
Upper explosion limit:	7.0 %(V)	
Vapour pressure:		The product has not been tested.
Density:	approx. 1.13 g/cm <sup>3</sup>	( 20 °C)
Relative density:		No applicable information available.
Vapour density:		Heavier than air.
Viscosity, dynamic:	29 mPa.s	( 40 °C) No applicable information available.
Viscosity, kinematic:	2,566 mm <sup>2</sup> /s	( 40 °C)
Solubility in water:		( 20 °C) slightly soluble
Miscibility with water:		( 20 °C) slightly soluble
Solubility (quantitative):		No applicable information available.
Solubility (qualitative):	No applicable information available.	
Evaporation rate:		No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

## 10. Stability and Reactivity

### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

### Corrosion to metals:

Corrosive effects to metal are not anticipated.

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

# Safety Data Sheet

## MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB

Revision date : 2014/07/11  
Version: 2.0

Page: 8/11  
(55517382/SDS\_GEN\_US/EN)

---

### Conditions to avoid

See MSDS section 7 - Handling and storage.

### Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

### Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Of high toxicity after short-term inhalation. Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact.

#### Oral

No applicable information available.

#### Assessment other acute effects

No applicable information available.

#### Sensitization

Assessment of sensitization: Sensitization after skin contact possible. The substance may cause sensitization of the respiratory tract. Studies in animals suggest that dermal exposure may lead to pulmonary sensitization. However, the relevance of this result for humans is unclear.

### Chronic Toxicity/Effects

#### Repeated dose toxicity

Assessment of repeated dose toxicity: The substance may cause damage to the upper respiratory tract after repeated inhalation, as shown in animal studies.

#### Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria.

#### Carcinogenicity

Assessment of carcinogenicity: Contains a suspect carcinogen.

#### Reproductive toxicity

Assessment of reproduction toxicity: Contains a suspected reproductive toxin.

#### Teratogenicity

Assessment of teratogenicity: Contains a suspect teratogen.



# Safety Data Sheet

## MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB

Revision date : 2014/07/11  
Version: 2.0

Page: 9/11  
(55517382/SDS\_GEN\_US/EN)

### Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

## 12. Ecological Information

### Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Aquatic toxicity

*Information on: 4,4'-methylenedicyclohexyl diisoncyanate*

*Assessment of aquatic toxicity:*

*Acutely toxic for aquatic organisms. Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible. The product has not been tested. The statement has been derived from the properties of the hydrolysis products.*

### Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O)

Not readily biodegradable (by OECD criteria).

### Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is expected.

### Additional information

Other ecotoxicological advice:

Do not release untreated into natural waters. Do not allow to enter soil, waterways or waste water channels. The product has not been tested. The statement has been derived from the properties of the individual components.

## 13. Disposal considerations

### Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

### Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

# Safety Data Sheet

## MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB

Revision date : 2014/07/11  
Version: 2.0

Page: 10/11  
(55517382/SDS\_GEN\_US/EN)

### 14. Transport Information

#### Land transport

USDOT

Hazard class: C  
Packing group: III  
ID number: UN 1263  
Hazard label: CBL  
Proper shipping name: PAINT, COMBUSTIBLE LIQUID (contains STODDARD SOLVENT)  
Classified as combustible liquid in containers greater than 119 gallons.

#### Sea transport

IMDG

Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Marine pollutant: NO  
Proper shipping name: PAINT

#### Air transport

IATA/ICAO

Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Proper shipping name: PAINT

### 15. Regulatory Information

#### Federal Regulations

##### Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Acute; Chronic; Fire

##### EPCRA 313:

##### CAS Number

5124-30-1

##### Chemical name

4,4'-methylenedicyclohexyl diisoncyanate

#### State regulations

##### State RTK

MA, NJ, PA  
MA, NJ, PA  
MA, NJ, PA  
MA, NJ, PA

##### CAS Number

8052-41-3  
5124-30-1  
14807-96-6  
1317-65-3

##### Chemical name

Stoddard solvent  
4,4'-methylenedicyclohexyl diisoncyanate  
talc  
Limestone

# Safety Data Sheet

## MasterSeal TC 225HT TB also SONOGUARD TOP COAT HT TB

Revision date : 2014/07/11  
Version: 2.0

Page: 11/11  
(55517382/SDS\_GEN\_US/EN)

MA, PA 112945-52-5 Silica

### CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

### NFPA Hazard codes:

Health : 2 Fire: 2 Reactivity: 1 Special:

### HMIS III rating

Health: 2<sup>a</sup> Flammability: 2 Physical hazard: 1

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations  
SDS Prepared on: 2014/07/11

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. END OF DATA SHEET