

Safety data sheet

PRIMER 733

Revision date : 2009/08/06
Version: 2.0

Page: 1/6
(30338186/SDS_GEN_CA/EN)

1. Substance/preparation and company identification

Company
BASF CANADA
100 Milverton Drive
Mississauga, ON L5R 4H1

24 Hour Emergency Response Information
CANUTEC (reverse charges): (613) 996-6666
BASF HOTLINE (800) 454-COPE (2673)

2. Hazardous ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Hazardous ingredients</u>
108-65-6	>= 10.0 - <= 30.0 %	1-methoxy-2-propylacetate
1305-78-8	>= 1.0 - <= 5.0 %	calcium oxide
1330-20-7	>= 1.0 - <= 5.0 %	Xylene
9017-09-8	>= 7.0 - <= 13.0 %	1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 1,3-diisocyanatomethylbenzene
108-88-3	>= 30.0 - <= 60.0 %	Toluene

3. Hazard identification

Emergency overview

FLAMMABLE. IRRITANT. Irritating to eyes and skin.
Contains a suspect teratogen.

Potential health effects

Acute toxicity:

Information on: ethylbenzene

Of moderate toxicity after short-term inhalation.

Virtually nontoxic after a single skin contact.

Of low toxicity after single ingestion.

Information on: Xylene

Of moderate toxicity after short-term inhalation.

Of moderate toxicity after short-term skin contact.

EU-classification

High concentrations in the air may cause narcosis.

Virtually nontoxic after a single ingestion.

Information on: Toluene

Vapours may cause drowsiness and dizziness.

Irritation:

Irritating to eyes, respiratory system and skin.

Information on: calcium oxide

Corrosive! Damages skin and eyes. Information on: ethylbenzene

Safety data sheet

PRIMER 733

Revision date : 2009/08/06
Version: 2.0

Page: 2/6
(30338186/SDS_GEN_CA/EN)

*Not irritating to the eyes. Skin contact causes irritation. Information on: Toluene
Skin contact causes irritation. Eye contact causes irritation.*

Sensitization:

There is no evidence of a skin-sensitizing potential.

Repeated dose toxicity:

Overexposure may cause CNS depression including headache, dizziness, nausea and loss of consciousness.

Information on: Xylene

Overexposure may cause liver and kidney toxicity.

The substance may cause damage to the central nervous system after repeated ingestion of high doses.

Information on: Toluene

Repeated inhalation exposure may affect certain organs.

Potential environmental effects

Aquatic toxicity:

No data available concerning aquatic toxicity.

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

5. Fire-Fighting Measures

Flash point:	18.33 °C
Lower explosion limit:	1.0 %(V)
Upper explosion limit:	7.1 %(V)

Suitable extinguishing media:

foam, water spray, dry extinguishing media, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Hazards during fire-fighting:

carbon monoxide, carbon dioxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Safety data sheet

PRIMER 733

Revision date : 2009/08/06
Version: 2.0

Page: 3/6
(30338186/SDS_GEN_CA/EN)

Further information:

Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions:

Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Sources of ignition should be kept well clear. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Cleanup:

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

7. Handling and Storage

Handling

General advice:

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Protection against fire and explosion:

Keep away from heat. Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

Storage

General advice:

Keep only in the original container in a cool, well-ventilated place. Protect from direct sunlight.

Storage incompatibility:

General: Segregate from metals. Segregate from lyes. Segregate from oxidants. Segregate from foods and animal feeds.

8. Exposure controls and personal protection

Components with workplace control parameters

Toluene	OSHA	TWA value 200 ppm ; CLV 300 ppm ; max. conc. 500 ppm ;
	ACGIH	TWA value 20 ppm ;
calcium oxide	OSHA	PEL 5 mg/m3 ;
	ACGIH	TWA value 2 mg/m3 ;
Xylene	OSHA	PEL 100 ppm 435 mg/m3 ;
	ACGIH	TWA value 100 ppm ; STEL value 150 ppm ;
ethylbenzene	OSHA	PEL 100 ppm 435 mg/m3 ;
	ACGIH	TWA value 100 ppm ; STEL value 125 ppm ;

Personal protective equipment

Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Safety data sheet

PRIMER 733

Revision date : 2009/08/06
Version: 2.0

Page: 4/6
(30338186/SDS_GEN_CA/EN)

Hand protection:

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	liquid	
Odour:	strong, solvent-like	
Odour threshold:	No data available.	
Colour:	amber	
pH value:		not applicable
Boiling point:	111.11 - 251.11 °C	
Vapour pressure:		No data available.
Density:	1.07 g/cm3	
Vapour density:		Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):		No data available.
Solubility in water:		slightly soluble

10. Stability and Reactivity

Substances to avoid:

strong acids, strong bases, strong oxidizing agents

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

Decomposition products:

Thermal decomposition products: carbon oxides

Oxidizing properties:

not fire-propagating

11. Toxicological information

Chronic toxicity

Carcinogenicity:

Information on: ethylbenzene

IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

NTP listed carcinogen

Safety data sheet

PRIMER 733

Revision date : 2009/08/06
Version: 2.0

Page: 5/6
(30338186/SDS_GEN_CA/EN)

Developmental toxicity/teratogenicity:

Information on: Xylene

A teratogenic potential cannot be excluded.

Information on: Toluene

Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Experiences in humans:

According to experience, the product is considered to be harmless to health if used in the correct manner.

Other Information:

The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

Environmental toxicity

Other ecotoxicological advice:

Do not allow to enter soil, waterways or waste water channels. According to experience, the material has no harmful effect on the environment.

13. Disposal considerations

Waste disposal of substance:

Do not discharge substance/product into sewer system.
Dispose of in accordance with local authority regulations.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport

TDG

Hazard class:	3
Packing group:	II
ID number:	UN 1263
Hazard label:	3
Proper shipping name:	PAINT (contains TOLUENE)

Sea transport

IMDG

Hazard class:	3
Packing group:	II
ID number:	UN 1263
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	PAINT (contains TOLUENE)

Safety data sheet

PRIMER 733

Revision date : 2009/08/06
Version: 2.0

Page: 6/6
(30338186/SDS_GEN_CA/EN)

Air transport

IATA/ICAO

Hazard class: 3
Packing group: II
ID number: UN 1263
Hazard label: 3
Proper shipping name: PAINT (contains TOLUENE)

15. Regulatory Information

Federal Regulations

Registration status:

DSL, CA released / listed

WHMIS classification: D1B: Materials Causing Immediate and Serious Toxic Effects - Toxic material
D2A: Materials Causing Other Toxic Effects - Very toxic material
D2B: Materials Causing Other Toxic Effects - Toxic material
B2: Flammable Liquid



THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

16. Other Information

Local Contact Information
BASF Construction Chemicals
bcc_prps@basf.com

END OF DATA SHEET