

# PRODUCT SPECIFICATIONS

## 8' Web Retractor

#8262

### Features

- 8' working length
- Inertial brake system
- 1 Zinc-treated steel snap hook; 1 eye-and-jaw swivel and 1 connecting carabiner
- Steel frame with PVC cover and polyester constituent line

### Material Specifications

- Webbing:** 1-3/4" polyester webbing - Min. 5,000 lbs tensile strength
- Connectors:** Alloy Steel; Min. 5,000 lbs. tensile strength
- Connector Gates:** Alloy Steel; Min. 3600 lbs. front and side load

### Performance Specifications

- Tensile Strength:** Min. 3,000 lbs.
- Max. Capacity:** 310 lbs.
- Max. Freefall:** 2 feet
- Average Arrest Force:** 1,350 lbs or less
- Max. Arrest Distance:** 24 inches or less

### Relevant Standards

- OSHA:** CFR1926.502, CFR1910.66
- ANSI:** ANSI Z359.14 – 2012, Class A

### Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- For use in overhead applications - **maximum allowable freefall = 2 feet!**



# Best Materials®

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.