

Distributed by: **BEST MATERIALS®**  
 Ph: 800-474-7570, 602-272-8128 Fax: 602-272-8014  
[www.BestMaterials.com](http://www.BestMaterials.com) Email: [Sales@BestMaterials.com](mailto:Sales@BestMaterials.com)

## GENERAL PURPOSE

For Concrete, Block, Brick, Natural Stone, Refractory Material, Soft Stone, Sand Stone.

**GOOD**

**BETTER**

**BEST**

### P2 PRO-V™



10MM RIM



PT. NUMBER	SPECS	MAX RPM
PV004S	4 x .080 x 20mm, 5/8	13,700
PV045S	4-1/2 x .080 x 7/8, 5/8	13,300
PV005S	5 x .080 x 7/8, 5/8	12,200
PV007S	7 x .090 x 7/8, $\phi$ , 5/8	8,500
PV010S	10 x .095 x 7/8, $\phi$ , 5/8	6,100

### P4™



12MM RIM



PT. NUMBER	SPECS	MAX RPM
DIA004CP	4 x .070 x 20mm, 5/8	13,700
DIA045CP	4-1/2 x .080 x 7/8, 5/8	13,300
DIA005CP	5 x .080 x 7/8, 5/8	12,200
DIA007CP	7 x .080 x 7/8, $\phi$ , 5/8	8,500
DIA008CP	8 x .080 x $\phi$ , 5/8	6,800

### P5™



12MM RIM



PT. NUMBER	SPECS	MAX RPM
DIA04CSP	4 x .070 x 20mm, 5/8	13,700
DIA45CSP	4-1/2 x .080 x 7/8, 5/8	13,300
DIA05CSP	5 x .080 x 7/8, 5/8	12,200
DIA07CSP	7 x .080 x 7/8, $\phi$ , 5/8	8,500
DIA08CSP	8 x .080 x $\phi$ , 5/8	6,800

## CONCRETE AND MASONRY

For Concrete, Reinforced Concrete, Masonry, Brick, Block, Paver Bricks, Hard Brick, Refractory Material, Soft Stone, Sand Stone.

### P1 EXV™



12MM RIM



PT. NUMBER	SPECS	MAX RPM
EXV1212XL	12 x .125 x 1, 20mm	6,300
EXV1212XL2	12 x .125 x 20mm	6,300
EXV1412XL	14 x .125 x 1, 20mm	5,400
EXV1412XL2	14 x .125 x 20mm	5,400

### P2 PRO-V™



12MM RIM



PT. NUMBER	SPECS	MAX RPM
PV1212XL	12 x .125 x 1, 20mm	6,300
PV1212XL2	12 x .125 x 20mm	6,300
PV1412XL	14 x .125 x 1, 20mm	5,400
PV1412XL2	14 x .125 x 20mm	5,400
PV1612XL	16 x .125 x 1, 20mm	4,700
PV1812XL	18 x .125 x 1	3,400
PV2014XL	20 x .140 x 1	3,000

### P4™



15MM RIM



PT. NUMBER	SPECS	MAX RPM
LW1008CP	10 x .080 x $\phi$ , 5/8	6,100
LW1008CPA	10 x .080 x 1	6,100
LW1211CP	12 x .110 x 1, 20mm	6,300
LW1211CP2	12 x .110 x 20mm	6,300
LW1212CP	12 x .125 x 1, 20mm	6,300
LW1212CP2	12 x .125 x 20mm	6,300
LW1411CP	14 x .110 x 1, 20mm	5,400
LW1411CP2	14 x .110 x 20mm	5,400
LW1412CP	14 x .125 x 1, 20mm	5,400
LW1412CP2	14 x .125 x 20mm	5,400
LW1612CP	16 x .125 x 1, 20mm	4,700
LW1612CP2	16 x .125 x 20mm	4,700
LW1812CP	18 x .125 x 1	3,400
LW2014CP	20 x .142 x 1	3,000

### P5™



15MM RIM



PT. NUMBER	SPECS	MAX RPM
LW1212CSP	12 x .125 x 1, 20mm	6,300
LW1212CSP2	12 x .125 x 20mm	6,300
LW1412CSP	14 x .125 x 1, 20mm	5,400
LW1412CSP2	14 x .125 x 20mm	5,400
<b>NEW!</b> LW1612CSP	16 x .125 x 1, 20mm	4,700
<b>NEW!</b> LW1814CSP	18 x .140 x 1	3,400
<b>NEW!</b> LW2014CSP	20 x .140 x 1	3,000