



FILL YOUR SEALANT AND INSULATION  
NEEDS WITH FROTH-PAK™  
POLYURETHANE FOAM SYSTEMS

FROTH-PAK™ Polyurethane Foam Systems are ready to quickly and professionally fill your needs. FROTH-PAK™ foam is a two-component, quick-cure polyurethane foam that fills cavities, penetrations and cracks for air sealing, insulation, sound damping, structural stabilization and more.

Designed for mobility and ease of use, FROTH-PAK™ foam is an ideal choice for penetrations greater than 2".\* FROTH-PAK™ foam ...

- Adheres to many surfaces, including wood, metal, glass and most plastics
- Becomes tack-free in less than a minute
- Cures in minutes, depending on temperature, foam thickness and specific nozzle
- Comes with flexible, pre-attached hoses for quicker start-up
- Kits have a temperature indicator to help assure maximum product performance

### ADVANTAGES OF FROTH-PAK™ SYSTEMS

- All-in-one insulation and air sealant that helps prevent air infiltration, moisture intrusion and much more
- Chemically cured, reducing curing time
- Patented anti-crossover nozzles – widest selection available in the industry today
- Self-contained kits and refillable canisters
- Variety of convenient sizes for smaller jobs and larger use demands
- Low maintenance and parts replacement costs
- Portable with no mixing, set-up or warm-up necessary



### SPRAY ACCURACY IN ACTION



The lightweight INSTA-FLO™ Dispensing Spray Gun is sturdy, reusable and features a comfort-designed grip. With the INSTA-FLO™ gun, flow rates can be easily controlled and output precisely metered to reduce overspray and waste.

Accurate and economical application of FROTH-PAK™ foam is now even easier with Dow's distinct anti-crossover nozzles. Some of the special features that make these nozzles industry favorites include:

- Patented nozzle design – helps eliminate plugged hoses
- Several nozzle types – offer a variety of outputs and spray patterns
- Side wing design – provides quick gun attachment
- Clear dispensing tips – easily identifies used nozzles

®™Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

\*For areas less than 2", Dow recommends GREAT STUFF PRO™ Gaps & Cracks Insulating Foam Sealant.



▲ Metal carrying handles and banding around cylinders help increase portability.

▶ Temperature indicator helps applicator optimize product performance.

For Best Results:  
Spray Above 75° F  
Store Below 120° F

95	35
85	29
75 °F	24 °C
65	18
55	13

Green: Exact Temperature  
Tan: Range Above Actual  
Blue: Range Below Actual

Below are just a few examples of the possible uses for FROTH-PAK™ systems.

#### AGRICULTURE

- Light control and insulation in poultry houses
- Silo and grain storage bin sealant
- Pest control

#### AIR SEALING

- Roof/wall junctures
- New and retrofit construction
- Odor control

#### ASBESTOS ABATEMENT

- Crack, void and hole sealant
- Sealant for irregular voids
- Sealant to maintain negative air pressure

#### COLD STORAGE

- Floor seams
- Fluted roof decks
- Wall-to-wall intersects

#### HEATING, VENTILATING, AIR CONDITIONING

- Pipe (including geothermal) insulator
- HVAC duct sealant

#### INSULATION

- Stud wall cavity fill
- Ceiling/floor/wall penetrations sealant

#### POOL AND SPA

- Insulation repair
- Structural support
- Sound damping

#### PLUMBING

- Sealant around copper or PVC pipes and penetrations
- Bathtub/shower base stabilizer
- Fiberglass bathtub repair

#### OTHER

- Archaeology fieldwork
- Elevators, sound damping

Expand your success with FROTH-PAK™ Polyurethane Foam Systems.

For more information on FROTH-PAK™ products, visit [www.dowbuildingsolutions.com](http://www.dowbuildingsolutions.com) or contact a Dow representative at 1-866-583-BLUE (2583).

For Technical Information: 1-866-583-BLUE (2583) . For Sales Information: 1-800-232-2436  
THE DOW CHEMICAL COMPANY . Dow Building Solutions . 200 Larkin . Midland, MI 48674

[www.dowbuildingsolutions.com](http://www.dowbuildingsolutions.com)

NOTICE: No freedom from any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries or regions. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean The Dow Chemical Company and its consolidated subsidiaries unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

COMBUSTIBLE: FROTH-PAK™ Foam Sealant is combustible and may constitute a fire hazard. Do not expose foam to flame or temperatures above 240°F. For more information, consult MSDS, call Dow at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400.

FROTH-PAK™ Polyurethane Spray Foam contains isocyanate, hydrofluorocarbon blowing agent and polyol. Read the instructions and Material Safety Data Sheets carefully before use. Wear protective clothing, gloves, goggles or safety glasses, and proper respiratory protection. Supplied air or an approved air-purifying respirator equipped with an organic vapor sorbent and a P100 particulate filter may be required to maintain exposure levels below ACGIH, OSHA, WEEL or other applicable limits. Provide adequate ventilation. Contents under pressure.

GREAT STUFF PRO™ Insulating Foam Sealants contain isocyanate and a flammable blowing agent. Read the label and Material Safety Data Sheet carefully before use. Eliminate all sources of ignition before use. Wear gloves, and goggles or safety glasses. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

